

Dell 1510X

Multimedia Projector



High brightness of 3,500 ANSI Lumens (Max.)

- Optimal brightness for lights-on presentations

Excellent contrast ratio of 2100:1 typical (Full On/Full Off)

- Complements brightness and helps deliver crisp and sharp pictures and text

Native XGA (1024x768) resolution

- Designed to deliver up to 63% more pixels than SVGA (800x600)¹

Crestron Roomview compatible

- Enjoy an optional multi-user resource management program which offers real-time facility-wide monitoring, management and reporting of AV resources/devices

Wide connectivity options

- Dual VGA-In
 - Two presenters in a single session can transition smoothly between one another to help prevent inherent interruptions or time-lag
- HDMI / Composite video / S-Video
 - Visual / audio flexibility and performance for work or digital entertainment
- RJ45 port
 - Set up email alerts and help manage the 1510X over your network
- Integrated microphone port
 - lends support to a conducive class-centric delivery

Supports closed captioning²

- Visual transcription of a program's audio portion on the screen

3D capability



- Enjoy total immersion and make your presentations pop when you leverage 3D content
- Active 3D goggles with DLP Link, 3D player software application, HDMI/VGA cable, 3D content, PC/laptop with a 120Hz signal output quad buffered graphics card are required and sold separately

Standard warranty and service

2-Year Advanced Exchange Service⁵ and Limited Hardware Warranty⁶ for projector unit with 1-year projector lamp coverage • Includes 24/7 online technical support and telephone technical support⁷

¹Resolution comparison based on SVGA pixel count of 480,000 (800 horizontal x 600 vertical) and XGA pixel count of 786,432 (1024 horizontal x 768 vertical).

²Closed captioning feature can be enabled only via composite / S-Video inputs.

³Lamp life rating is typical time for lamp lumens to diminish by 50% based on lab testing. Actual operating life will vary and be less under conditions including high use, temperature, dust, or abrupt power-off environments.

⁴Options from Dell Custom Factory Integration (CFI), Software and Peripherals (S&P) and customer kits may not be EU RoHS-compliant. For more information, please visit www.dell.com/recycling and www.dell.com/environment.

⁵Replacement system or part dispatched, if necessary, following phone-based troubleshooting, in advance of receipt of returned defective part or system. Availability varies.

⁶For a copy of limited hardware warranty, write Dell USA L.P., Attn: Warranties, One Dell Way, Round Rock, TX 78682 or visit www.dell.com/service descriptions.

⁷Operating hours for telephone support may vary from country to country. Kindly contact your local Dell representative for exact availability in your country.

Dell cannot be responsible for errors and omissions in typography or photography. DLP[®] and the DLP[®] logo are registered trademarks and BrilliantColor[™] and DarkChip3[™] are trademarks of Texas Instruments. Crestron Roomview[®] and the Crestron Roomview[®] logo are registered trademarks of Crestron Electronics, Inc. Other trademarks or trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Dell disclaims proprietary interest in the marks and names of others. Reproduction of this material in any manner whatsoever without the expressed written permission from Dell Inc. is strictly forbidden.

Dell™ 1510X Multimedia Projector

Display	
Light valve	Single-chip 0.55" XGA S450 DMD, DarkChip3 [™] technology
Brightness	3,500 ANSI Lumens (Max.)
Throw ratio	1.6 (wide) ~ 1.92 (tele)
Projection lens	F-Stop: F/2.4 ~ 2.66; Focal length, f=18.2 ~ 21.8 mm; 1.2x manual zoom lens
Projection screen size	0.78m ~ 7.79m (30.8" ~ 307") (diagonal)
Projection distance	1.2m ~ 10m (3.94 ft ~ 32.81 ft)
Lamp	Philips 225W user-replaceable lamp of up to 3,000 hours ³ in Normal mode or up to 4,000 hours ³ in Eco-Mode
Resolution	
Number of pixels	1024 x 768 (XGA)
Contrast ratio	2100:1 Typical (Full On/Full Off)
Displayable colors	1.07 billion colors
Video compatibility	Composite video/S-Video: NTSC (J, M, 4.43), PAL (B, D, G, H, I, M, N, Nc, 60), SECAM (B, D, G, K, K1, L) Component video via VGA and HDMI: 1080i/p, 720p, 576i/p, 480i/p
Power	
Power supply	Universal AC 100-240V 50-60Hz with PFC input
Power consumption	Normal mode 287W ± 10% @ 110Vac (network on) Eco-Mode 219W ± 10% @ 110Vac (network on) Power-saving mode ≤15W (network on, fan speed at minimum) Standby mode ≤0.5W (network off, VGA OUT off)
Sound	
Audio / noise level	8W speaker / 35 dB(A) in Normal mode, 32 dB(A) in Eco-Mode
Size and weight	
Projector (WxHxD)	296.5mm x 87.9mm x 202mm ± 1mm (11.68" x 3.46" x 7.96" ± 0.04")
Weight	2.36 kg (5.2 lbs)
Compliance	
Uniformity	85% typical (Japan - JBMA)
Environmental	EU RoHS compliant ⁴ Yes Operating temperature 5°C to 35°C (41°F to 95°F), humidity: 80% max. Storage temperature 0°C to 60°C (32°F to 140°F), humidity: 90% max. Shipping temperature -20°C to 60°C (-4°F to 140°F), humidity: 90% max.
Connectivity	
I/O ports	Power 1x AC power socket (3-pin - C14 inlet) VGA input 2x 15-pin D-Sub connector (blue), VGA-A & VGA-B, for analog RGB/component input signals VGA output 1x 15-pin D-Sub connector (black) for VGA-A loop-through S-Video input 1x standard 4-pin mini-DIN S-Video connector for Y/C signal Composite video input 1x yellow RCA jack for CVBS signal HDMI input 1x HDMI connector for supporting HDMI 1.3 (HDCP compliant) Analog audio input 1x 3.5mm stereo mini phone jack (blue), 1x pair of RCA connector (red/white) Variable audio output 1x 3.5mm stereo mini phone jack (green) USB port 1x USB-B slave for remote support RS232 port 1x mini-DIN 6-pin for RS232 communication RJ45 port 1x RJ45 connector for control of projector through network Microphone 1x 3.5mm stereo mini phone jack (pink)
Package contents	
Contents	Dell 1510X projector, carrying case, power cord, VGA cable, remote control and 2x AAA battery, CD User's Guide and documentation