



The power to do more

Reliable color printer with enhanced print performance and robust security features



Dell™ Color Printer - C2660dn

Meet demanding printing needs reliably with the C2660dn printer. This robust printer with a high duty cycle¹ delivers brilliant color prints at fast speeds, and comes with security features to safeguard your data. Built-in Gigabit Ethernet connectivity enables fast network transfers for greater efficiency, while the optional External Wireless Adapter gives you freedom to print from virtually anywhere within the wireless network².

Designed with the environment in mind, this energy efficient printer features low melt toner technology to help reduce power consumption and save on total cost of ownership. The printer also includes a duplexer for automatic two-sided printing.

Get excellent performance and outstanding value while consuming fewer resources with the Dell Color Printer – C2660dn.



¹ Duty cycle is defined as the maximum number of imaged outputs a device could deliver in a month. This metric provides a comparison of robustness in relation to other Dell printers and multifunction printers.
² The printer and the device must be connected on the same network.



Print at fast speeds of up to 28ppm¹ (letter) / 27ppm¹ (A4)



Protect your data with embedded security features



Save on printing costs with optional high yield toner cartridges



Reduce paper consumption with default two-sided printing

Stellar performance and ease of use

- Get high quality color and mono prints at fast print speeds of up to 28 pages per minute (ppm) (letter) / 27ppm (A4)¹.
- Handle large print loads reliably with a monthly duty cycle² of up to 50,000 pages.
- Easily navigate printer functions with the 4-line LCD user interface and 10-digit numeric pad.
- Print directly from a variety of mobile devices with:
 - Dell Mobile Print app (for Android™ mobile devices)³
 - AirPrint (for iOS mobile devices)⁴
 - Google Cloud Print™
- Get fast connection to your network with Gigabit Ethernet connectivity.
- Connect to a wireless network with the optional External Wireless Adapter (sold separately).

Robust security and simplified manageability

- Safeguard sensitive prints from remaining uncollected with Secure Print, which requires users to enter a 4-digit PIN on the printer before releasing the prints.
- Secure network data transmission with Secure Socket Layer (SSL) and Internet Protocol Security (IPSec).
- Simplify driver deployment and setting changes with Dell Open Printer Driver (OPD).
- Monitor, manage and create reports for the Dell printers on your network with the Dell OpenManage™ Printer Manager v2 (OPMPM).

Exceptional value and long-term savings

- Benefit from a low cost per page with optional high yield toner cartridges.
- Save on maintenance costs with standard 1-year Limited Warranty⁵ and 1-year Advance Exchange Service after Remote Diagnosis⁶. Dell printers base and extended warranty also cover the fuser maintenance kit within the warranty period.
- Get outstanding value with a low Total Cost of Ownership (up to 22% lower than that of HP LaserJet Pro M451dn⁷ over a period of 3 years).

Environmentally-conscious design

- Designed with the environment in mind, the C2660dn is EPEAT® registered in the US and Canada⁸, ENERGY STAR® qualified⁹ and RoHS compliant¹⁰.
- Save on energy costs and reduce carbon dioxide emissions with Dell low melt toners, which use less power and shorten first print out time.
- Reduce paper consumption with the default two-sided print setting. The C2660dn also supports printing on recycled, renewable content, and chlorine-free paper.
- Activate the Toner Save mode to reduce toner usage on each printed page.
- Reduce power consumption by activating the Power Save button to put the printer into sleep mode.



1. Measured in accordance with ISO IEC 27434/75 methodology. Actual print speeds will vary with use.
 2. Duty cycle is defined as the maximum number of imaged outputs a device could deliver in a month. This metric provides a comparison of robustness in relation to other Dell printers and multifunction printers.
 3. The printer and the mobile device must be connected to the same network.
 4. AirPrint-enabled printers work with iPad, iPhone (3GS or later), and iPod touch (3rd generation or later) running iOS 4.2 or later.
 5. For a copy of Limited Hardware Warranty, write Dell USA LP, Attn: Warranties, One Dell Way, Round Rock, TX 78682 or visit dell.com/warranty.
 For warranty information for other countries, see website: dell.com/servicecontracts and then select the country.
 6. Remote Diagnosis is the determination by online/phone technician of cause of issue; may involve customer access to inside of system and multiple or extended sessions. If issue is covered by Limited Hardware Warranty (dell.com/warranty) and not resolved remotely, technician and/or part will be dispatched, usually within 1 business day following completion of Remote Diagnosis. Availability varies. Other conditions apply.
 7. HP prices for hardware and consumables are taken from www.hp.com as of 27 Aug 2013.
 8. EPEAT registration varies by country. See www.epeat.net for registration status by country.
 9. For details on energy efficiency of ENERGY STAR® qualified products, refer to: www.energystar.gov
 10. Meets the requirements of the EU RoHS Directive 2011/65/EU on the Restriction of the use of certain Hazardous Substances (RoHS).

Consumables		Warranty and service options	
Ship-with toner cartridge capacity¹	1,200 pages (black) 1,200 pages (color - CMY)	Standard service	1 Year Limited Hardware Warranty ² and 1 Year Advanced Exchange Service ³ after Remote Diagnosis ⁴
Standard capacity toner cartridge¹	1,200 pages (black) 1,200 pages (color - CMY)		
High capacity toner cartridge¹	3,000 pages (black) 4,000 pages (color - CMY)		
Extra high capacity cartridge¹	6,000 pages (black)		
Imaging Drum	55,000 page yield (black) 55,000 page yield (color)		
Fuser unit	100,000 pages	Service upgrade options	<ul style="list-style-type: none"> • 2 - 5 Years Advanced Exchange Service³ after Remote Diagnosis⁴ • 1 - 5 Years On-site Service after Remote Diagnosis⁴ • 1 - 5 Years Advanced Exchange ProSupport™⁵ after Remote Diagnosis⁴ • 1 - 5 Years On-site ProSupport™⁵ after Remote Diagnosis⁴ • 1 - 5 Years On-site with On-site Resolution ProSupport™⁵

Accessories



Optional 550-sheet lockable input tray

Increase the input capacity of the C2660dn printer to 950 sheets with the optional 550-sheet input tray.



External Wireless Adapter

Connect the C2660dn printer to WiFi network with the optional wireless adapter.

Product Specifications

Physical specifications	Dimensions (W x D x H)	Printer: 17.3" x 19.1" x 14.9" (439 mm x 485 mm x 379 mm) Shipping: 22.4" x 27" x 20.7" (570 mm x 686 mm x 526 mm)
	Weight	Printer: 56.4 lbs (25.6 kg); Shipping: 67.2 lbs (30.5 kg)
	Operating environment	Temperature: 41°F to 90°F (5°C to 32°C); Relative humidity: 15% to 85% RH, non-condensing; Altitude: ≤ 10,170 ft (3,100 m)
	Storage	Temperature: 32°F to 95°F (0°C to 35°C); Relative humidity: 5% to 90% RH, non-condensing; Altitude: ≤ 10,170 ft (3,100 m)
	Acoustics (Pressure/Power)	Printing: 53dB ⁶ / 6.92B ⁶ ; Standby: 25.5dB ⁶ / 4.3B ⁶
Power specifications	Voltage	120 VAC model 110 to 127 VAC, 50 Hz ± 3 Hz/60 Hz ± 3 Hz
	Power consumption	Printing mode: 705 W Ready mode: 58 W at 110 VAC Power saver mode: 9.5 W (Sleep), 2 W (Deep sleep)
	Typical Energy Consumption (TEC)⁷	2.4 kWh
	Environmental compliance	ErP Lot 4 and 6, RoHS-compliant ⁸ , ENERGY STAR [®] qualified ⁹ , Blue Angel (Germany) UZ171, WEEE, GS Mark (Germany), registered EPEAT [®] in US and Canada ¹⁰
	Connectivity	Standard interfaces High speed USB 2.0 client port, Gigabit Ethernet port, Wireless Port (for optional dongle)
Operating Systems	Windows	Microsoft [®] Windows [®] 8 (32/64 bit), Windows 8 RT, Windows 7 (32/64 bit), Windows Vista (32/64 bit), Windows Server 2008 R1 & R2, Windows 8.1 (available in Nov, 2013), Windows XP (32/64 bit), Windows 2003, Windows Cluster Server Environment, Windows 2012 Server
	Macintosh	Macintosh OS 10.5 to 10.8
	Others	SUSE [®] Linux Enterprise Desktop 10, 11; Red Hat Linux Enterprise Desktop 5, 6; Nowell [®] Netware Support; SAP R/3 Release 4.6B onwards; Citrix [®] Presentation Server™ 4.5, Citrix XenApp 5.0 to 6.5
Supported languages	English, French, German, Italian, Spanish, Dutch, Danish, Norwegian and Swedish	
Product certifications	Safety certifications	IEC/EN60950-1:2005 2nd edition (International); EN60950-1:2006 2nd edition; IEC60825-1 (Laser); SEMKO; CE Mark (EU); cTUVus; FDA/DHHS (21CFR, Chapter 1, Subchapter J)
	Other certifications	CE mark (EU countries) EMC/Safety Standard; EN55022:2006 + A1:2007 Class B; EN61000-3-2:2006; EN 61000-3-3:1995+A1:2001+A2:2005; EN55024:1998+A1:2001+A2:2003; FCC CFR Title 47, Part 15 Class B (USA); ICES-003, Issue 4 (Canada); WHQL, Citrix, SAP, Novell, USB, WiFi, Google Cloud Print, Apple Airprint
Contents in box	Dell Color Printer – C2660dn, Ship-With Black Cartridge and Color (Cyan, Magenta, Yellow) Cartridges (1,200-page yield ¹), Power cord, Quick Setup Guide, Software and Instructions CD, Important Information	

1. Toner yield based on testing in accordance with ISO/IEC 19798. Yields vary with usage and environmental conditions.

2. For a copy of Limited Hardware Warranty, write Dell USA LP, Attn: Warranties, One Dell Way, Round Rock, TX 78682 or visit dell.com/warranty. For warranty information on other countries, see website: dell.com/servicecontracts and then select the country.

3. Replacement part/unit dispatched, if needed, following completion of phone/online diagnosis. Fee charged for failure to return defective unit. Availability varies. Other conditions apply.

4. Remote Diagnosis is the determination by online/phone technician of cause of issue; may involve customer access to inside of system and multiple or extended sessions. If issue is covered by Limited Hardware Warranty (dell.com/warranty) and not resolved remotely, technician and/or part will be dispatched, usually within 1 business day following completion of Remote Diagnosis. Availability varies. Other conditions apply.

5. Availability and terms of Dell Services vary by region. For more information, visit dell.com/servicesdescriptions.

6. Tested in accordance with ISO 7779 and reported in accordance with ISO 9296. Acoustics - Declared noise emission values of computer and business equipment

7. For the Typical Energy Consumption value calculation details please visit: www.energystar.gov/ia/products/fap/IE_TEC_Test_Procedure.pdf

8. Meets the requirements of the EU RoHS Directive 2011/65/EU on the Restriction of the use of certain Hazardous Substances (RoHS).

9. For details on energy efficiency of ENERGY STAR[®] qualified products, refer to: www.energystar.gov

10. EPEAT registration varies by country. See www.epeat.net for registration status by country.

Product Specifications

Printer specifications	Print speed (Mono/Color)	
	Simplex (600 x 600 dpi)	Up to 28 ppm ¹ (letter) and 27 ppm ¹ (A4)
	Duplex (600 x 600 dpi)	Up to 18 ppm ¹ (letter/A4)
	First page out time from Ready state	Less than or equals to 14 seconds (simplex)
	Print resolution	600 x 600 dpi (up to 2400 dpi image quality)
	Operation panel	LCD: 4 Lines Bitmap based Mono LCD, font scalable; 10-key Numeric pad; Viewing Area: 1.97" (49.97 mm) (W) x 0.8" (19.17 mm)(L); Backlight: White backlight; Status LED: 1 LED (combination "Data Green/Error Amber") Power Saver Button (Light on/off)
	Print language	
	Printer Driver Language	PCL6, PostScript™ 3, XPS
	Printer data stream (FW)	PCL5C, PCL 6 (PCLXL 2.1), PostScript 3
	Fonts	HP PCL® 6 Emulation: 80 scalable fonts PostScript® Level 3 : 80 scalable fonts
	Processor speed	525 MHz
	Memory	512 MB ²
	Maximum duty cycle	Up to 50,000 pages per month ³
	Recommended monthly print volume	750 - 3,500 pages per month
Mobile printing support	Dell Mobile Print ⁴ (Android™ OS), AirPrint ⁵ (iOS), Google Cloud Print	
Printer management	Dell Printer Configuration Web Tool, Dell ColorTrack 2.2, Dell Toner Management System, Dell Open Print Driver (OPD), Dell OpenManage™ Printer Manager v2 (OMPM)	
Security features	Print Job Management	Secure Print with 4 Digit Pin, Virtual Mail Box, Print Job disable/enabling scheduling
	Network Authentication	SNMP V3
	Data Encryption	Ipssec (Ikev1)/Pre-shared key
	Access Control Management	Embedded Web Server access control of Enable/Disable of network port & Protocol , printer settings & report access, Operator Panel access
	I/O Access control	Protocol base (Network)
	Color Control	Dell ColorTrack 2.2
	Lock type and location	Kensington lock for printer, primary input tray, optional input tray and accessories (wireless dongle)
	Standard media types, sizes and paper weights	Standard tray
Media types and weights supported		Plain paper (60-90 gsm), Thicker paper (91-105 gsm), Heavier paper (106-216 gsm), Preprint (60-163 gsm), Letterhead (60-163 gsm), Prepunched (60-105 gsm), Cardstock (106-216 gsm), Coated paper (95-216 gsm), Recycled paper
Media sizes		A4 Short Edge Feed (SEF), B5 SEF, A5 SEF, Letter SEF, Executive SEF, Folio (8.5" x 13") SEF, Legal SEF Custom size: 5.8" - 8.5" (148 mm - 215.9 mm) (W), 8.3" x 14" (210 mm - 355.6 mm) (L)
Multipurpose tray		
Media types and weight supported		Plain paper (60-163 gsm), Preprinted (60-163 gsm), Letterhead (60-163 gsm), Prepunched (60-105 gsm), Cardstock (106-216 gsm), Heavier paper (164-216 gsm), Coated paper (95-216 gsm), Recycled paper, Labels, Envelope, Hagaki cards
Media sizes		A4 SEF, B5 SEF, A5 SEF, Letter SEF, Executive SEF Folio (8.5" x 13") SEF, Legal SEF, Envelope Com-10 (SEF), Envelope Monarch (SEF), Envelope DL (LEF/SEF), C5 (SEF), Post Card Custom size: 3" - 8.5" (76.2 mm - 216 mm) (W), 5" - 14" (127 mm - 355.6 mm) (L)
Optional Tray		
Media types and weights supported		Plain paper (60-90 gsm), Thicker paper (91-105 gsm), Heavier paper (106-216 gsm), Preprint (60-163 gsm), Letterhead (60-163 gsm), Prepunched (60-105 gsm), Cardstock (106-216 gsm), Coated paper (95-216 gsm), Recycled paper, Labels
Media sizes		A4 SEF, B5 SEF, A5 SEF, Letter SEF, Executive SEF, Folio (8.5" x 13") SEF, Legal SEF Custom size: 5.8" - 8.5" (148 mm - 215.9 mm) (W), 8.3" x 14" (210 mm - 355.6 mm) (L)
Duplexer		
Media types and weights supported	Plain paper (60-90 gsm), Thicker paper (91-105 gsm), Heavier paper (106-163 gsm), Recycled paper, Coated paper (95-163 gsm)	
Media sizes	Letter SEF, Executive SEF, A5 SEF, A4 SEF, B5 SEF, Legal13 SEF, Legal 14 SEF Custom size: 5.8" to 8.5" (148.5 mm - 215.9 mm) (W), 8.3" to 14" (210 mm - 355.6mm) (L)	
Printable area	8.2" (207.9 mm) x 13.7" (347.6 mm)	
Paper handling	Standard input sources	250-sheet standard tray, 150-sheet multipurpose tray
	Additional input capacity	550-sheet option tray
	Maximum input capacity	950 sheets (via addition of one 550-sheet optional tray)
	Duplexer	Automatic two-sided printing (default)
	Standard output capacity	250 sheets
Maximum output capacity	250 sheets	

1. Measured in accordance with ISO IEC 27434/75 methodology. Actual print speeds will vary with use.

2. 1 MB means 1 million bytes, 1 GB means 1,000 megabytes or 1,000,000,000 bytes; total accessible capacity varies depending on operating environment.

3. Duty cycle is defined as the maximum number of imaged outputs a device could deliver in a month. This metric provides a comparison of robustness in relation to other Dell printers and multifunction printers.

4. The printer and the mobile device must be connected on the same network.

5. AirPrint-enabled printers work with iPad, iPhone (3GS or later), and iPod touch (3rd generation or later) running iOS 4.2 or later.

©2013 Dell Corporation Limited. Dell, the Dell logo and Dell Toner Management System are registered trademarks or trademarks of Dell Inc. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Dell disclaims proprietary interest in the marks and names of others. Microsoft, Windows and Windows NT are registered trademarks or trademarks of Microsoft Corporation. Android and Google Cloud Print are registered trademarks of Google Inc. iPad, iPhone, iPod, and iPod touch are trademarks of Apple Inc., registered in the U.S. and other countries. AirPrint and the AirPrint logo are trademarks of Apple Inc. Specifications are subject to change without notice. Dell cannot be responsible for errors and omissions in typography or photography.