



The Dell C3760n and Dell C3760dn color laser printers

Empower your organization to do more with the Dell C3760n and Dell C3760dn color laser printers

Enjoy great performance, security features, and reliability combined with outstanding value

Perfect for medium workgroup needs in a networked environment, the Dell C3760n and Dell C3760dn color laser printers offer the ultimate combination of excellent print quality at a low cost per page, exceptionally high print speeds, and outstanding reliability designed to help maximize uptime. In addition, the standard automatic duplexer in the C3760dn allows two-sided printing which can help reduce paper costs for your organization.

Featuring Dell's total print quality solution, ColorbyDell, the C3760n and C3760dn color laser printers deliver excellent color saturation and image sharpness plus outstanding overall print quality. With stunning print speeds of up to 36 pages per minute (ppm)¹ (letter) in both mono and color/35 ppm¹ (A4), (actual print speed will vary with use) and large print volume capacity of up to 80,000 pages per month (max), the Dell C3760n and Dell C3760dn will easily handle the requirements of your organization. For added convenience, you can print directly to the Dell C3760n and C3760dn from Android devices by using the Dell Mobile Print app.²

For fast, cost-efficient, high-quality color and reliable laser network printing with security features choose the Dell C3760n and Dell C3760dn color laser printers.



Product benefits

Excellent value

- Packed with crucial high performance features with one of the lowest Cost Per Page (CPP)* and lower acquisition price** than comparable printers in its class
- Industry-leading high yield drums to reduce the running cost and total cost of ownership
- Toner cartridges that are separate from the drum unit are standard so that either drum unit or toner cartridge can be replaced without wasting the other
- Fuser maintenance kit is covered under the warranty so there are no additional costs if parts wear out during the warranty period

Direct printing from mobile devices

Experience the convenience of printing directly from your Android device using the Dell Mobile Print app²

Superior performance

- Dell's total print quality solution, ColorbyDell, is standard and delivers excellent color saturation and image sharpness plus outstanding print quality using advanced print technologies
- True performance workhorses offer stunning print speeds of up to 36 pages per minute $(ppm)^1$ (letter) in both mono and color/ 35 ppm¹ (A4), (actual print speed will vary with use)
- Greater level of secure print management through a combination of LDAP protocol and Kerberos authentication
- High-speed duplexer for two-sided printing (Dell C3760dn only) can help boost office productivity

Order supplies online or through selected partners





Dell C3760n/dn color laser printer

Dell C3760n/dn color laser printer control panel



- Faster warm up and print time compared to printers with conventional toners thanks to Dell's Emulsion Aggregation Eco Toner (EA-Eco)
- Easy one-touch operation activates Sleep Mode via the Energy Saver button to save energy
- Help reduce paper consumption with features like "N-Up" which prints multiple pages on one sheet of paper

Easy to set up, manage and use

• Dell features a suite of management software including Dell Toner Management System™, Dell Printer Configuration Web Tool and Dell ColorTrack Pro v1.1 allowing managers to monitor toner levels, configure the printer remotely using a web browser, and manage color printing access to control printing costs

Outstanding reliability

- Large volume capacity of up to 80,000 pages per month (max)
- High-yield toner cartridges to help minimize both down time and user intervention
- Gain peace of mind with Dell's standard 1-Year Limited Hardware Warranty³ and 1-Year Next Business Day On-Site Service After Remote Diagnosis⁴ that includes a Fuser Maintenance Kit



Dell C3760n/dn color laser printer connectivity



Dell C3760n/dn Enterprise Security and Wireless Kit

Get the most out of your Dell printer with genuine Dell options and supplies

Toner cartridges⁵	Dell C3760n/dn black toner standard and ship-with capacity: approximately 3,000 pages black and color (CMY); high capacity: approximately 7,000 pages black and 5,000 pages color (CMY); extra high capacity: 11,000 pages black and 9,000 pages color (CMY)
Memory (RAM)	256 MB standard; up to 512 MB RAM via DDR2 SO-DIMM slot x 1, 144-pin SO-DIMM (768 MB RAM maximum including standard memory)
Connectivity	USB 2.0 (high speed) Client port, Ethernet port (Gigabits), Wireless port (For optional dongle), USB Host Port (USB 2.0 Embedded Host Port for USB Direct Print)
Paper handling	Standard input 550-sheet tray, 150-sheet multipurpose tray; Optional: 550-sheet tray; Standard output: 250-sheet bin
Standard warranty and service	1-Year Limited Hardware Warranty ³ and 1-Year Next Business Day On-Site Service After Remote Diagnosis ⁴



The Dell C3760n and Dell C3760dn color laser printers



Product description	Designed for medium businesses and large organizations with medium workgroup needs, these cost-effective color laser printers offer fast, reliable, and secure high-quality color printing.
Printer specifications	
Print speed	Up to 36 pages per minute (ppm) ¹ (letter) in both mono and color/ 35 ppm ¹ (A4), (actual print speed will vary with use
Duplex speed	Up to 23 pages per minute (ppm) (letter) in both mono and color/ 23 ppm (A4), (actual print speed will vary with use)
Warm up time	Less than 19.9 sec from "Power on" to Ready state on display
First page out time	
From Ready state	Less than 13.5 sec (mono), 14 sec (color)
Print resolution	600 x 600 dpi
User interface	4-line with bitmap-based mono LCD with scalable font
Data streams	PCL® 6 Emulation (includes PCL 5e), Adobe® PostScript® 3™
Processor speed	533 MHz
Memory (RAM)	256 MB
Memory expansion	Up to 512 MB RAM via one DDR2 SO-DIMM slot (768 MB RAM max including standard memory)
Read-only memory (ROM)	64 MB (programs, fonts)
Maximum duty cycle	80,000 pages per month
Mobile printing	Print directly from Android mobile devices via Dell Mobile Print app ²
Paper handling	
Standard input sources	150-sheet multipurpose tray, 550-sheet standard tray
Additional input capacity	Optional 550-sheet tray
Maximum input capacity Duplexer (for two-sided printing)	1250 sheets Standard (C3760dn only)
Standard output destination	250-sheet bin
Maximum output capacity	250 sheets
Additional output destinations	Not available
Supported media types, sizes	
and paper weights	
Media types supported	Plain paper (light, normal, thick); coated paper (normal, thick); label stock (normal,thick); envelope; post card; recycled paper
Media sizes	
Multipurpose 150-sheet tray	US Letter, Executive, Folio, US Legal 14 in, A4, B5, A5, Envelope#10 (SEF), Custom size: Width: 3 in. – 8.5 in., Length: 5 in. – 14 in.
Standard and optional 550-sheet	US Letter, Executive, Folio, US Legal 14 in, A4, B5, A5, Custom size: Width: 5.8 in. – 8.5 in., (148.5 mm to 215.9 mm)
drawers and duplexer	Length: 8.3 in. – 14 in. (210 mm to 355.6 mm)
Media weight	Multipurpose tray: paper density @ bond paper, 16 - 57 lb (60 - 216 gsm) Standard and optional tray: paper
	density @ bond paper, 16 - 57 lb (60 - 216 gsm)
Maximum printable area	8.2 in. x 13.7 in. (207.9 mm x 347.6 mm)
Page layout options	Portrait or landscape orientation, multiple copies, duplex printing, multipage printing (N-up), poster, booklet printing, watermarks, collate, form, rotation
Connectivity	
Standard interfaces	USB 2.0 (high speed) Client port, Ethernet port (Gigabits), Wireless port (For optional dongle), USB Host Port
	(USB 2.0 Embedded Host Port for USB Direct Print)
Print languages and fonts	Print languages: PCL 6, PostScript 3, XPS; Fonts: HP PCL [®] 6 Emulation: 80 scalable fonts PostScript [®] Level 3 136 scalable fonts
Operating Systems (OS) Support	Microsoft® Windows® 7 32-bit / 64-bit, Vista 32-bit / 64-bit (Home Basic, Home Premium, Ultimate, Business), Windows® Server® 2008 R1&R2, Windows® XP 32-bit, 64-bit & embedded, Windows® 2003 Server®, Windows®
	Cluster Server Environment (SSW not supported), Mac OS: 10.3.9 - 10.7, 10.3.9 (power PC x32), 10.4.11 (Power PC
	32-bit/Intel 32-bit/, 10.5.8 (Power PC 32/64-bit/Intel 32/64-bit), 10.6.x (Intel 32-bit/64-bit), PowerPC 64-bit, SUSE
	Linux Enterprise Desktop 11 (x86), SUSE Linux Enterprise Desktop ver 10, Red Hat [®] Linux Enterprise Desktop 5
	(x86), HP UX 11i v2, Solaris™ 9, IBM AIX 5.1, 5.2, 5.3 and 6, Novell Netware Support (NovellYES, iPrint), SAP R/3
	Release 4.6B, Citrix [®] Presentation Server (Metaframe) Support, Microsoft [®] Windows [®] Server [®] 2003 32/64-bit:
	Citrix [®] Presentation Server™ 4.5, Microsoft [®] Windows [®] Server [®] 2003 32/64-bit: Citrix [®] XenApp™ 5.0, Microsoft [®]
	Windows® Server® 2008 32/64-bit: Citrix® Presentation Server™ 4.5, Microsoft® Windows® Server® 2008
	32/64-bit: Citrix® XenApp™ 5.0, Microsoft® Windows® Server® 2008 R2: Citrix® XenApp™ 6.0
Wireless kit (Options: Wireless	Enterprise Security (WPA2 Enterprise, Digital Certificate, HDD Encryption and Secured Erase), WPA2 Personal,
Dongle and 160 GB HDD)	WPA, WEP
Network transport, print &	TCP/IP, IPv4/IPv6, Port 9100, LPD/LPR, FTP, SMB, IPP, IPP over SSL (with harddisk), WSD, HTTP, HTTPS, SSL/TLS,
management protocols standard	SNMP (v1, v2, v3), MIBv2 (RFC1213 compliant), BOOTP, DHCP, RARP, Auto IP, WINS, DNS,Bonjour(mDNS), Telnet Dell MIB s v0.85

The Dell C3760n and Dell C3760dn color laser printers

Consumables

Printer firmware and printer driver software User documentation (soft copy user manual on CD)	English, French, Italian, German, Spanish, Dutch, Danish, Norwegian and Swedish English, French, Italian, German, Spanish, Dutch, Danish, Norwegian and Swedish
Safety certifications	IEC/EN60950-1:2005 2nd edition (International); EN60950-1:2006 2nd edition IEC60825-1 (Laser); CE Mark (EU); cTUVus FDA/DHHS (21CFR, Chapter 1, Subchapter J) Other safety approvals required by individual countries.
EMC certifications	CE mark (EU countries) EMC/Safety Standard: EN55022:2006 + A1:2007 Class B; EN61000-3-2:2006 + A:2009 + A2:2009 ClassA, EN 61000-3-3:2008, EN55024:1998 + A1:2001 + A2:2003; FCC CFR Title 47, Part 15 Class B (USA); ICES-003, Issue 4 (Canada)
Environmental compliance and other certifications/compliances	ErP Lot 6 Tier 1(2010), Tier 2(2013), ErP Lot 4 Tier 1(2010), Tier 2 (2012), GS Mark(Germany), RoHS-compliant ⁶ , Energy Star-qualified (C3760dn only) ⁷ , Blue Angel (Germany) - (C3760dn only), WEEE
Printer management	Dell Printer Configuration Web Tool, Dell Supplies Ordering Utility, Standard Printer MIB, Dell Private MIB v0.85, Dell ColorTrack Professional v1.1
Warranty and service options Standard service Service options	1-Year Next Business Day On-Site Service After Remote Diagnosis ⁴ Extended service options are available up to 4 years
Physical specifications Dimensions (W x D x H)	<i>Printer:</i> 19.09 in. x 17.28 in. x 14.92 in. (439 mm x 485 mm x 379 mm); <i>Shipping:</i> 27.01 in. x 22.44 in. x 20.71 in. (570 mm x 686 mm x 526 mm)
Weight Operating environment	Printer: 56.4 lbs (25.6 kg); Shipping: 67.3 lbs (30.5 kg) Temperature: 41°F to 90°F (5 to 32 °C); Relative humidity: 15 to 85% RH, non-condensing; Altitude: ≤ 10,170 ft (3,100 m) above sea level.
Storage	<i>Packaged:</i> Temperature: 32°F to 95°F (0 to 35° C); Relative humidity: 15 to 80% RH; Altitude: \leq 10,170 ft (3,100 m) above sea level.
Acoustics ⁸ Printing (simplex mode)	Sound Pressure, Bystander position (LpAm): 54dB (Ref); Average Sound Power (LWAd), declared: 7.15B Color, 6.95B Mono
Standby mode	Sound pressure, bystander position (LpAm): 29dB (Ref); Average Sound Power (LWAd), declared: 4.69B
Power specifications Voltage	
100 and 120 vac models 230 vac models	100 to 127 vac ± 10 %, 50 ± 3 Hz / 60 ± 3 Hz nominal 220 to 240 vac ± 10 %, 50 ± 3 Hz / 60 ± 3 Hz nominal
Power consumption (Energy Star®-compliant) ⁷	Continuous printing: 705W; Standby mode: 76W; Power Saver mode: Sleep: 14W, Deep sleep: 5W; Off: 0W
Typical energy consumption Average current consumption	3.1KWH/week (TEC 230V / 120V) 6A or less @110V 2A or less @220V/
Power Save options	3A or less @220V User definable 5 - 60 mins. (default 6 mins.)
Contents in box	Dell C3760n/dn Printer, Dell ship-with black, cyan, magenta and yellow cartridges (3,000 page yield ⁵), placemat

*Dell C3760n/dn has one of the lowest CPP (1.54 cents mono/10.0 cents color) in this class of printers **Dell C3760n/dn has a lower acquisition price than comparable printers in its class with a list price of \$549/\$649 1 Measured in accordance with ISO IEC 27434/35 methodology. Actual print speeds will vary with use.

² The printer and the mobile device must be connected to the same wireless network.
³ For a copy of limited hardware warranty, write Dell USA LP, Attn: Warranties, One Dell Way, Round Rock, TX 78682 or visit dell.com/warranty.
⁴ Remote Diagnosis is determination by online/phone technician of cause of issue; may involve customer access to inside of system and multiple or extended sessions. If issue is covered by

Limited Hardware Warranty and not resolved remotely, technician and/or part will be dispatched, usually within 1 business day following completion of Remote Diagnosis. Availability varies. Other conditions apply.

⁶ Toner conductors apply.
⁶ Toner yield based on testing in accordance with ISO/IEC 19798. Yields vary with usage and environmental conditions.
⁶ Meets the requirements of the EU Directive on the Restriction of the use of certain Hazardous Substances (RoHS) dated 27 January 2003
⁷ For details on energy efficiency of Energy Star-qualified products, refer to: http://www.energystar.gov.
⁸ Tested in accordance with ISO 7779 and reported in accordance with ISO 9296, Acoustics - Declared noise emission values of computer and business equipment

Microsoft, Windows and Windows Vista are trademarks or registered trademarks of Microsoft Corporation in the U.S. and other countries. Dell Inc. disclaims any proprietary interest in trademarks and trade names other than its own. © Copyright 2012 Dell Inc. Dell's Terms and Conditions of Sales and Service apply and are available upon request. Dell cannot be held responsible for errors in typography or photography.