

TH-PT8

ProAV

Installation Instructions



telehook

Projector | Suspended Ceiling Tile 8"


Component Checklist

Tools Required:

Phillips head screwdriver
Wire cutters
Power drill
6mm (1/4") drill bit
6mm (1/4") masonry drill bit
Claw hammer
Jigsaw/Hole cutter
Spirit level



Hardware



IMPORTANT INFORMATION:


! IMPORTANT - Install Telehook Projector - Suspended Ceiling Tile 8" as per Installation Instructions.

- ! Compatible with 1.5" NPT Pole Mounts, Atdec Pole Mount (TH-WH-PJ-CM), Atdec Flush Mount (TH-WH-PJ-FM), Atdec ProAv Projector Ceiling Mount (TH-PF) and Atdec pole accessories (TH-PPA-18-25, TH-PPA-24-48 & TH-PPE-24).
- ! Maximum weight capacity 22.7kg (50lbs).
- ! The manufacturer accepts no responsibility for incorrect installation.

Step 1. Check Components

Check you have received all parts against the Component Checklist and Hardware above.

Step 2. Remove Existing Ceiling Tile



Remove existing ceiling tile from ceiling grid where the product is going to be installed.

NOTE: Keep this ceiling tile for later in the installation.

TIP: Also temporarily remove an adjacent ceiling tile to allow easy access to the product during installation.


Step 3. Fix Anchors to True Ceiling

Uncoil Support Wire and cut into 4 equal lengths. Select the anchoring method appropriate to your ceiling (see below).

NOTE: Each anchor point should be directly above each corner of the Suspended Ceiling Tile.


Wooden Joists

Drill 4x Ø6mm holes, at least 50mm deep (4x Ø1/4" holes, 2" deep).
Fully screw Lag Eye bolts into wooden joists.




Solid Concrete

Drill 4x Ø6mm holes, 36mm deep (4x Ø1/4" holes 1 1/2" deep).
Tap anchors into hole to an embedded depth of at least 25mm deep (1" deep).
Using a claw hammer, pull anchor out 6mm (1/4") to activate anchor.




Truss Beams

Thread one end of Support Wires through the trusses, and wrap 5 times to secure.



Step 4. Attach Turnbuckles onto Support Wires



Loop each dangling Support Wire through a Turnbuckle, and wrap 5 times to secure.


Make sure that the position of the x4 Turnbuckles are approximately at the same height.

TIP: When mounting 1.5" NPT pole mounts or flush mounts the turnbuckle hooks should be level with the top of ceiling grid.
When mounting an Atdec pole mount (TH-WH-PJ-CM) the hooks should be approximately 130mm (5") above the top of the ceiling grid.

Step 5. Assemble Projector Mount Interface onto Suspended Ceiling Plate


1.5" NPT mount interfaces

(Included) (compatible with Atdec pole accessories & 1.5" NPT poles)




Atdec Pole Mount

(TH-WH-PJ-CM supplied separately)




Atdec Flush Mount

(TH-WH-PJ-FM supplied separately)



Step 6. Hook Suspended Ceiling Tile



Hook Suspended Ceiling Tile to the Turnbuckles. Twist Turnbuckles for height adjustment.



TIP: Use a spirit level to ensure the Suspended Ceiling Tile is level.



Step 7. Fix Safety Wire

Thread one end of the Safety Wire through a Lag Eye Bolt, Concrete Anchor, or Truss and clamp using Safety Clamp.




Step 8. Cut out Hole in Original Ceiling Tile

Hold the original ceiling tile up to the ceiling grid and mark out where the projector mount will protrude through.



Replace original ceiling tile into the ceiling grid.




Step 9. Install Projector Mount and Ceiling Cover

(choose Ceiling Cover to suit projector mount)


Atdec Pole Accessories

(TH-PPA-18-25, TH-PPA-24-48 & TH-PPE-24 supplied separately) or 1.5" NPT Pole Mount (supplied separately)



Atdec Pole Mount


(TH-WH-PJ-CM supplied separately)



Atdec Flush Mount

(TH-WH-PJ-FM supplied separately)

NOTE: For TH-WH-PJ-FM the cut-out must be at least Ø65mm (2.5") to allow access to the Locking Hook and fasteners.



Installation Complete - Ready to install Projector



No portion of this document or any artwork contained herein should be reproduced in any way without the express written consent of Atdec Pty Ltd. Due to continuing product development, the manufacturer reserves the right to alter specifications without notice. Published 12.03.14©