

Model #: P005-010-14RA

10-ft. Heavy-Duty 14AWG Power Cord (IEC-320-C13 to Right-Angle IEC-320-C14)



Highlights

- 10 ft. C13 to Right-Angle C14 Power Cord
- 14 AWG x 3C, 15A, 100-250V, SJT
- UL Listed

Description

Use Tripp Lite's P005-010-14RA in server applications that require a higher rated, heavier gauge cable, and in which space is in high demand. The right-angle C14 connector on this power cord is perfect for saving space in tight areas, such as in the back of your rack enclosure cabinet. When plugged in, it seats flush against the back of a device (e.g. PDU, UPS, etc.), providing space for your rack door to close, or additional room to organize a tight area. C13 to Right-Angle C14 connectors, 3 x 14 AWG conductors, 15A rating, 100-250V, SJT jacket. Tripp Lite Lifetime Limited Warranty.

Applications

The right-angle C14 connector on this power cord is perfect for saving space in tight areas, such as in the back of your rack enclosure cabinet. When plugged in, it seats flush against the back of a device (e.g. PDU, UPS, etc.), providing space for your rack door to close, or additional room to organize a tight area.

Package Includes

• P005-010-14RA C13 to Right-Angle C14 Power Cord

Features

- Molded, Heavy-Duty Power Cable, 10 ft.
- IEC-60320-C13 to Right-Angle IEC-60320-C14 connectors
- Right-angle C14 connector is perfect for saving space in tight areas
- 14 AWG x 3C, 15A, 100-250V, SJT jacket
- RoHS Compliant
- UL Listed

Specifications

OVERVIEW	
Cable Type	POWER
Model Type	Power Cords
INPUT	
Cable Length (ft.)	10
Cable Length (m)	3.05

037332179951	
PHYSICAL	
Black	
Power Cables	
CONNECTIONS	
IEC-320-C13	
IEC-320-C14	
WARRANTY	
Lifetime limited warranty	

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?variables.txtModelID=5483.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.