

## Single-Phase Basic PDU, 7.4kW 32A 230V, 1U Horizontal Rackmount, 10 C13 outlets, Blue IEC309 32A input plug

MODEL NUMBER: **PDUH32HV**



### Highlights

- Basic single phase 32A 230V PDU
- 1U horizontal rackmount installation
- Blue IEC309 32A (2P+E) input; 12 ft. / 3.6m line cord
- 10 C13 outlets
- Reversible housing; 5.2 in. / 13.2 cm depth

### Applications

Ideal for datacenter power distribution in datacenter equipment racks, network closets and other IT applications

### Package Includes

- PDUH32HV Power Strip
- Instruction manual

### Description

Tripp Lite Basic Power Distribution Units / PDU systems offer reliable rackmount power distribution. Supplies equipment with continuous power from any protected UPS, generator or mains input power source. High quality design includes rugged all-metal housing and secure rackmount installation with included mounting accessories.

### Features

- 32A single phase 230V Basic Power Distribution Unit / PDU
- Attached Blue IEC-309 32A (2P+E) 230V input plug with 12 ft. / 3.6m line cord
- 1U horizontal rackmount format installs in one rack space
- 10 C13 outlets
- Mounting flanges are reversible front or rear facing installation
- Mounting flanges support installation in 2 and 4 post racks, with additional support for wall-mount and under-counter installation formats

## Specifications

SELECTOR	
Selector Type	PDU'S
General Info	
Product Group	PDUS
SELECTOR	
Digital Load Meter	No



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

Redundant Power Cords	No
SNMP Compatible	No
<b>OVERVIEW</b>	
Style	Rackmount, Vertical Rackmount, Wallmount/Under-Counter
PDU Type	Basic
<b>OUTPUT</b>	
Output Capacity Details	7.4kW (230V), 7kW (220V), 7.7kW (240V); 32A maximum total output, 20A max per breakered load bank, 10A max per C13 outlet
Frequency Compatibility	50 / 60 Hz
Output Nominal Voltage	200-240V nominal, single phase
Overload Protection	Two 20A circuit breakers protect 5 outlets each
Outlet Quantity / Type	10 C13
Outlet Type	IEC-C13
<b>INPUT</b>	
PDU Input Voltage	200; 208; 220; 230; 240
Maximum Input Amps	32
PDU Plug Type	IEC-309 32A BLUE (2P+E)
Input Cord Length (ft.)	12
Input Cord Length (m)	3.6
Input Phase	Single-Phase
<b>PHYSICAL</b>	
Shipping Dimensions (hwd / in.)	3 x 20.25 x 11.25
Shipping Dimensions (hwd / cm)	7.6 x 51.4 x 28.6
Unit Dimensions (hwd / in.)	1.75 x 17.5 x 5.2
Unit Dimensions (hwd / cm)	4.5 x 44.5 x 9.5
Material of Construction	Steel
Form Factors Supported	1U rackmount, 0U vertical mount, wallmount and under-counter
PDU Form Factor	Horizontal (1U, 2U, etc)
<b>CERTIFICATIONS</b>	
Certifications	Tested to UL60950-1, CE (EN 60950-1), CE Class A, RoHS
<b>WARRANTY</b>	



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

Product Warranty Period (Worldwide)	5-year limited warranty
-------------------------------------	-------------------------

© 2015 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.