

Single-Phase Basic PDU, 5/5.8kW 30A 208/240V, 1U Horizontal Rackmount, 4 C19 outlets, NEMA L6-30P input plug

MODEL NUMBER: **PDUH30HV19**



Highlights

- Basic single phase 30A 208/240V PDU
- 1U horizontal rackmount installation
- NEMA L6-30P input; 12 ft. / 3.6m line cord
- 4 C19 outlets
- Reversible housing; 5.2 in. / 13.2 cm depth

Applications

Ideal for datacenter power distribution in datacenter equipment racks, network closets and other IT applications

Package Includes

- PDUH30HV19 PDU
- Warranty information
- Instruction manual

Description

Tripp Lite Basic Power Distribution Units / PDU systems offer reliable rackmount power distribution. Supplies equipment with continuous power from any protected UPS, generator or mains input power source. High quality design includes rugged all-metal housing and secure rackmount installation with included mounting accessories.

Features

- 30A single phase 208/240V Basic Power Distribution Unit / PDU (agency de-rated to 24A continuous)
- Attached NEMA L6-30P 30A 208/240V input plug with 12 ft. / 3.6m line cord
- 1U horizontal rackmount format installs in one rack space
- 4 C19 outlets
- Mounting flanges are reversible front or rear facing installation
- Mounting flanges support installation in 2 and 4 post racks, with additional support for wall-mount and under-counter installation formats

Specifications

SELECTOR	
Selector Type	PDU'S
General Info	
Product Group	PDUS
SELECTOR	
Digital Load Meter	No



Redundant Power Cords	No
SNMP Compatible	No
OVERVIEW	
Style	Rackmount, Vertical Rackmount, Wallmount/Under-Counter
PDU Type	Basic
OUTPUT	
Output Capacity Details	5kW (208V input), 5.3kW (220V input), 5.8kW (240V input), 4.8kW (200V input); 30A maximum (agency de-rated to 24A continuous)
Frequency Compatibility	50 / 60 Hz
Output Nominal Voltage	200-240V nominal, single phase
Overload Protection	30A
Outlet Quantity / Type	4 C19
Outlet Type	IEC-C19
INPUT	
PDU Input Voltage	200; 208; 220; 240
Maximum Input Amps	30
Maximum Input Amps Details	30A maximum (agency de-rated to 24A continuous)
PDU Plug Type	NEMA L6-30P
Input Cord Length (ft.)	12
Input Cord Length (m)	3.6
Input Phase	Single-Phase
PHYSICAL	
Shipping Dimensions (hwd / in.)	3 x 20.25 x 11.25
Shipping Dimensions (hwd / cm)	7.6 x 51.4 x 28.6
Unit Dimensions (hwd / in.)	1.75 x 17.5 x 5.2
Unit Dimensions (hwd / cm)	4.5 x 44.5 x 9.5
Material of Construction	Steel
Form Factors Supported	1U rackmount, 0U vertical mount, wallmount and under-counter
PDU Form Factor	Horizontal (1U, 2U, etc)
ENVIRONMENTAL	
Storage Temperature Range	-15C to +50C (+5F to +122F)
Relative Humidity	5-95% non-condensing



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

CERTIFICATIONS	
Certifications	Tested to UL60950-1 (USA), CSA-C22.2 (Canada), RoHS
WARRANTY	
Product Warranty Period (Worldwide)	5-year limited warranty

© 2015 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.