

Dual VGA with Audio over Cat5 Extender, Receiver, Up to 300-ft.

MODEL NUMBER: B132-200A-SR









Description

Tripp Lite's B132-200A-SR Dual VGA with Audio over Cat5 Extender Receiver Unit is designed to work with Tripp Lite's B132-002A-2 and B132-004A-2 VGA with Audio over Cat5 Extender / Splitter Transmitter Units. Unlike the B132-100A Receiver Unit (which supports distances up to 1,000-ft.), or the B132-100A-MR (which supports distances up to 750-ft.) the B132-100A-SR is a cost effective solution for distances up to 300-ft. It extends a 1440 x 900 video and audio signal up to 150-ft. from the source, or a 1024 x 768 video and audio signal up to 300-ft. It also features dual VGA and audio ports for the connection of two sets of monitors and speakers. An Equalization control is provided to adjust the video image. Audio connections are made with standard 3.5mm stereo cables (not included). Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases.

Features

- Features dual VGA and audio ports for the connection of two sets of monitors and speakers
- Works with a B132-002A-2 or B132-004A-2 Transmitter Unit to extend a VGA video and audio signal up to 300-ft. from the source
- Extends a 1440 x 900 video and audio signal up to 150-ft, or a 1024 x 768 video and audio signal up to 300-ft.
- 24AWG, Solid Wire Cat5e/6 cable (such as Tripp Lite's N202-Series Cat6 cables) is required to achieve maximum distance and resolution
- Features a built-in equalization control to adjust the video image
- All operating systems supported
- · Plug and play; no software or drivers required
- HDCP and EDID compliant
- Ideal for digital signage installations for retail, schools, churches, etc.
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Specifications

Highlights

- Features dual VGA and audio ports for the connection of two sets of monitors and speakers
- Works with a B132-002A-2 or B132-004A-2 Transmitter Unit to extend a VGA video and audio signal up to 300-ft. from the source
- Extends a 1440 x 900 video and audio signal up to 150-ft, or a 1024 x 768 video and audio signal up to 300-ft.
- Plug and play, no software or drivers required
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases.

Package Includes

- B132-200A-SR
- External Power Supply (Input: 100-240V, 50/60Hz, 0.5A Output: 5V, 2A)
- Screwdriver for EQ adjustment
- Owner's Manual





OVERVIEW	
Chromebook Compatible	No
Display Style	Splitter
Model Type	VGA
Cable Types	CAT5/CAT5E
PHYSICAL	
Shipping Weight (lbs.)	1
Shipping Weight (kg)	0.45
Unit Dimensions (hwd / in.)	1.1 x 4.5 x 2.5
Unit Dimensions (hwd / cm)	2.7 x 11.5 x 6.24
Unit Weight (lbs.)	0.5
Unit Weight (kg)	0.23
Color	Black
CONNECTIONS	
Connector A	HD15 (FEMALE) (X2)
Connector B	3.5MM (FEMALE) (X2)
Connector C	RJ45 (FEMALE)
CERTIFICATIONS	
Approvals	CE, FCC, RoHS, REACH
WARRANTY	
Product Warranty Period (Worldwide)	1-year limited warranty

© 2015 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.