

1U 19" Rackmount LCD Console - USB + PS/2

StarTech ID: RACKCONS1901



The RACKCONS1901 1U 19" Rack Mount LCD Console provides a complete keyboard, video and mouse control point, integrated neatly into only 1U of rack/cabinet space - providing complete KVM control right from a server rack.

Offering a durable, compactable 1U design, when the rack console is not in use it's as simple as folding the display like a laptop computer, and sliding it back into the server rack on the sturdy mounting rails (included). The included key lock provides an added security layer, helping to reduce unauthorized access to connected computers.

Offering consolidated control from a convenient location, the KVM rack console can be connected to virtually any multiport KVM switch, for control of multiple servers/computers, providing a scalable KVM control solution that lets you determine the type of KVM switch to use based on function and budget.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Applications

- Centralized control of dozens of PCs and servers if used with optional KVM
- Managing cabinet mounted servers
- Improving the internal space efficiency of existing cabinets

Features

- Bright Active Matrix TFT Display
- Durable design
- OSD function (On Screen Display) for LCD display
- Security features, including port locking and auto scan



Technical Specifications

Warranty 2 Years
Audio No
Display Size 19in

Panel Type Active Matrix TFT LCD

KVM Ports 1

PC Interface USB and PS/2

PC Video Type VGA
Multi-Monitor No
Rack-Mountable Yes
Key Lock Yes

Host Connectors 1 - USB A (4 pin) Female

Host Connectors 1 - VGA (15 pin; High Density D-Sub) Female

Host Connectors 2 - PS/2 (6 pin; Mini-DIN) Female

Brightness 250 cd/m²
Contrast Ratio 1000:1

Pixel Pitch Support 0.294 x 0.294 mm

Response Time 5ms

Viewing Angle 176° (H), 170° (V)

IP Control No

Maximum Analog Resolutions 1280x1024(SXGA)@60Hz

Aspect Ratio Standard (4:3)

Color Depth 24-bit, 16.7M colors (Truecolor)

Maximum Number of Users 1

Port Selection Support Hotkeys and OSD (On Screen Display)

MTBF 60,000 Hours

Maximum Mounting Depth 31.5 in [800 mm]

Minimum Mounting Depth 21.9 in [555 mm]

Product Height 1.8 in [45 mm]

Product Length 22.6 in [575 mm]

Product Weight 30.3 lb [13.7 kg]

Product Width 18.9 in [480.8 mm]

Color Black

Enclosure Type Heavy Duty Steel Input Voltage 115 ~ 230 AC





Hard-to-find made easy®

Center Tip Polarity Positive

Operating Temperature 0°C to 50°C (32°F to 122°F)
Storage Temperature -20°C to 60°C (-4°F to 140°F)

Shipping (Package) Weight 41.9 lb [18.9 kg]

Included in Package 1 - 1U LCD Rack Console Drawer

Included in Package 1 - Mounting Rails - Set Included in Package 1 - Console Cable Kit

Included in Package 1 - Power Cord

Certifications, Reports and Compatibility







