

2.5in USB 3.0 SATA Hard Disk Drive Enclosure for SAT2510U3REM

StarTech ID: SAT2510U3S



The SAT2510US 2.5in Hard Disk Drive Enclosure for SAT2510U3REM is a spare SATA drive enclosure for use with the SAT2510U3REM [Removable Hard Drive Backup System/Mobile Rack](#), which simplifies removing/rotating drives.

This 2.5" SATA enclosure allows for native SATA connectivity (SATA 6 Gbps compliant) while mounted inside the SAT2510U3REM backup system, but also provides SuperSpeed USB 3.0 connectivity (with up to 5 Gbps of data bandwidth) when used externally.

Applications

- Use multiple hard drives with the same SAT2510U3REM installation for archiving or rotating backups
- Professionals working with very large files who need to transport them between computers/locations
- Business professionals who need first hand access to their office data while travelling

Features

- Spare 2.5" hard drive enclosure for SAT2510U3REM mobile rack
- SuperSpeed USB 3.0 compliant host interface with support for up to 5Gbps of bandwidth
- Flammability rating of UL 94 V-0
- Durable aluminum construction for the drive enclosure
- Compatible with SATA revision 1/2/3 (1.5/3.0/6.0 Gbps) drives
- Supports 2.5" form factor SATA hard drives (HDD) and solid state drives (SSD)

Technical Specifications

Warranty	2 Years
Chipset ID	ASMedia ASM1053 ASMedia ASM1456
Drive Installation	Fixed
Drive Size	2.5in
Drive Type	SATA
Interface	SATA
Interface	USB 3.0
Number of Drives	1
Drive Connectors	1 - SATA Data & Power Combo (7+15 pin) Receptacle
Host Connectors	1 - SATA Data & Power Combo (7+15 pin) Plug
Host Connectors	1 - USB 3.0 Micro-B (10 pin; SuperSpeed) Female
Type and Rate	SATA III (6 Gbps)
Type and Rate	USB 3.0 - 5 Gbit/s
OS Compatibility	Windows XP (32/64-bit)/ Server 2003 (32/64-bit)/ Server 2008 R2/ Vista (32/64-bit)/ 7 (32/64-bit)/ 8 (32/64-bit) Mac OS X (tested up to 10.8) Linux
Color	Black
Enclosure Type	Aluminum and Plastic
Max Drive Height	0.4 in [9.5 mm]
Product Height	0.6 in [15.9 mm]
Product Length	5.2 in [132.8 mm]
Product Weight	4.2 oz [120 g]
Product Width	3.1 in [79.1 mm]
LED Indicators	1 - Power/Activity (Green)
Humidity	5% ~ 95% RH
Operating Temperature	0°C to 40°C (32°F to 104°F)
Storage Temperature	-20°C to 70°C (-4°F to 158°F)
Package Quantity	1
Shipping (Package)	0.6 lb [0.3 kg]
Weight	
Included in Package	1 - 2.5" SATA Enclosure for SAT2510U3REM
Included in Package	1 - USB 3.0 A to Micro-B Cable

Included in Package 1 - Screw Kit

Certifications, Reports and Compatibility

