

2 Port USB VGA Cable KVM Switch - USB Powered with Remote Switch

StarTech ID: SV211USB



The SV211USB 2-Port VGA Cable KVM Switch lets you control two VGA, USB-equipped PCs with a single monitor, keyboard and mouse.

To help organize your desk without sacrificing valuable work space, this VGA USB KVM switch features a compact footprint and integrated KVM cables that can be connected directly to your systems. Plus, the KVM is USB-powered, eliminating the need for a bulky external power adapter and wall outlet.

This VGA KVM switch offers support for resolutions up to 2048x1536, for the ability to drive a high-resolution VGA display. For simple switching between connected systems, the KVM features a convenient push-button remote switch on a 1.5 meter (5ft) cable, as well as keyboard hot-key support and PC or Mac® compatible switching software.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Applications

- Great for PC test/burn-in computer control, saving the desk space required for two monitors, keyboards and mice
- Perfect for sharing computers and attached peripherals in the home or home office
- Dual system control for single user workstations, increasing user productivity in the office

Features

- Supports resolutions up to 2048x1536
- Switch PCs via push-button, hot-keys or switching software (included)
- Space-saving design, minimal footprint
- Integrated KVM cables and remote switch
- Switching software supports PC and Mac® platforms
- USB Powered - No external power adapter required
- Supports hot-plugging
- Remote switch on 1.5m (5ft.) cable

Technical Specifications

| | |
|---------------------------|---|
| Warranty | 2 Years |
| Audio | No |
| KVM Ports | 2 |
| PC Interface | USB |
| PC Video Type | VGA |
| Multi-Monitor | No |
| Rack-Mountable | No |
| Cables Included | Yes |
| Daisy-Chain | No |
| Console Interface(s) | 1 - VGA (15 pin; High Density D-Sub) Female |
| Console Interface(s) | 2 - USB A (4 pin) Female |
| Host Connectors | 1 - VGA (15 pin; High Density D-Sub) Male |
| Host Connectors | 1 - USB A (4 pin) Male |
| IP Control | No |
| Port Selection Support | Push Button, Hotkeys, and Software |
| OS Compatibility | Windows® 8 / 8.1 (32/64bit), 7 (32/64), Vista(32/64), XP(32/64), 2000 Windows Server® 2012, 2008 R2, 2003(32/64) Mac OS 10.x (Tested up to 10.9), 9.x |
| Note | OS Compatibility refers to KVM software only - the KVM itself can be used without software on any platform |
| Color | Black |
| Enclosure Type | Plastic |
| Cable Length | 850 mm [33.5 in] |
| Product Length | 88 mm [3.5 in] |
| Product Width | 66 mm [2.6 in] |
| Product Height | 23 mm [0.9 in] |
| Product Weight | 380 g [13.4 oz] |
| LED Indicators | 1 - PC Selection indicator |
| Power Source | USB-Powered |
| Operating Temperature | 0°C to 40°C (32°F to 104°F) |
| Storage Temperature | -20°C to 60°C (4°F to 140°F) |
| Humidity | 0~90% RH Non-Condensing |
| Shipping (Package) Weight | 385 g [13.6 oz] |
| Included in Package | 1 - KVM Switch |

- Included in Package 1 - Software CD
- Included in Package 1 - Instruction Manual

Certifications, Reports and Compatibility

