

NEC V Series

Flat-panel monitors ideal for general business users



Step up to superior flat-panel display performance without emptying your pockets. With affordable LCD monitors for a variety of users, NEC V Series monitors have set a new standard in value in the display product category. In fact, with affordability akin to that of comparable CRT monitors, V Series monitors offer you a perfect opportunity to take advantage of the many benefits offered by flat-panel monitors without having to break your budget. The 17" NEC LCD17V and 19" NEC LCD19V deliver ideal visual display solutions to general business users, adding clarity to presentation and document creation, vibrant splashes of color to web surfing and exciting, lifelike action to gaming.

Enhanced screen performance. With contrast ratios as high as 550:1 (typical) and brightness quality much higher than CRTs at 270 cd/m², outstanding LCD monitor front-of-screen visual performance is NEC's #1 goal. The V Series delivers vibrant colors and flicker-free images that make your time in front of the monitor more comfortable and productive. NEC's Rapid Response™ technology provides for uninterrupted display of full-motion video with response times as quick as 8ms. This remarkably quick motion makes these models better than ever for gaming and video applications such as presentations and streaming web video.

Intelligent power management ensures a smart investment. Using approximately 70% less power and emitting less heat than comparable CRT monitors, V Series monitors allow you to conserve energy and lower your total cost of ownership.

Series Features and Benefits

Exceptional screen performance provides a more comfortable and productive visual experience with crisp, sharp and accurate text and images

Rapid Response technology delivers virtually uninterrupted, undistorted viewing of high-speed, full-motion video

Enhanced cable management helps prevent unattractive, space-consuming wire clutters

On Screen Manager (OSM®) puts you in complete control of your screen setting adjustments

No Touch Auto Adjust™ reduces setup time and provides optimal image settings upon initial power-on

Wall/arm mounting capability adds flexibility and comfort, while freeing up valuable desktop space (using third-party product)

ENERGY STAR 4.0 compliance/low power consumption reduces electrical costs and lowers total cost of ownership

NEC Display Solutions' quality and reliability provide peace of mind with a 1-year limited parts and labor warranty (including backlight) and 24/7 customer service and technical support

V Series Specifications

Model	LCD17V	LCD19V
Display:		
Viewable Image Size	17"	19"
Pixel Pitch	0.264mm	0.294mm
Pixels Per Inch	96 @ native resolution	86 @ native resolution
Brightness (typical)	270 cd/m ²	270 cd/m ²
Contrast Ratio (typical)	500:1	550:1
Viewing Angle (typical)	130° Vert., 160° Hor.(60U/70D/80L/80R)	145° Vert., 160° Hor.(75U/70D/80L/80R)
Response Time (typical)	Rapid Response (8ms)	Rapid Response (8ms)
Display Colors	More than 16 million	More than 16 million
Synchronization Range:		
Horizontal	31.5-81 kHz	31.5-81 kHz
Vertical	56-76 Hz	56-76 Hz
Input Signal:		
Video	Analog 0.7 Vp-p/75 Ohms	Analog 0.7 Vp-p/75 Ohms
Sync	Separate Sync: TTL Level (positive/negative)	Separate Sync: TTL Level (positive/negative)
Input	VGA 15 pin D-sub	VGA 15 pin D-sub
Resolutions Supported	720 x 400 @ 70 Hz 640 x 480 @ 60-75 Hz 800 x 600 @ 56-75 Hz 832 x 624 @ 75 Hz 1024 x 768 @ 60-75 Hz 1152 x 864 @ 70-75 Hz 1152 x 870 @ 75 Hz 1280 x 960 @ 60-75 Hz 1280 x 1024 @ 60-75 Hz	720 x 400 @ 70 Hz 640 x 480 @ 60-75 Hz 800 x 600 @ 56-75 Hz 832 x 624 @ 75 Hz 1024 x 768 @ 60-75 Hz 1152 x 864 @ 70 Hz 1152 x 870 @ 75 Hz 1280 x 960 @ 60-75 Hz 1280 x 1024 @ 60-75 Hz
Native Resolution	1280 x 1024 @ 60 Hz	1280 x 1024 @ 60 Hz
Additional Features	Thin-frame (bezel), tilt, No Touch Auto Adjust, cable management, NaViSet software, digital smoothing, digital controls, user (OSM) controls, Plug and Play (VESA DDC & 2Bi), AccuColor color control, DDC/CI, VESA DPMS power management, ISO 13406-2 Class II	Thin-frame (bezel), tilt, No Touch Auto Adjust, cable management, NaViSet software, digital smoothing, digital controls, user (OSM) controls, Plug and Play (VESA DDC 1/2B), AccuColor color control, DDC/CI, VESA DPMS power management, ISO 13406-2 Class II
Touch-Capable	No	No
Voltage Rating	100-240V @ 50/60 Hz	100-240V @ 50/60 Hz
Power Consumption (typical):		
On	36W	37W
Power Savings Mode	2W	2W
Dimensions (W x H x D):		
Net (with stand)	14.5 x 15 x 8.1 in. /368 x 381.5 x 205mm	16 x 16 x 8.1 in. /405.5 x 405.5 x 205mm
Net (without stand)	14.5 x 12.5 x 2.4 in. /368 x 316.5 x 60.6mm	16 x 13.6 x 2.4 in. /405.5 x 346 x 61.5mm
Weight		
Net (with stand)	8.8 lbs. /4 kg	11.7 lbs. /5.3 kg
Net (without stand)	7.9 lbs. /3.6 kg	10.8 lbs. /4.9 kg
VESA Hole Configuration Specifications	100 x 100mm	100 x 100mm
Environmental Conditions:		
Operating Temperature	5-35°C/41-95°F	5-35°C/41-95°F
Operating Humidity	10-80%	10-80%
Operating Altitude	3048m/10,000 ft.	3048m/10,000 ft.
Storage Temperature	-10-60°C/14-140°F	-10-60°C/14-140°F
Storage Humidity	10-85%	10-85%
Storage Altitude	12,192m/40,000 ft.	12,192m/40,000 ft.
Limited Warranty	1 year parts and labor, including backlight	1 year parts and labor, including backlight
Technical Support	24 hours/7 days	24 hours/7 days



OSM is a registered trademark and NaViSet, No Touch Auto Adjust and Rapid Response are trademarks of NEC Display Solutions. All other brand or product names are trademarks or registered trademarks of their respective holders. Product specifications subject to change.

©2006 NEC Display Solutions of America, Inc.
All rights reserved. 8/06 ver.1.

NEC Display Solutions

500 Park Boulevard, Suite 1100
Itasca, IL 60143
866-NEC-MORE
www.necdisplay.com

Empowered by Innovation

