

Empowered by Innovation

NEC

NEC MultiSync® LCD195WXM





- Professional Wide 16:10 LCD monitor with TN-film TFT display
- Slim bezel design
- Stable and excellent picture quality with NTAA (Non-Touch-Auto-Adjustment)
- ErgoDesign®: Height adjustable stand (50 mm)
- Cable Management
- Low power consumption for reduced Total Cost of Ownership (TCO)
- Safety of investment with analog/digital interface
- Rapid Response technology (5 ms)
- Versatile installation (VESA standard)
- Ergonomics and safety complying to the highest industry standards incl. ISO 13406-2

see more.

NEC Display Solutions

NEC MultiSync® LCD195WXM

Panel Technology	TN+ film TFT
Screen Size [inch/cm]	19 / 48.1
Pixel Pitch [mm]	0.284
Viewing Angle	150° horizontal / 135° vertical (typ. at contrast ratio 10:1); 170° horizontal / 160° vertical (typ. at contrast ratio 5:1)
Contrast Ratio (typ.)	700:1
Brightness (typ.) [cd/m²]	300
Response Time (typ.) [ms]	5 (1 white / black; 4 black / white)
Colours [Mio.]	16.2
Horizontal Frequency [kHz]	31.5 - 81.0
Vertical Frequency [Hz]	56 - 76
Optimum Resolution	1440 x 900 at 60 Hz
Other Resolutions	1360 x 768; 1280 x 1024; 1280 x 960; 1152 x 870; 1152 x 864; 1024 x 768; 832 x 624; 800 x 600; 720 x 400; 640 x 480
Connectors	Digital: 1 x DVI-D; Analog: 1 x mini D-sub 15 pin
Plug & Play	VESA DDC/CI; DDC2B/2Bi; EDID Standard
Adjust Functions	Auto Adjust; Brightness; Colour Temperature Control; Contrast; Fine Adjust (analogue); Language Select; Monitor Information; NTAA (Non-Touch-Auto-Adjustment); On-Screen-Manager (OSM) lock-out; Volume; Volume
Safety and Ergonomics	CE; TCO'03; TÜV ergonomics approved; TÜV GS; Energy Star; FCC Class B; PCT/Gost; UL/C-UL or CSA; ISO 13406-2 (pixel failure class II); MPR II/ MPR III; RoHS
Power Requirements on Mode [W]	42 (typ.)
Power Requirements Power-saving Mode [W]	2
Power Supply	100-120 V/220-240 V; 0.65 A/0.3 A; integrated power supply
Ambient Temperature (operating) [°C]	+5 to +35
Ambient Humidity (operating) [%]	30 to 80
VESA Mounting [mm]	100 x 100
ErgoDesign®: Height Adjustable Stand [mm]	50
Dimensions (W x H x D) [mm]	440 x 340 x 240
Screen Tilt [°]	-5 to +20
Swivel [°]	340 to
Bezel Width [mm]	14.9
Cable Management	yes
Kensington Lock	yes
Weight [kg]	5.8
Specials	Analog/Digital Interface; NaViSet® and NaViSet® Administrator compatible; Rapid Response Technology
Audio Functions	Integrated Speakers (1W + 1W)
Colour Versions	Silver Front Bezel, Light Grey Back Cabinet; Black Front Bezel, Black Back Cabinet
Shipping Content	Monitor; Power Cable; Signal Cable VGA - VGA, DVI-D - DVI-D; Audio Cable; CD-ROM; Sales Office List; Manual
Warranty	3 years warranty including backlight



All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All rights reserved. All specifications are subject to change without notice. 07/2007