

ALLROUND INSTALLATION PROJECTOR

NEC NP3250



product
design
award

2009

Top performer for multiple business applications - installation projector with intense brightness, 5 optional bayonet lenses and PLug&Play network function (LAN/W-LAN).

- Native Resolution: 1024 x 768 (XGA)
- Brightness: 5000 ANSI Lumens
- Lens Shift (vertical and horizontal)
- Plug&Play W-LAN, thanks to Windows Vista™ certification
- Stacking Function

LCDs • Projectors • Plasmas • LCDs • **Projectors** • Plasmas • LCDs • Projectors • Projectors • LCDs • LCDs

Display	3 x 2.03 cm (0.8") p-Si LCD Panel with MLA (Aspect Ratio 4:3)
Lamp	330 W (264 W Eco Mode)
Lamp Life [hrs]	2000 (3000 Eco Mode)
Brightness ¹	5000 ANSI Lumens (approx. 80% in Eco Mode)
Contrast Ratio ¹	600:1
Lens	F= 1.7–2.2, f= 24.4–32.5 mm
Diagonal: min. / max. [cm]	76 (30") / 1270 (500")
Projection Distance [m]	0.89 – 20.8
Projection Factor	1.5 – 2.0 : 1
Frequency	Horizontal: 15–108 kHz (RGB: 24 kHz or more); Vertical: 48 – 120 Hz
Native Resolution	1024 x 768 (XGA)
Supported Resolutions	1920 x 1080 (HDTV 1080i @50/60Hz); 1600 x 1200 (UXGA); 1400 x 1050 (SXGA+); 1280 x 1024 (SXGA); 1280 x 768 (WXGA) with Advanced AccuBlend™ Technology; 1280 x 720 (HDTV 720p); 1152 x 900 (SGI. SUN); 1152 x 870 (Mac); 1024 x 768 (XGA); 832 x 624 (Mac); 800 x 600 (SVGA); 720 x 576 (SDTV 557p); 720 x 480 (SDTV 480p); 640 x 480 (VGA/Mac)
ComputerAnalog	Input: 1 x 5BNC, shared with Component Signal (YPbPr); Input: 1 x Mini D-sub 15-pin, compatible to component (YPbPr); Output: 1 x Mini D-sub 15 pin
Computer Digital	Input: 1 x DVI-D (with HDCP)
Component	Input: 1 x 3 RCA
Video	Input: 1 x RCA
S-Video	Input: 1 x Mini DIN 4-pin
Audio	Input: 1 x RCA Stereo for Video, S-Video and Component; Input: 2 x 3.5 mm Stereo Mini Jack for Computer analog and digital; Output: 1 x 3.5 mm Stereo Mini Jack (variable) for Computer 1, 2, 3 (DVI-D), Component, Video and S-Video
PC Control	Input: 1 x D-Sub 9 pin (RS-232) (male)
Remote Control	Input: 1 x 3.5 mm Stereo Mini Jack
LAN	1 x RJ45, 10/100 base-T and W-LAN by Wireless LAN Module (removable)
USB	1 x Type A (USB 2.0 high speed)
Video Signals	PAL / PAL60 / NTSC / SECAM / NTSC 4.43 / PAL-N / PAL-M
Audio Functions [W]	2 x 5 (stereo)
Zoom / Focus Adjustment	Manual / Manual
Benefits	Windows Vista™ Network Projector; 3 x Security System; Auto Color Correction; Auto Power-ON Function; DICOM Simulation; Digital 3D Reform™; Direct Power-Off Function; Help Function; HQV™ Processing for best image quality; IR Remote Control with Optional Mouse and Presentation Control; Keystone Correction (H=±40°, V=±30°); LAN and W-LAN; Lens Shift (vertical 0.5 max., horizontal ± 0.1 max.); On/Off Timer; Picture in Picture / Picture and Picture; Plug&Play; Quick Lens Replacement and 5 Optional Lenses; Stacking Function; Windows Media Content Function; Windows Network Drive; Windows Vista certified
Remote Control	Type RD433E; 3D Reform™ Control; Aspect Ratio; Automatic Picture Adjustment; Freeze-function; Help-function; IR and LAN Control; Lamp Mode Control; Laser Pointer; Magnify-function; Page Control; PC Mouse Control; Picture Mute; PIP Function; Source Select
Dimensions (W x H x D) [mm]	399 x 150 x 358 (without lens and feet)
Weight [kg]	7.5
Power Supply	100-240 V AC; 50 - 60 Hz
Power Consumption [W]	490 Normal Mode; 410 Eco Mode; 26 Stand-by Mode; 5 Power-saving Mode
Calorific Value	max. 1672 BTU (1 KWh= 3,412.14 British Thermal Unit)
Fan Noise [dB (A)]	38; < 30 Eco Mode
Safety and Ergonomics	CE; TÜV GS; RoHS
Warranty	Projector: 3 years; Lamp: 6 Months
Shipping Contents	Projector; IR Remote Control (RD-433E); Mini D-SUB Signal Cable (1.8 m); Power Cord (3 m); Remote Control Cable (4 m); W-LAN Module (NP01LM2); Users Manual; Network Set-up Guide; CD-ROM with NEC Projector User Supportware 5; Lens Cap
Optional Accessories	Ceiling Mount Kit (NP05CM); Hardcase (NP01TC); Lamp (NP06LP); YUV Cable (ADP-CV1); Lenses: NP03ZL (1.9-3.1:1); Lenses: NP04ZL (3.0-4.8:1); Lenses: NP02ZL (1.2-1.5:1); Lenses: NP05ZL (4.7-7.2:1); Lenses: NP01FL (0.8:1)



www.nec-display-solutions.co.uk

NEC Display Solutions UK Ltd, 32 Southwark Bridge Road, London SE1 9EU
Phone: 0207 202 6300, e-mail: infomail@nec-displays.com
For further information on NEC products call: 08701 201160