

Professional-grade monitor for pros.

VP2655wb

**26" (25.5" VIEWABLE)
PROFESSIONAL LCD
WITH IPS PANEL TECHNOLOGY**

The VP2655wb is one of ViewSonic's new LCD Professional Series monitors that utilizes the power of true IPS panel technology. Featuring the best 118% NTSC wide color gamut by OptiColor™, high contrast ratio and super wide 178/178 degree viewing angles. This coupled with 1920x1200 resolution, makes the VP2655wb the ultimate professional grade LCD monitor for medical facilities, scientific design, digital art, video production, architecture and any application where true color and total screen viewing is essential. 4-port USB hub for cluster free connectivity, ergonomic functions with pivot, height adjust, tilt, swivel and slim bezel make the VP2655wb an amazing monitor.



A HARD WORKING TOOL

- **118% NTSC high color gamut**
Finally true color – what you see is what you get. Takes the guesswork and rework out for color sensitive applications.
- **178/178 degree super wide viewing angles**
No image distortion or color shifting even at extreme angles.
- **1920x1200 Full HD resolution**
- **Slim bezel for multi-monitor applications**
Seamless viewing for larger formats and increased productivity with multiple window options.
- **Connections, connections**
4-port USB hub provides all the connectivity you need to stay focused on the real work.
- **Eco-mode saves up to 42% power use**
- **Full ergonomics**
Pivot, height adjust, tilt and swivel for perfect ergonomics and comfort.



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic®
See the difference®



VP2655wb

26" (25.5" VIEWABLE) PROFESSIONAL LCD WITH IPS PANEL TECHNOLOGY



LCD	Type	26" (25.5" viewable) Color TFT active matrix LCD
	Display Area	21.7" horizontal x 13.5" vertical; 25.5" diagonal
	Optimum Resolution	1920x1200
	Contrast Ratio	1000:1 static (typ), 4000:1 dynamic
	Viewing Angles	178° horizontal, 178 vertical @ contrast ratio > 10:1
	Response Time	5ms (typ)
	Light Source	Long life, 40,000 hrs. (typ)
	Brightness	400 cd/m ² (typ)
	Panel Surface	Anti-glare
VIDEO INPUT	Analog / Digital	RGB analog (75 ohms, 0.7/1.0 Vp-p) / DVI (HDCP)
	Frequency	F _H : 24~92kHz, F _V : 50~85Hz
	Sync	H/V separated (TTL), composite, sync-on-green
COMPATIBILITY	PC	VGA up to 1920x1200 non-interlaced
	Mac®*	G3/G4/G5 up to 1920x1200
CONNECTOR	Analog / Digital	15-pin mini D-sub / DVI-D
	USB	V2.0, 1-up/4-down
	Power	Internal power; 3-pin AC plug (CEE22)
POWER	Voltage	AC 100~240V, 50~60Hz (auto switch)
	Consumption	110W (typ)
CONTROLS	Basic	Power, 2, up, down, 1
	OnView®	Auto image adjust, contrast, brightness, input select (D-SUB, DVI), color adjust (sRGB, 9300K, 7500K, 6500K, 5000K, User color [R, G, B]), information, manual image adjust (H/V position, horizontal size, fine tune, sharpness, dynamic contrast, aspect ratio, eco mode), setup menu (language select, resolution notice, OSD position, OSD time out, OSD background) memory recall
ERGONOMICS		Height adjustment range 5.4", tilt -3°/+20°, swivel range 120°, pivot 0~90°
OPERATING CONDITIONS	Temperature	32~104°F (0~40°C)
DIMENSIONS (W x H x D)	Humidity	10~90% (non-condensing)
	Physical with stand	23.4" x 18.4" x 15.3" (595mm x 468mm x 388mm)
	Physical without stand	23.4" x 15.3" x 3.9" (595mm x 389mm x 100mm)
WEIGHT	Packaging	26.9" x 19.1" x 22.0" (683.3mm x 485.1mm x 558.8mm)
	Net with stand	24.2 lb. (11.0 kg)
	Net without stand	17.0 lb. (7.7 kg)
	Gross	30.1 lb. (14.0 kg)
VESA® MOUNT		200mm x 100mm
REGULATIONS		UL, CUL, FCC-B (ICES), CB, CE, TCO'03, ICES-003B, ISO13406-2, TUV/GS, TUV ERGO (covers ISO13406-2 & MPRII), TUV-S, NOM, GOST-R, HYGIENIC (20 copies), CCC, BSMI, PSB, C-TICK, KTL/MIC, SASO, WEEE, RoHS
RECYCLE/DISPOSAL		The lamp in this product contains mercury. Please dispose of in accordance with local, state or federal laws.
POWER MANAGEMENT		Meets TCO'03 standards
PACKAGE CONTENTS		LCD display, power cable, VGA cable, DVI cable, USB cable, Quick Start Guide, ViewSonic Wizard CD
WARRANTY		Three-year limited warranty on parts, labor and backlight.



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by TUV NORD.

Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

*Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Windows Vista and the Windows logo are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2009 ViewSonic Corporation. All rights reserved. [14573-01B-10/09] VP2655wb-1

ViewSonic®
See the difference®



For more product information, visit us on the web at ViewSonic.com