

AOC®

e2260Swdn



Cabinet Color	Fine Texture Black Finish
Panel	TFT Active Matrix, LED Backlight 22" Class Widescreen, 16:9 Aspect Ratio 21.5" Viewable Image Size, Diagonal
Pixel Pitch	0.248 x 0.248mm
Display Area	476.6mm x 268.1mm
Brightness	200 cd/m ² (typ)
Contrast Ratio	20,000,000:1 (dynamic)
Response Time	5ms (typical)
Viewing Angle	Horizontal: 90 Degrees (CR>10) Vertical: 60 Degrees (CR>10)
Scanning Frequency	Horizontal: 30K~83KHz Vertical: 50~75 Hz
Pixel Frequency	165MHz
Maximum Resolution	1920x1080@60Hz
Recommended Resolution	1920x1080@60Hz
Supported Resolutions	640x480@60/67/72/75Hz, 800x600@56/60/72/75Hz, 1024x768@60/70/75Hz, 1280x960@60Hz, 1280x1024@60/75Hz, 1440x900@60Hz, 1680x1050@60Hz, 1920x1080@60Hz
Color	16.7M
Signal Input	Analog: 0.7Vp-p(standard), 75 OHM, Positive
Digital Input	DVI-D with HDCP*
Connectors	Analog RGB Signal: 15-pin D-sub Male Digital Signal: 24-pin DVI-D
Power Source	Universal 100~240VAC, 50/60Hz
Power Consumption	30 Watts (Max)
Plug & Play	DDC/2B, DDC/CI
User Control	Auto/Source/Exit, Eco/Left, Wide/Right, Menu/Enter, Power
OSD Languages	16 Languages including English, French and Spanish
Regulations	cTUVus, FCC, ROHS, EPA 5.1, EPEAT Silver
Other Features	User Friendly Graphical OSD Menu, VESA 100mm Wall Mount Compliant*, Kensington Security Slot, , Includes AOC's e-Saver, Screen+ and iMenu Software
Dimensions (WxHxD mm)	Monitor: 511x373x185, Carton: 568x437x120
Dimensions (WxHxD inches)	Monitor: 20.1x14.7x7.3, Carton: 22.4x17.2x4.7
Weight	5.9 lbs (2.68 Kg) Net 8.6 lbs (3.93 Kg) Gross
Loading Qty w/pallet	20' = 840 pcs.; 40' Std = 1734 pcs.
UPC Code	685417047888

Note: Specifications are subject to change without notice. *High-bandwidth Digital Content Protection: Enables viewing of High-Definition contents. **Wall mount arm & bracket not included.