

- ••. B4250

POWERFUL, ROBUST, COMPACT

Keep business flowing smoothly with this supremely productive A4 mono printer. Perfect for very small workgroups and personal desktop applications, it produces an impressive 22 ppm with 16MB memory upgradeable to 272MB. Options include network capability, second input tray and multi-purpose feeder for different paper stock, making it a highly flexible and affordable printer for a multitude of printing tasks.

MAIN FEATURES OF THE B4250

- --- 22 pages per minute from an ultra compact printer
- --- 6.2 seconds first-page-out time reduces waiting time
- ---- Oki reliability for years of trouble-free service
- Easy-to-use drivers and features
- --- Compatibility with all major computer systems



The B4250 is the ideal high speed printer for very small workgroups or personal users.



B4250 MONO PRINTER

PRODUCT SPECIFICATION

		B4250	B4250n
Order number		01145101	01145201
Speed & throughput	Print speed	22ppm	
	Time to first print	6.2 seconds	
	Warm up time	35 seconds	
	Processor speed	266MHz PowerPC	
Print quality	Resolution	1200 x 600dpi	
Typefaces	PCL Printer fonts	86 scaleable PCL fonts, 4 bitmap fonts	
	Dot matrix fonts	Courier and line printer, various pitches + barcode fonts	
Compatibility	Printer languages	PCL5e, PCL6, Epson FX, IBM ProPrinter	
	OS Compatibility	Windows 95 / 98 / 98 SE / ME / NT4 Workstation / NT4 Server / 2000 Workstation / 2000 Professional / 2000 Server / 2000 Advanced Server / XP Professional / XP Home / NT Terminal Server Edition and 2000 Terminal Server with Citrix Metaframe 1.8 or Citrix Metaframe XP 1.0. Mac OS 8.6 (or higher), Mac OS X (10.1 or higher), Variants of Unix and Linux via PPDs	
	Standard interfaces	IEEE1284 Bi-directional parallel, USB 2.0	IEEE1284 Bi-directional parallel, USB 2.0, 10/100BaseTX Ethernet
	Optional interfaces	10/100 BaseTX Ethernet, 25 Pin RS232C serial	25 pin RS232C serial
Memory	Standard/Max. RAM	16/272MB	
	Flash memory	8/16MB option for storage of fonts, forms and macros	
Paper handling	Internal tray capacity	250 sheets, 60 – 105gsm (16 – 28 lb)	
	Internal tray sizes	A4, A5, B5(JIS), A6, Letter, Legal 13, Legal 14, Executive	
	Manual feeder capacity	Single sheet	
	Manual feeder	60 – 120gsm (60 – 32lb)	
	Optional paper input trays	2nd tray: 500 sheets (20lb), 60 – 105gsm (16 – 28 lb)	
	Second tray sizes	A4, A5, B5(JIS), Letter, Legal 13, Legal 14, Executive	
	Optional envelope/multi-feeder capacity	100 sheets (20lb)/50 envelopes	
	Optional envelope/multi-feeder sizes	A4, A5, B5(JIS), A6, Letter, Legal 13, Legal 14, Executive, envelopes: Monarch, Com-9, Com-10, DL, C5	
	Output capacity	150 sheets face down, 50 sheets face up	
Operating conditions	Temperature/humidity (operating)	10C – 32C (50 - 90F), 20–80% RH non-condensing	
	Storage	-10C – 43C (14 - 110F), 10–90% RH non-condensing	
Power requirements	Power supply	230 VAC */- 10%, 50 or 60Hz */- 2%	
	Power consumption	Powersave -14W; Idle - 66W, Operating - 360W	
Physical	Noise	53dB(A) or less	
	Size (HxWxD)	200 x 355 x 395mm	
	Weight	Approx. 9kg	
	Max. monthly duty cycle	30,000	
Warranty	Standard	One year return to depot	
Supplies	Toner	2,500 pages @ 5% coverage (Oki type 9 toner)	
	Image drum	Up to 25,000 pages (continuous print), 17,000 pages @ 3 pages per job	





OKI EUROPE, PART OF OKI ELECTRIC

Only use genuine Oki Original consumables to ensure the best quality and performance from your hardware. Non Oki Original products may damage your printer's performance and invalidate your warranty. $Specifications \ subject \ to \ change \ without \ notice. \ All \ trademarks \ acknowledged.$

OKI EUROPE LTD, CENTRAL HOUSE, BALFOUR ROAD, Hounslow, Middlesex, TW3 1HY, United Kingdom TEL: +44(0) 20 8219 2190

FAX: +44(0) 20 8219 2199

