

ML520/ML521 ELITE DOT MATRIX PRINTER



- ❖ ML520 ELITE
- ❖ ML521 ELITE
- ❖ 9-PIN DOT MATRIX PRINTER

INTELLIGENT DESIGN AND OKISMART® PAPER HANDLING

The ML520/ML521 Elite narrow and wide carriage models, feature OkiSmart® advanced paper handling technology making them a leading force as some of the fastest and most flexible printers in the dot matrix market.

MAIN FEATURES OF THE ML520/ML521 PRINTER

- ❖ 80/136 column dot matrix printers
- ❖ 9-pin print head with OkiSmart® print head (automatically variable head-gap and forms adjustment)
- ❖ Up to 433 characters per second print speed
- ❖ Multi-part paper-handling (original + 4 copies) and easy switching between multiple paper types
- ❖ High speed printing for general use - multi-part forms, listings and data processing



OKI

ML520/ML521 ELITE DOT MATRIX PRINTER

PRODUCT SPECIFICATION

		ML520 ELITE	ML521 ELITE
General	Number of pins	9	
	No. of multi-part forms	5 (one original + 4 copies)	
Speed & throughput	High speed draft (12cpi & 10cpi)	433cps	
	Utility (12cpi & 10cpi)	325cps	
	Near letter quality (12cpi & 10cpi)	81cps	
	Fastest print speed (10cpi)	433cps	
Font & print features	Carriage width (10cpi)	80 columns	136 columns
	Max. in compressed mode	160 columns	272 columns
	Character pitch	10/12/15/17.1/20 pitch & proportional	
	Graphics resolution	Up to 240 x 216 dpi	
	Typeface & Font	NLQ-Courier, NLQ-Gothic, OCR-B, High Speed Draft, Utility + Barcodes	
	Typestyle	Emphasised, Enhanced, Double Width, Double Height, Italics, Bold, Superscript, Subscript, Underline, Overscore	
Emulations & interfaces	Printer emulations	Epson FX, IBM ProPrinter/Graphics, Oki MICROLINE	
	Standard interfaces	Centronics Parallel	
	Optional interfaces	Serial RS 232C/RS 422A/Current Loop	
Paper-handling	Continuous paper	76 – 254mm	76 – 406mm
	Continuous envelope	165 x 91mm	239 x 102mm
	First printable line (from top of page)	8.9mm	
	Standard	Paper parking, Zero tear-off, Autoload single sheet, Rear push tractor	
	Optional	Pull tractors, Single/dual bin sheet feeder, Roll paper stand (ML520 Elite only), Bottom tractors with stand and zero tear-off	
Physical	Dimensions (HxWxD)	165 x 431 x 380mm	165 x 585 x 380mm
	Weight	8kg	10.5kg
	Memory	Standard buffer 64KB	
	Noise level	57dB(A)/52dB(A) quiet mode	
Power	Power requirements	230V AC	
	Frequency	50/60Hz	
Reliability	Print head life	200 million characters	
	Ribbon life	4 million characters (re-inking cartridge)	
Supplies life	MTBF	6,000 hours	

OKI

*Ok!, Network Solutions
for a Global Society*

OKI SYSTEMS (UK) LTD, PART OF OKI ELECTRIC

OKI SYSTEMS (UK) LTD,
550 DUNDEE ROAD,
SLOUGH, BERKSHIRE
SL1 4LE
UNITED KINGDOM

TEL: +44 (0)1753 819819
FAX: +44 (0)1753 819899

WWW.OKI.CO.UK

Only use genuine Oki Original consumables to ensure the best quality and performance from your hardware. Non Oki Original products may damage your printer's performance and invalidate your warranty. Specifications subject to change without notice. All trademarks acknowledged.



As an ENERGY STAR Partner, Oki Europe Ltd has determined that this product meets the ENERGY STAR guidelines for energy efficiency

09400929
© 2003 Oki Europe Ltd.