

B4350 MONO PRINTERS



- …❖ **B4350**
- …❖ **B4350n**
- …❖ **B4350nPS**

POWERFUL, ROBUST, COMPACT

A flexible mono printer compatible with all major operating systems, handling legacy environments, PCL and Postscript. The B4350 features point-of-service applications, as well as a user-friendly front panel so that you always know what your printer is doing. It makes it the ideal choice where performance and a compact footprint is a necessity for businesses, such as hotel receptions or a retail environment. To minimize intervention and reduce cost per copy on mailshots, reports and charts for example, it also boasts a high capacity toner cartridge. Professional printing made to look easy.

MAIN FEATURES OF THE B4350

- …❖ 22 ppm from an ultra compact printer
- …❖ 6.2 seconds first-page-out time reduces waiting time
- …❖ Oki reliability for years of trouble-free service
- …❖ Choice of toner cartridge sizes ensures low cost of ownership
- …❖ Compatibility with all major computer and network operating systems
- …❖ Flexible upgrade options for the future



The B4350 mono printers are designed for small workgroups of 3-5 people.

OKI

B4350 MONO PRINTERS

PRODUCT SPECIFICATION

		B4350	B4350N	B4350NPS
Order number		01145301	01145401	01145501
Speed & throughput	Print speed	22ppm		
	Time to first print	6.2 seconds		
	Warm up time	35 seconds		
	Processor speed	266MHz PowerPC		
Print quality	Resolution	1200 x 600 dpi		
Typefaces	PCL Printer fonts	86 scaleable PCL fonts, 4 bitmap fonts		
	Dot matrix fonts	Courier and line printer, various pitches + barcode fonts		
	PostScript fonts	N/A	136 fonts	
Compatibility	Printer languages	PCL5e, PCL6, Epson FX, IBM ProPrinter	PCL5e, PCL6, Epson FX, IBM ProPrinter, PostScript3	
	OS Compatibility	Windows 95 / 98 / 98 SE / ME / NT4 Workstation / NT4 Server / 2000 Workstation / 2000 Professional / 2000 Server / 2000 Advanced Server / XP Professional, Home / NT Terminal Server Edition and 2000 Terminal Server with Citrix Metaframe 1.8 or Citrix Metaframe XP 1.0. Mac OS 8.6 (or higher), Mac OS X (10.1 or higher), Variants of Unix and Linux via PPDs		
	Standard interfaces	IEEE1284 Bi-directional parallel, USB 2.0	IEEE1284 Bi-directional parallel, USB 2.0, 10/100BaseTX Ethernet	
	Optional interface	25Pin RS232C serial 10/100BaseTX Ethernet	25 Pin RS232C serial	
	Network & protocols	10/100 BaseTX Ethernet card with internal web server for printer and network card set-up and management. Includes POP3 and SMTP mail client for submission of print jobs and for alerts. All major network protocols supported – TCP/IP, Netware, EtherTalk and NetBEUI. TCP/IP :-ARP, RARP, IP, TCP, ICMP, UDP, LPR, FTP, TELNET, HTTP(IPP), BOOTP, DHCP, AutoIP, SNMP, DNS, uPnP, SLP, JetDirect protocols. Netware 3.x, 4.x, 5.x and 6 with full NDS and NDPS support:- QServer over IP and IPX, R-Printer, N-Printer, NCP, SPX, IPX, SAP, RIP, NDPS supported via dedicated OKI NDPS Gateway. EtherTalk:- ELAP, AARP, DDP, AEP, NBP, ZIP, RTMP, ATP, PAP . NetBEUI:- SMB, CIFS, WINS, NetBIOS		
	Utilities	Oki PrintSuperVision web based printer management software for Oki and other brand printers. Oki Admin Manager and quick setup utilities. Oki Utility, Oki NDPS Gateway, plug-ins for 3rd party management utilities		
Memory	Standard/Max. RAM	16/272MB	32/272MB	
	Flash memory	8/16MB option for storage of fonts, forms and macros		
Paper handling	Internal tray capacity	250 sheets, 60 - 105gsm (16 - 28 lb)		
	Internal tray sizes	A4, A5, B5(JIS), A6, Letter, Legal 13, Legal 14, Executive		
	Manual feeder capacity	Single sheet		
	Manual feeder	60 - 120gsm (60 - 32lb)		
	Optional paper input trays	2nd tray:500 sheets (20lb), 60 - 105gsm (16 - 28 lb)		
	Second tray sizes	A4, A5, B5(JIS), Letter, Legal 13, Legal 14, Executive		
	Optional envelope/multi-feeder capacity	100 sheets (20lb)/50 envelopes		
	Optional envelope/multi-feeder sizes	A4, A5, B5(JIS), A6, Letter, Legal 13, Legal 14, Executive, envelopes: Monarch, Com-9, Com-10, DL, C5		
	Output capacity	150 sheets face down, 50 sheets face up		
Operating conditions	Temperature/humidity (operating)	10C – 32C (50 – 90F), 20-80% RH non-condensing		
	Storage	-10C – 43C (14 – 110F), 10-90% RH non-condensing		
Power requirements	Power supply	230VAC +/- 10%, 50/60Hz +/- 2%		
	Power consumption	Powersave – 14W, Idle – 66W, Operating – 360W.		
Physical	Noise	53dB(A) or less		
	Size (HxWxD)	215 x 355 x 395mm		
	Weight	Approx. 9kg		
	Max. monthly duty cycle	30,000		
Warranty	Standard	One year return to depot		
Supplies	Toner	Standard capacity toner: 2,500 pages @ 5% coverage, high capacity toner: 6,000 pages @ 5% coverage (Oki type 9 toner)		
	Image drum	Up to 25,000 pages (continuous print), 17,000 pages @ 3 pages per job		

OKI

Only use genuine Oki Original consumables to ensure the best quality and performance from your hardware.
Non Oki Original products may damage your printer's performance and invalidate your warranty.
Specifications subject to change without notice. All trademarks acknowledged.

Oki, *Network Solutions*
for a Global Society

OKI EUROPE, PART OF OKI ELECTRIC

OKI EUROPE LTD,
CENTRAL HOUSE, BALFOUR ROAD,
HOUNSLAW, MIDDLESEX, TW3 1HY,
UNITED KINGDOM
TEL: +44(0) 20 8219 2190
FAX: +44(0) 20 8219 2199
WWW.OKIEUROPE.COM



As an ENERGY STAR Partner, Oki Europe Ltd has determined that this product meets the ENERGY STAR guidelines for energy efficiency