

LifeBook P7230 Notebook

Providing unheard of functionality in a truly mobile form factor, the LifeBook P7230 notebook offers exceptional performance with a bright Crystal View display, long battery life¹, and your choice of advanced Mobile Technologies.

The LifeBook P7230 notebook is the ultimate travel companion.

BENEFITS

Portable Performance

The LifeBook P7230 notebook is the ideal mobile solution for professionals, students, and technology enthusiasts alike. With a configurable weight of under 3 pounds, overall dimensions of only 10.74" x 7.91" x 1.17", and a power-efficient Intel® Core™ Solo U1400 Ultra Low Voltage Processor, the LifeBook P7230 notebook delivers on its ultra-portability, ultra-performance promise. The second modular battery dramatically extends your time away from a power outlet. With the exhaustive time now needed to travel, it's good to know your notebook will be ready to entertain you or let you finish that report.

The optional built-in camera, centered above the display, is ideal for visually demonstrating a complicated procedure over the web, illustrating what something actually looks like, or just messaging with your buddies.

Security

The LifeBook P7230 notebook has an integrated biometric fingerprint sensor that puts industryleading data security at your fingertips. With the included Softex OmniPass software, you only need to swipe your finger or remember a single master password to keep all of your system log-ins and data protected. The fingerprint sensor also doubles as a scroll button once you have logged in. Additionally, the LifeBook P7230 notebook has an embedded Trusted Platform Module (TPM) that can store data file passwords/ keys on a microchip and help protect your data. With a security lock slot, you can keep your physical assets safe as well. In a worse-case scenario, Computrace will help track down your stolen notebook.

Flexible Communication Options

The P7230 notebook conforms to your lifestyle: you have complete flexibility on how you connect to your office network and the Internet, via the integrated V.90 modem, the Gigabit Ethernet LAN or the Intel PRO/Wireless Network

Connection (Tri-Mode 802.11a/b/g) wireless LAN. You also have the option of Atheros Super AG® Wireless LAN (802.11a/b/g, not available on pink unit) for your wireless connection.

Complete Array of Industry Standard Ports for Quick Connections

The LifeBook P7230 notebook design includes a wide variety of ports that you would typically find on a notebook computer twice its size, including two USB 2.0 ports, IEEE 1394, external monitor, RJ-45, RJ-11 ports, and headphone and microphone jacks. For fast and easy storage/ transfer of music, pictures and data, the LifeBook P7230 notebook is equipped with a dedicated Memory Stick PROTM/SD/xD slot.

Versatile Design

The unique modular bay of the LifeBook P7230 notebook can be adapted to your specific work style. The bay accepts an optional bay battery or a weight-saver module for extreme portability. When used with a bay battery, your work can be extended up to 9¹ hours wherever your work takes you. It can accommodate either the DVD/CD-RW combo drive or a modular Dual-Layer Multi-Format DVD Writer for the ultimate in DVD reading and writing functionality. Its wide display format with 16 million vibrant colors presents an incredibly crisp view of your DVDs or projects.

A port replicator makes leaving your work area a snap. Simply remove your notebook from the port replicator—you don't have to deal with your network or a tangle of peripheral cables. Productivity goes up while frustration goes down.


Quality and Reliability

The close interaction between Fujitsu design, manufacturing, and service engineers creates some of the highest quality products offered in the PC market. In a time when most PCs are assembled by third-party vendors, Fujitsu takes pride in its world-class, tightly integrated design and manufacturing capabilities.



OVERVIEW

- Ultra-light and portable, configurable to approximately 2.6 lbs.
- Built-in modular bay can be fitted with modular Dual-Layer Multi-Format DVD Writer, a bay battery, or a weight-saver module
- Modular second battery option for up to 9¹ hours of total battery life
- Crystal View display technology with wide screen format for the ultimate video experience
- Fully secure with embedded TPM security chip, fingerprint sensor, and a security lock slot
- Designed for mobile performance with an energy-efficient Intel[®] Core[™] Duo U2500 (not available on pink unit) or Intel[®] Core[™] Solo U1400 Ultra Low Voltage Processor.
- Choice of Intel PRO/Wireless 3945BG Network Connection (Tri-Mode 802.11a/b/g) or Atheros Super AG[®] Wireless LAN (802.11a/b/g; not available on pink unit), and Bluetooth
- Built-in Memory Stick PRO, SD, and xD picture card slot
- Superior connectivity with a suite of ports typically found on larger notebooks
- Optional built-in camera for video messaging



Key Specifications

	Intel® Core Solo U1400 Ultra Low Voltage Processor (1.20 GHz, 2 MB L2 cache, 533 MH FSB) or Intel Core Duo U2500 Ultra Low Voltage Processor (1.20 Ghz, 2 MB L2 cache, 533 MHz FSB; not available as an option for pink unit)				
Chipset	Intel® 945GMS Express				
System Memory	One DIMM slot; max. 2 GB (2 GB x 1); DDR2 667 MHz, So-DIMM				
Display	LCD 10.6" Crystal View TFT WXGA display				
	Video Controller Intel® Graphics Media Accelerator 950. Dynamic Video Memory Technolog (DVMT) responds to application requirements and efficiently allocates the proper amount of system memory (up to 224 MB) for optimal graphics and system performance				
	Resolution	olution Maximum internal display: 1280 x 768, 16M colors External monitor display: (max.): 1600 x 1200, 16M colors Simultaneous display (max.) 1024 x 768 16M colors			
Hard Drive ³	80 GB (not available on pink unit), 60 GB or 40 GB; (4200 rpm) P-ATA Ultra DMA 100; shock-mounted, and protected by intelligent shock sensor technology				
Optical Drive			-Format DVD Writer	Modular DVD/CR-RW Combo Drive	
	2.4x DVD+R I 4x DVD-R 2x DVD-RW 4x DVD+R 2.4x DVD+RV	DL 2x I 8x I 24x 10x	DVD-RAM DVD-ROM CD-R CD-RW CD-ROM	8x DVD 10x CD-RW 24x CD-R 24x CR-ROM	
Audio	Sigmatel STAC9228 compliant codec, 18 bits stereo full duplex codec with independent				
	and variable sampling rates Headphone jack Microphone (mono)/line-in jack Internal built-in microphone included (2x digital microphones)				
Communication Wireless Communication	Multinational⁴ 56K⁵ V.90 Azalia I/F Modem (MDC1.5) modem and 10/100/1000 Gigabit Ethernet LA				
	Intel® PRO/Wireless 3945BG Network Connection (Tri-Mode 802.11a/b/g), or Atheros Super AG® Wireless LAN (802.11a/b/g, not an available option on pink unit). Bluetooth (v2.0) Personal Area Network (PAN) for file transfer and data synchronization with other Bluetooth devices Wi-Fi®, CCX and WPA certified; diversity antenna				
	with other Blu Wi-Fi®, CCX a	etooth devic	es tified; diversity antenn	a	
User Interfaces	with other Blu Wi-Fi®, CCX a 82-key keybo Integrated tou	ietooth device and WPA cer ard with 18 n achpad point	es tified; diversity antenn nm key pitch and 2 mn ing device with scroll I	a n key stroke outton	
User Interfaces Notebook Ports	with other Blu Wi-Fi®, CCX a 82-key keybo	netooth device and WPA certard with 18 nuchpad point 45)	es tified; diversity antenna nm key pitch and 2 mn	a n key stroke outton	
	with other Blu Wi-Fi®, CCX a 82-key keybo Integrated to Ethernet (RJ- Modem (RJ-1 Two USB 2.0 Headphone/li Ethernet (RJ- Three USB 2. Line-Out Jac	uetooth device and WPA certard with 18 nuchpad point 45) 1) ine-out jack 45) 0	es iffied; diversity antenn nm key pitch and 2 mi ng device with scroll I IEEE 1394 (4-pin) External video Docking connect S-Video Out External video DC Power	a n key stroke outton or	
Notebook Ports Port Replicator Ports Card Slots	with other Blu Wi-Fi®, CCX a 82-key keyboo Integrated to Ethernet (RJ- Modem (RJ-1 Two USB 2.0 Headphone/li Ethernet (RJ- Three USB 2. Line-Out Jacl One Type I/II One shared s	netooth device and WPA certard with 18 nuchpad point 45) 1) ne-out jack 45) 0 4 PCMCIA slot lot for: Memorial with 45 lot	es iffied; diversity antenn nm key pitch and 2 mn ing device with scroll I IEEE 1394 (4-pin) External video Docking connect S-Video Out External video DC Power c, 32-bit PC CardBus a bry Stick®, Memory Sti	a n key stroke button or rchitecture ck PRO™, Secure Digital (SD)	
Notebook Ports Port Replicator Ports	with other Blu Wi-Fi®, CCX a 82-key keyboo Integrated tot Ethernet (RJ- Modem (RJ-1 Two USB 2.0 Headphone/li Ethernet (RJ- Three USB 2. Line-Out Jacl One Type I/II One shared s Trusted Platfc AuthenTec Fir 15cm/sec slic Security lock Computrace	netooth device and WPA certard with 18 nuchpad point 45) 1) Ine-out jack 45) 0 0 C PCMCIA slot lot for: Memorr Module (negerprint Sertal slot) et speed (registed slot) BIOS Persist	es iffied; diversity antenn m key pitch and 2 mn ing device with scroll I IEEE 1394 (4-pin) External video Docking connect S-Video Out External video DC Power a, 32-bit PC CardBus a bry Stick®, Memory Sti TPM), TCG 1.1b-comp isor with TruePoint Ter places scroll button) e Module	a n key stroke button or rchitecture ck PRO TM , Secure Digital (SD)	
Notebook Ports Port Replicator Ports Card Slots	with other Blu Wi-Fi®, CCX a 82-key keyboo Integrated tou Ethernet (RJ- Modem (RJ-1 Two USB 2.0 Headphone/li Ethernet (RJ- Three USB 2. Line-Out Jacl One Type I/II One shared s Trusted Platfo AuthenTec Fir 15cm/sec slic Security lock Computrace Optional built	netooth device and WPA certard with 18 nuchpad point 45) 1) ne-out jack 45) 0 4 PCMCIA slot lot for: Memory Module (ngerprint Serte slot BIOS Persistin web cam	es iffied; diversity antenn nm key pitch and 2 mn ing device with scroll I IEEE 1394 (4-pin) External video Docking connect S-Video Out External video DC Power 7, 32-bit PC CardBus a bry Stick®, Memory Sti TPM), TCG 1.1b-comp isor with TruePoint Tec places scroll button) e Module 1.3 megapixel	rchitecture ck PRO TM , Secure Digital (SD)	
Notebook Ports Port Replicator Ports Card Slots Security Camera	with other Blu Wi-Fi®, CCX a 82-key keybo Integrated tou Ethernet (RJ-Modem (RJ-1 Two USB 2.0 Headphone/Pil Ethernet (RJ-Three USB 2. Line-Out Jacl One Type I/II One shared s Trusted Platfa AuthenTec Fir 15cm/sec slic Security lock Computrace Ioptional built Main battery: plus bay batte	netooth device and WPA certard with 18 nuchpad point 45) 1) Inne-out jack 45) 0 K PCMCIA slot lot for: Memory Module (ngerprint Sertal BIOS Persist -in web cam Lithium ion (tery, up to 9 here)	es iffied; diversity antenn m key pitch and 2 mn ing device with scroll I IEEE 1394 (4-pin) External video Docking connect S-Video Out External video DC Power , 32-bit PC CardBus a ory Stick®, Memory Sti TPM), TCG 1.1b-comp isor with TruePoint Teo places scroll button) e Module 1.3 megapixel 6-cell: 10.8V, 5800 mA	a n key stroke button or rchitecture ck PRO™, Secure Digital (SD) sliant chnology; Ah, 37 WHr) up to 5.45 hours:	
Notebook Ports Port Replicator Ports Card Slots Security Camera Battery Life ¹	with other Blu Wi-Fi®, CCX a 82-key keybo Integrated tou Ethernet (RJ-Modem (RJ-1 Two USB 2.0 Headphone/lil Ethernet (RJ-Three USB 2. Line-Out Jacl One Type I/II One shared s Trusted Platfo AuthenTec Fir 15cm/sec slic Security lock Computrace Optional built Main battery: Il Bay battery: I	netooth device and WPA certard with 18 nuchpad point 45) 1) ine-out jack 45) 0 c PCMCIA slot lot for: Memorm Module (regerprint Sertal BIOS Persist in web cam Lithium ion (erry, up to 9 huithium ion	es iffied; diversity antenn m key pitch and 2 mi ing device with scroll I IEEE 1394 (4-pin) External video Docking connect S-Video Out External video DC Power 3, 32-bit PC CardBus a ory Stick®, Memory Sti TPM), TCG 1.1b-comp sor with TruePoint Teo places scroll button) e Module 1.3 megapixel 6-cell: 10.8V, 5800 m/ ours 6-cell, 10.8V, 2300 mAl	a n key stroke button or rchitecture ck PRO™, Secure Digital (SD) sliant chnology; Ah, 37 WHr) up to 5.45 hours: n, 25 WHr)	
Notebook Ports Port Replicator Ports Card Slots Security Camera	with other Blu Wi-Fi®, CCX a 82-key keyboo Integrated tot Ethernet (RJ- Modem (RJ-1 Two USB 2.0 Headphone/li Ethernet (RJ- Three USB 2.0 Cone Type I/II One shared s Trusted Platfic AuthenTec Fin 15cm/sec slic Security lock Computrace I Optional built Main battery: plus bay battery: plus bay battery: Lauto-sensing 10.74" x 7.91" x	netooth device and WPA certard with 18 nuchpad point 45) 1) ine-out jack 45) 0 c PCMCIA slot lot for: Memorm Module (negerprint Sertes speed (reps slot BIOS Persist in web cam Lithium ion (edual voltage 1.06" – 1.17"; A	es iffied; diversity antenn nm key pitch and 2 mn ing device with scroll I IEEE 1394 (4-pin) External video Docking connect S-Video Out External video DC Power 1, 32-bit PC CardBus a bry Stick®, Memory Sti TPM), TCG 1.1b-comp isor with TruePoint Ter places scroll button) e Module 1.3 megapixel 6-cell: 10.8V, 5800 m/ ours i-cell, 10.8V, 2300 mAl support, 100-240V Al approximately 2.63 lbs. w	a h key stroke button or rchitecture ck PRO TM , Secure Digital (SD) bliant chnology; Ah, 37 WHr) up to 5.45 hours: n, 25 WHr) C supplying 16V DC, 3.75A th a 6-cell battery and weight saver, 2.96 lbs.	
Port Replicator Ports Card Slots Security Camera Battery Life¹ AC Adapter Dimensions and Weight	with other Blu Wi-Fi®, CCX a 82-key keyboo Integrated tot Ethernet (RJ- Modem (RJ-1 Two USB 2.0 Headphone/li Ethernet (RJ- Three USB 2. Line-Out Jacl One Type I/II One shared s Trusted Platfc AuthenTec Fir 15cm/sec slic Security lock Computrace I Optional built Main battery: plus bay battery: plus bay battery: I Auto-sensing 10.74" x 7.91" x with 6-cell batte	netooth device and WPA certard WPA certard With 18 nuchpad point 45) Ine-out jack 45) Commodule (18 nuchpad point 45) Commodule (es iffied; diversity antenn m key pitch and 2 mn ing device with scroll I IEEE 1394 (4-pin) External video Docking connect S-Video Out External video DC Power 1, 32-bit PC CardBus a bry Stick®, Memory Sti TPM), TCG 1.1b-comp isor with TruePoint Tec places scroll button) e Module 1.3 megapixel 6-cell: 10.8V, 5800 m/s ours i-cell, 10.8V, 2300 mAl support, 100-240V Ac pproximately 2.63 lbs. widrive, 3.08 lbs. with mod	a h key stroke button or rchitecture ck PRO™, Secure Digital (SD) Jiant chnology; Ah, 37 WHr) up to 5.45 hours: n, 25 WHr) C supplying 16V DC, 3.75A th a 6-cell battery and weight saver, 2.96 lbs. ular bay battery and 6-cell battery	
Notebook Ports Port Replicator Ports Card Slots Security Camera Battery Life¹ AC Adapter	with other Blu Wi-Fi®, CCX a 82-key keybo Integrated tot Ethernet (RJ- Modem (RJ-1 Two USB 2.0 Headphone/Ii Ethernet (RJ- Three USB 2. Line-Out Jacl One Type I/II One shared s Trusted Platfc AuthenTec Fir 15cm/sec slic Security lock Computrace I Optional built Main battery: plus bay batte Bay battery: I Auto-sensing 10.74" x 7.91" x with 6-cell batte 41° F to 95° F/5	uetooth device and WPA cerrard with 18 nuchpad point 45) 1) Inne-out jack 45) 0 K PCMCIA slot lot for: Memore form Module (ngerprint Series lot BIOS Persist Lithium ion (engual voltage 1.06" – 1.17"; // erry and optical of F to 35° C (and to the control of the	es ified; diversity antenn m key pitch and 2 mr ing device with scroll I IEEE 1394 (4-pin) External video Docking connect S-Video Out External video DC Power C, 32-bit PC CardBus a bry Stick®, Memory Sti TPM), TCG 1.1b-comp sor with TruePoint Tec claces scroll button) e Module 1.3 megapixel 6-cell: 10.8V, 5800 m/ ours i-cell, 10.8V, 2300 mAl support, 100-240V AC Approximately 2.63 lbs. with mod mbient temperature); 200 module 1.3 megapixel 1.3 m	a h key stroke button or rchitecture ck PRO TM , Secure Digital (SD) bliant chnology; Ah, 37 WHr) up to 5.45 hours: n, 25 WHr) C supplying 16V DC, 3.75A th a 6-cell battery and weight saver, 2.96 lbs.	

Service & Regulatory Information

	8 2 3
Compliance	FCC Part 15B Class B; FCC Part 15C; IC ICES-003 Class B and RSS-210; FCC Part 15 E UL-cUL Listed FCC Part 68; IC CS-03
Warranty ⁶	One- or three-year International Limited Warranty on select corporate configurations; 24/7 technical support; Fujitsu extended service plans available.



Fujitsu Computer Systems Corporation

Enterprise Sales:

1.800.831.3183 us.fujitsu.com/computers

Consumer Sales (24/7): 1.800.FUJITSU www.shopfujitsu.com

Battery life estimates reflect the results of BAPCo MobileMark2005 Productivity Workloads performed upon systems with battery life setting enabled on Windows* XP operating systems. Actual battery life will vary based on screen brightness, applications used, features selected, power management settings, battery conditioning, and other customer preferences. DVD/CD-RW, DVD Writer, LAN, wireless LAN or hard drive usage may also have a significant impact on battery life.

battery life.

2) Preinstalled with a free 90-day trial version of Symantec Norton Internet Security 2007. The 90-day trial version is activated upon user's acceptance of software license agreement. After 90 days, the user must purchase a subscription from Symantec to download latest virus definitions.

3) One gigabyte (GB) = one billion bytes; accessible capacity will be less and actual capacity depends on the operating environment and formatting.

4) The internal modems on all Fujitsu notebooks

4) The internal modems on all Fujitsu notebooks from Fujitsu Computer Systems Corporation are only qualified for use with telephone systems in selected countries, including the United States and Canada. For a list of certified countries, please check http://www.computers.us.fujitsu.com/modems.

 Actual speeds over U.S. telephone lines vary, and are less than 56Kbps due to the current FCC regulations and line conditions.

and line conditions.

6) Service and warranty turnaround time may vary by country and product. International warranty valid only for products purchased in North, Central, and South America

Fujitsu, the Fujitsu logo, and LifeBook are registered trademarks of Fujitsu Limited. Intel, Intel logo, Intel Inside, Intel Inside, Intel Inside, Intel Inside, Intel Inside, Intel Inside logo, Intel Centrino, Intel Centrino logo and Pentium are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries. Wi-Fi is a registered trademark of the Wireless Ethernet Compatibility Alliance (WECA). Genuine Windows Vista, Microsoft, And Windows are trademarks or registered trademarks of Microsoft Corporation in the United States and/ or other countries. Memory Stick is a registered trademark and Memory Stick PRO is a trademark of Sony Corporation and/or its affiliates. Adobe Acrobat Reader is a registered trademark of Adobe Systems, Inc. Quicken is a registered trademark of Intuit, Inc. Norton AntiVirus is a registered trademark of Symantec Corporation. All other trademarks mentioned herein are the property of their respective owners. Product description data represents Fujitsu design objectives.

© 2007 Fujitsu Computer Systems Corporation. All rights reserved. FPC58-1705-02 7/07. 07.0640









