

# fi-6130/fi-6230

## Color Duplex Workgroup Scanners

Enhanced for the ultimate in performance and reliability

- ▶ Fast, 40ppm / 80ipm scanning in monochrome and grayscale
- ▶ Exceptional 300 dpi color scanning at 30ppm / 60ipm
- ▶ Advanced paper handling technology for the ultimate in feeding reliability
- ▶ Robust 50-page Automatic Document Feeder (ADF) with enhanced hard embossed card scanning
- ▶ Comes with Kofax® VRS® Professional, Adobe® Acrobat® Standard, and ScandAll Pro



**FUJITSU**

THE POSSIBILITIES ARE INFINITE

# fi-6130/fi-6230

## Color Duplex Workgroup Scanners

Discover a new level of front-office productivity with the fi-6130 and fi-6230 documents scanners. Enhanced with innovative features, the Fujitsu fi-6130 and fi-6230 scanners offer outstanding price/performance value in a compact footprint, conserving both space and budget. With duplex scanning performance of up to 80 images per minute in monochrome and grayscale, the fi-6130 and fi-6230 also delivers uncompromised high-resolution performance of up to 60 images per minute in color at an astounding 300 dpi. Engineered with one of the most advanced paper separation features in their class, the fi-6130 and fi-6230 are the first workgroup scanners equipped with reversing roller technology\*, resulting in exceptional feeding reliability for an even wider variety of document weights. Furthermore, the automatic document feeder (ADF), capable of scanning document up to 10 feet long, is also robust enough to feed up to three hard cards continuously or an embossed card up to 1.4 mm in thickness. Additionally, the fi-6130 and fi-6230 harmoniously combines the security of Ultrasonic Double Feed Detection with the efficiency of Intelligent MultiFeed Function (IMFF) so that intentional double-feeds, such as a taped receipt or sticky note, can be manually bypassed while double-feed detection is enabled.

### Fully Loaded One Box Solution.

Fujitsu fi-6130 and fi-6230 workgroup scanners conveniently include everything in the box to get organizations up and scanning. With the full version of Kofax VRS® Professional, Adobe® Acrobat® Standard, and ScandAll Pro software, users get image enhancement functionality as well as the option of scanning directly to PDF, file, print or batch. And the one-year Limited Warranty, along with eligibility for our Advance Exchange Program, provides peace-of-mind. For full details on the Limited Warranty and on all service programs, go to [www.ImageService.com](http://www.ImageService.com) or call (800) 626-4686.

### About Fujitsu Computer Products of America, Inc.

Fujitsu Computer Products of America, Inc. is a subsidiary of Fujitsu Limited, a leading provider of customer-focused IT and communications solutions for the global marketplace. FCPA provides innovative solutions for the U.S. marketplace. Current product and service offerings include high performance hard disk drives, scanners and scanner maintenance, palm vein recognition technology, 10Gb Ethernet switches and degaussers.

\* Statement true as of March 2008

Fujitsu Computer Products of America, Inc.  
<http://us.fujitsu.com/fcpa>

1255 East Arques Avenue Sunnyvale, CA 94085-4701. (800) 626-4686 (408) 746-7000 [info@fcpa.fujitsu.com](mailto:info@fcpa.fujitsu.com)

©2008 Fujitsu Computer Products of America, Inc. All rights reserved. Fujitsu and the Fujitsu logo are registered trademarks and The Possibilities are Infinite is a trademark of Fujitsu Limited. Adobe and Acrobat are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States and/or other countries. Microsoft, Windows and Vista are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. ISIS is a registered trademark of Pixel Translations, a division of Captiva Software Corporation. VRS is a registered trademark of Kofax Image Products, Inc. As an ENERGY STAR® Partner, Fujitsu Ltd. has determined that this product meets the ENERGY STAR® guidelines for energy efficiency. ENERGY STAR® is a U.S. registered trademark. All other trademarks are the property of their respective owners.

All statements herein are valid only in the U.S. for U.S. residents, are based on normal operating conditions, are provided for informational purposes only, and are not intended to create any implied warranty of merchantability or fitness for a particular purpose. Fujitsu Computer Products of America, Inc. reserves the right to modify at any time without prior notice these statements, our products, their performance specifications, availability, price and warranty, post-warranty and service programs.

Printed in the U.S.A. Qty. 5M DS38200408

fi-6130/fi-6230			
Functional Specifications			
Image Sensor Type	fi-6130	Color Charge Coupled Device (CCD) x 2	
	fi-6230	Color Charge Coupled Device (CCD) x 3	
Light Source		White cold cathode discharge lamp	
Optical Resolution		600 dpi	
Output Resolution¹	Color (24 bit)	50 to 600 dpi (adjustable by 1 dpi increments, 1200 dpi)²	
	Grayscale (8 bit)		
	Monochrome		
Output Format		Color: 24 bit, 8 bit/4 bit; Grayscale: 8 bit, 4 bit; Monochrome: 1 bit	
AD Converter		1024 levels (10 bit)	
Output Mode		Dither / Error diffusion	
Scanning speeds			
Output (Letter/A4 size)³		Simplex	Duplex
Color⁴	200 dpi	30 ppm	60 ipm
	300 dpi	30 ppm	60 ipm
Grayscale⁴/ Monochrome	200 dpi	40 ppm	80 ipm
	300 dpi	30 ppm	60 ipm
ADF Capacity⁵		50 Sheets (letter/A4, 20 lb.)	
Document size	ADF minimum	2 in. x 3 in. (52mm x 74mm)	
	ADF maximum	8.5 in. x 14 in. (Legal)	
	Long Document	8.4 in. x 122 in. (10 feet)⁹	
	Flatbed (fi-6230 only)	8.5 in x 11.69 in. (216mm x 297mm)	
ADF Feeding	Normal	11 to 56.2 lb. (41 to 210g/m²)	
Paper Weight (Thickness)	A8 sheets	34 to 56.2 lb. (127 to 210g/m²)	
	Card⁶ (1.4 mm)⁷	Portrait and Landscape feeding⁸	
Interface		USB 2.0 / USB 1.1 (B type connector)	
Physical Specifications			
Power requirements		100 – 240 VAC, 50/60 Hz	
Power consumption	fi-6130	38W or less (Sleep: less than 6.2W)	
	fi-6230	45W or less (Sleep: less than 6.2W)	
Dimensions (WxDxH)¹⁰	fi-6130	11.8 x 6.4 x 6.2 in. (301 x 160 x 158 mm)	
	fi-6230	11.8 x 22.9 x 9.0 in. (301 x 567 x 229 mm)	
Weight	fi-6130	9.24 lb. (4.2 kg)	
	fi-6230	19.36 lb. (8.8 kg)	
Environmental Compatibility¹¹		ENERGY STAR® and RoHS	
Operating Environment	Temperature	42° to 95°F (5° to 35°C)	
	Relative humidity	20% – 80% (non-condensing)	
Inbox Contents		TWIN, ISIS™, USB cable, AC adapter	
Bundled Software (DVD format)		Adobe® Acrobat® Standard, Kofax® VRS® Professional and ScandAll Pro	
Options		Software IPC, Imprinter, (Flatbed Cover Black Background for fi-6230)	
OS Support		Microsoft® Windows® 2000 Professional / Microsoft® XP (32 bit/64 bit) / Microsoft® Windows Server™ 2003 (32 bit/64 bit) / Microsoft® Windows Vista™ (32 bit/64 bit)	
Feed Detection Features		Ultrasonic Double Feed Detection Sensor Intelligent Multifeed Function (Manual Bypass)	
Other Features		Embossed and Hard Card Scanning Capability, Long Document Scanning, Automatic Color Recognition, Automatic Paper-Size Detection, Automatic De-skew Correction, Selectable White & Black Background (in ADF only).	
Limited Warranty		One-year. Advance Exchange program also available; restrictions apply. For full details, visit <a href="http://www.ImagingService.com">www.ImagingService.com</a> or call (800) 626-4686.	
Service Options		Post-Warranty: Advance Exchange Plus; restrictions apply. Consumables: ScanAid™ kit. For full details, visit <a href="http://www.ImgengService.com">www.ImgengService.com</a> or call (800) 626-4686.	
Part Number	fi-6130	PA03540-B055	
	fi-6230	PA03540-B555	

¹ Maximum output resolutions may vary, depending upon the size of the area being scanned and whether the scanner is scanning in simplex or duplex.  
² Scanning limitations brought about by scanning mode, document size and available memory may occur when scanning at high resolutions (600dpi or higher).  
³ Actual scanning speeds are affected by data transmission and software processing times.  
⁴ JPEF compressed figures.  
⁵ Maximum capacity varies, depending upon paper weight.  
⁶ Supports ISO7810 embossed cards.  
⁷ Able to digitize cards that are up to 1.25mm thick when scanning in monochrome at 200dpi (60ppm).  
⁸ Capable of scanning up to 3 cards at a time. (Note: does not support multi-embossed card feedability.)  
⁹ The scanning of documents that exceed 35 inches in length will be limited to using TWIN at 200 dpi or less.  
¹⁰ Excluding the ADF paper chute and stacker.  
¹¹ PFI Limited, a Fujitsu company, has determined that this product meets RoHS requirements (2005/95/EC).



ScandAll PRO

FUJITSU

THE POSSIBILITIES ARE INFINITE