

3Com® OfficeConnect® Hubs

DATA SHEET



- Features 10/100 autosensing technology
- Plug-and-play simplicity
- At-a-glance network status information from front-panel diagnostic LEDs

Key Benefits

Easy to Install and Use

Enjoy plug-and-play simplicity.

Simple Troubleshooting

Get at-a-glance network status information from front-panel diagnostic LEDs.

Compact Design

Save valuable small-office space with compact, ergonomic, and clippable design.

3 Year Hardware Warranty

Ensures peace of mind when purchasing 3Com® OfficeConnect® products.

Engineered for Small-Business Needs

The OfficeConnect family is the first solution designed specifically for small-office operations—often imitated but never equaled by other network vendors.

Specifically designed for small businesses and offices, 3Com OfficeConnect switches and hubs provide businesses with an integrated system of small-office networking. By installing a LAN, users can work more effectively with file and print sharing and reduce costs by sharing expensive resources as printers.

OfficeConnect products provide connectivity for every business need. For the value-conscious user, standard Ethernet hubs are ideal, while Fast Ethernet switches and hubs provide additional speed for high-volume traffic. OfficeConnect Dual Speed Ethernet switches and hubs feature autosensing technology, allowing users to migrate to higher speeds when needed. They are available in a variety of port densities—from 4 to 16 ports.

OfficeConnect Switches and Hubs are a core part of the OfficeConnect family.

The 3Com OfficeConnect family offers the most flexible, expandable, and integrated networking solutions for small businesses.

OfficeConnect products include:

LAN Connectivity

- Network interface cards
- Switches and hubs

Remote Access and Internet Connectivity

- LAN modems
- Internet Gateway Routers
- Internet firewalls



OfficeConnect Dual Speed Hub 16

OfficeConnect Dual Speed Hubs

The OfficeConnect family of dual speed hubs provides full 100 Mbps performance and is designed for small businesses that want more performance from their network. This family of hubs delivers quick exchange of data between PCs and swift downloading from the network. OfficeConnect Dual Speed Hubs feature 10/100 autosensing technology and provide the flexibility to connect

devices at either speed—automatically assigning power where possible and offering a smooth transition from 10 Mbps to 100 Mbps.

Each hub features plug-and-play installation, requires no configuration, has an easy-to-read, front-panel display with diagnostic LEDs. All hubs are backed by a 3 Year Hardware Warranty.

OFFICECONNECT DUAL SPEED HUBS	10/100 AUTOSENSING PORTS	LED INDICATORS	MAC ADDRESSES SUPPORTED	MDI/MDIX PORT	HARDWARE WARRANTY	FCC CLASS B	EXTERNAL POWER SUPPLY
OfficeConnect Dual Speed Hub 5 (3C16755) A low density affordable hub.	5	Power, Port Status, Collision	1,024	✓	3 Years	✓	11 W
OfficeConnect Dual Speed Hub 8 (3C16753) A popular hub combining Fast Ethernet performance with the flexibility to expand an existing Ethernet network to Fast Ethernet.	8	Power, Port status, Collision	1,024	✓	3 Years	✓	11 W
OfficeConnect Dual Speed Hub 16 (3C16754) Ideal for Fast Ethernet connectivity with the flexibility to expand an existing Ethernet network to Fast Ethernet.	16	Power, Network utilization, Port status, Collision	1,024	✓	3 Years	✓	11 W



OfficeConnect Ethernet Hub 8

OfficeConnect Ethernet Hubs

The OfficeConnect family of Ethernet hubs is specifically designed for small businesses with basic networking requirements, such as file or peripheral sharing, or for those who simply want to add additional users to a

10BASE-T network. OfficeConnect hubs offer compatibility with legacy coax networks and provide connections for 4, 8, or 16 users or networked devices.

	10BASE-T RJ-45	10BASE-T COAX	10BASE-T AUI	LED INDICATORS	NETWORK UTILIZATION (LED)	MDI-MDIX PORT	HARDWARE WARRANTY	FCC CLASS B	EXTERNAL POWER SUPPLY
OfficeConnect Ethernet Hub 4 (3C16704A) A low-cost, entry-level hub, providing basic Ethernet connectivity.	4			✓		✓	3 Years	✓	11 W
OfficeConnect Ethernet Hub 4C (3C16703A) Ideal for entry-level networks requiring alternative media connectivity.	4	1	1	✓	✓	✓	3 Years	✓	11 W
OfficeConnect Ethernet Hub 8 (3C16700A) A popular entry-level hub providing basic Ethernet connectivity.	8			✓		✓	3 Years	✓	11 W
OfficeConnect Ethernet Hub 8C (3C16701A) Ideal hub for businesses wanting to expand their existing coaxial network.	8	1		✓	✓	✓	3 Years	✓	11 W
OfficeConnect Ethernet Hub 16C (3C16702A) Provides expanded network capacity and connectivity to legacy coaxial networks.	16	1		✓	✓	✓	3 Years	✓	11 W

Features

	Description
10/100 autosensing ports	Allows users to connect at either 10 Mbps or 100 Mbps to the hub. The hub will operate at the highest speed possible, optimizing network performance and user flexibility.
Compact and clippable design	One-piece clipping system lets users connect up to four units in a stack.
External power supply	Provides more flexibility and reduces power requirements in the product, eliminating the need for a noisy fan.
FCC Class B	Indicates that a product is certified for use in domestic as well as office environments (more stringent classification than Class A).
Fully compatible with leading operating systems	OfficeConnect units support Novell NetWare, Microsoft Windows 95, 98, 2000, Windows NT, and other leading software systems, giving the widest range of backward compatibility with existing office software.
3 Year Hardware Warranty	Provides complete peace of mind.
MDI/MDIX push button switch	Enables direct connection to a server, end station, or another switch or hub, using regular straight-through cables.
Network utilization meter (available on most OfficeConnect hubs)	Indicates how much of the network bandwidth is in use. These LEDs are continually updated to show when the network needs more bandwidth.

Specifications

OfficeConnect hubs come with a user guide, power adapter, one-piece clipping system, and rubber feet.

OfficeConnect Ethernet Hub 4 (10BASE-T Hub) 3C16704A

Connectors:

4 RJ-45 ports for 10BASE-T twisted pair

Dimensions:

Width: 228 mm (9.1 in)
Height: 41.8 mm (1.6 in)
Depth: 135.4 mm (5.3 in)
Weight: 500 g (1.1 lb)

Power: 2.33 VA

Functional:

ISO 8802/3; IEEE 802.3

EMC:

EN 55022 Class B; EN 55024; EN 61000-3-2,
EN 61000-3-3; FCC Part 15 Class B; ICES-003 Class B;
VCCI Class B; AS/NZS 3548 Class B

Environmental: EN 60068 (IEC 68)

Safety:

UL 1950; EN 60950; CSA 22.2 #950, IEC 60950

OfficeConnect Ethernet Hub 4C (10BASE-T Hub) 3C16703A

Connectors:

4 RJ-45 ports for 10BASE-T twisted pair; one BNC port for 10BASE2 thin Ethernet (50 ohm); one AUI

Dimensions:

Width: 228 mm (9.1 in)
Height: 41.8 mm (1.6 in)
Depth: 135.4 mm (5.3 in)
Weight: 500 g (1.1 lb)

Power: 10.3 VA

Functional:

ISO 8802/3; IEEE 802.3

EMC:

EN 55022 Class B; EN 55024; EN 61000-3-2,
EN 61000-3-3; FCC Part 15 Class B; ICES-003 Class B;
VCCI Class B; AS/NZS 3548 Class B

Environmental: EN 60068 (IEC 68)

Safety:

UL 1950; EN 60950; CSA 22.2 #950, IEC 60950

OfficeConnect Ethernet Hub 8 (10BASE-T Hub) 3C16700A

Connectors:

8 RJ-45 ports for 10BASE-T twisted pair

Dimensions:

Width: 228 mm (9.1 in)
Height: 41.8 mm (1.6 in)
Depth: 135.4 mm (5.3 in)
Weight: 500 g (1.1 lb)

Power: 3.13 VA

Functional:

ISO 8802/3; IEEE 802.3;

EMC:

EN 55022 Class B; EN 55024; EN 61000-3-2,
EN 61000-3-3; FCC Part 15 Class B; ICES-003 Class B;
VCCI Class B; AS/NZS 3548 Class B

Environmental: EN 60068 (IEC 68)

Safety:

UL 1950; EN 60950; CSA 22.2 #950, IEC 60950

OfficeConnect Ethernet Hub 8C (10BASE-T Hub) 3C16701A

Connectors:

8 RJ-45 ports for 10BASE-T twisted pair; one BNC port for 10BASE2 thin Ethernet (50 ohm)

Dimensions:

Width: 228 mm (9.1 in)
Height: 41.8 mm (1.6 in)
Depth: 135.4 mm (5.3 in) + 15.2 mm (0.6 in) for coaxial port
Weight: 550 g (1.2 lb)

Power: 5.53 VA

Functional:

ISO 8802/3; IEEE 802.3;

EMC:

EN 55022 Class B; EN 55024; EN 61000-3-2,
EN 61000-3-3; FCC Part 15 Class B; ICES-003 Class B;
VCCI Class B; AS/NZS 3548 Class B

Environmental: EN 60068 (IEC 68)

Safety:

UL 1950; EN 60950; CSA 22.2 #950, IEC 60950

OfficeConnect Ethernet Hub 16C (10BASE-T hub) 3C16702A

Connectors:

16 RJ-45 ports for 10BASE-T twisted pair; one BNC port for 10BASE2 thin Ethernet (50 ohm)

Dimensions:

Width: 228 mm (9.1 in)
Height: 60.6 mm (2.4 in)
Depth: 185.4 mm (7.3 in)
Weight: 960 g (2.1 lb)

Power: 6.73 VA

Functional:

ISO 8802/3; IEEE 802.3

EMC:

EN 55022 Class B; EN 55024; EN 61000-3-2,
EN 61000-3-3; FCC Part 15 Class B; ICES-003 Class B;
VCCI Class B; AS/NZS 3548 Class B

Environmental: EN 60068 (IEC 68)

Safety:

UL 1950; EN 60950; CSA 22.2 #950, IEC 60950

OfficeConnect Dual Speed Hub 5 (10BASE-T/ 100BASE-TX Hub) 3C16755

Connectors:

5 RJ-45 10BASE-T/100BASE-TX ports

Dimensions:

Width: 228 mm (9.1 in)
Height: 41.8 mm (1.6 in)
Depth: 135.4 mm (5.3 in)
Weight: 484 g (1.05 lb)

Power: 3 VA

Functional:

ISO 8802/3; IEEE 802.3

EMC:

EN 55022 Class B, EN 50082-1, FCC Part 15 Class B,
KES 003 Class B, VCCI Class B, CNS 13438 Class A

Environmental: EN 60068 (IEC68)

Safety:

UL 1950, EN 60950, CSA 22.2 #950, IEC 60950

Specifications, *continued***OfficeConnect Dual Speed Hub 8
(10BASE-T/100BASE-TX Hub) 3C16753***Connectors:*

8 RJ-45 10BASE-T/100BASE-TX ports

Dimensions:

Width: 228 mm (1.6 in)

Height: 41.8 mm (2.4 in)

Depth: 135.4 mm (5.3 in)

Weight: 552 g (1.2 lb)

Power: 3 VA*Functional:*

ISO 8802/3; IEEE 802.3

EMC:

EN 55022 Class B; EN 55024; EN 61000-3-2, EN

61000-3-3; FCC Part 15 Class B; ICES-003 Class B;

VCCI Class B; AS/NZS 3548 Class B

Environmental: EN 60068 (IEC 68)*Safety:*

UL 1950; EN 60950; CSA 22.2 #950, IEC 60950

**OfficeConnect Dual Speed Hub 16
(10BASE-T/100BASE-TX) 3C16754***Connectors:*

16 RJ-45 10BASE-T/100BASE-TX ports

Dimensions:

Width: 228 mm (9.1 in)

Height: 60.6 mm (2.4 in)

Depth: 185.4 mm (7.3 in)

Weight: 945 g (2.08 lb)

Power: 8 VA*Functional:*

ISO 8802/3; IEEE 802.3

EMC:

EN 55022 Class B; EN 55024; EN 61000-3-2, EN

61000-3-3, FCC Part 15 Class B; ICES-003 Class B;

VCCI Class B; AS/NZS 3548 Class B

Environmental: EN 60068 (IEC 68)*Safety:*

UL 1950; EN 60950; CSA 22.2 #950, IEC 60950

Ordering Information

PRODUCT DESCRIPTION	3COM SKU
OfficeConnect Dual Speed Hub 5	3C16755
OfficeConnect Dual Speed Hub 8	3C16753
OfficeConnect Dual Speed Hub 16	3C16754
OfficeConnect Ethernet Hub 4	3C16704A
OfficeConnect Ethernet Hub 4C	3C16703A
OfficeConnect Ethernet Hub 8	3C16700A
OfficeConnect Ethernet Hub 8C	3C16701A
OfficeConnect Ethernet Hub 16C	3C16702A



3Com Corporation, Corporate Headquarters, 350 Campus Drive, Marlborough, MA 01752-3064

To learn more about 3Com solutions, visit www.3com.com. 3Com is publicly traded on NASDAQ under the symbol COMS.

Copyright © 2004 3Com Corporation. All rights reserved. 3Com, the 3Com logo, and OfficeConnect are registered trademarks of 3Com Corporation. All other company and product names may be trademarks of their respective companies. While every effort is made to ensure the information given is accurate, 3Com does not accept liability for any errors or mistakes which may arise. Specifications and other information in this document may be subject to change without notice. 400719-004 09/04