

H81 Series

DDR3 1333 Qualified Vendors List (OVL)

Vendors	Part No.	Size	SS/DS	Chip Brand	Chip NO.	Timing	Voltage	DIMM socket support (Optional)	
								1 DIMM	2 DIMM
TEAM	TED34GM1333C9BK	4GB	DS	HYNIX	DWLDL9J5HL	9-9-9-24	1.5V	●	●
TEAM	TED38GM1333C9BK	8GB	DS	HYNIX	DT38J3bbDHJ	9-9-9-24	1.5V	●	●

DDR3 1600 Qualified Vendors List (OVL)

Vendors	Part No.	Size	SS/DS	Chip Brand	Chip NO.	Timing	Voltage	DIMM socket support (Optional)	
								1 DIMM	2 DIMM
KINGSTON	KVR16N11S8/4(Low Profile)	4GB	SS	KINGSTON	U317X8BRR19	-	1.50V	●	●
SANMAX	SMD-4G28N1P-16KM	4GB	SS	ELPIDA	J4208BBBG-GN-F	-	-	●	●
SANMAX	SMD-8G28NP-16KM	8GB	DS	ELPIDA	J4208BBBG-GN-F	-	1.50V	●	●
TEAM	TLD34G1600HCBK	4GB	SS	-	-	9-9-9-24	1.5V	●	●
TEAM	TED34GM1600C11BK	4GB	DS	HYNIX	DW3DJJ273	-	1.5V	●	●
TEAM	TED38GM1600C11BK	8GB	DS	HYNIX	DT38J3bb4AM	11-11-11-28	1.5V	●	●
TEAM	TLD38G1600HC9BK	8GB	DS	-	-	9-9-9-24	1.5V	●	●
MIRAGES	KMD3U1600V4G(PC3-12/00U)	4GB	SS	-	SEC246BCKOK4B4GO846	-	-	●	●
V-COLOR	TD4G8C11-H11	4GB	SS	HYNIX	H5TQ4G83MFR	-	-	●	●

DDR3 1866 Qualified Vendors List (OVL)

Vendors	Part No.	Size	SS/DS	Chip Brand	Chip NO.	Timing	Voltage	DIMM socket support (Optional)	
								1 DIMM	2 DIMM
AMD	AP38G1869U2K	8GB(4GBX2)	DS	-	-	9-10-9-27	1.5V	●	●
TEAM	TED34GM1866C13BK	4GB	DS	HYNIX	DW3DJ472B3	-	1.5V	●	●
TEAM	TLD34G1866HC9KBK	4GB	DS	-	-	9-11-9-27	1.5V	●	●
TEAM	TED38GM1866C13BK	8GB	DS	HYNIX	DT38G54BHM	-	1.5V	●	●
TEAM	TLD38G1866HC10SBK	8GB	DS	-	-	10-11-10-30	1.5V	●	●

DDR3 2133 Qualified Vendors List (OVL)

Vendors	Part No.	Size	SS/DS	Chip Brand	Chip NO.	Timing	Voltage	DIMM socket support (Optional)	
								1 DIMM	2 DIMM
TEAM	TLD34G2133HC11ABK	4GB	SS	-	-	11-11-11-31	1.65V	●	●
TEAM	TLD38G2133HC11ABK	8GB	DS	-	-	11-13-13-31	1.65V	●	●
ADATA	AX3U2133W4G10-DR	8GB (2x 4GB)	SS	-	-	10-11-11-30	1.65V	●	●
ADATA	AX3U2133W8G10-DR	16GB (2x 8GB)	DS	-	-	10-11-11-30	1.65V	●	●

DDR3 2400 Qualified Vendors List (OVL)

Vendors	Part No.	Size	SS/DS	Chip Brand	Chip NO.	Timing	Voltage	DIMM socket support (Optional)	
								1 DIMM	2 DIMM
CORSAIR	CMD16GX3M2A2400C9(Ver4.21)	8GB	DS	-	-	10-12-12-31	1.65V	●	●
TEAM	TXD34G2400HC10QBK	4GB	DS	-	-	10-12-12-31	1.62V	●	●
TEAM	TXD38G2400HC10QBK	8GB	DS	-	-	10-12-12-31	1.62V	●	●
ADATA	AX3U2400W8G11-DMV	16GB (2x 8GB)	DS	-	-	11-13-13-35	1.65V	●	●

DDR3 2800 Qualified Vendors List (QVL)

Vendors	Part No.	Size	SS/DS	Chip Brand	Chip NO.	Timing	Voltage	DIMM socket support (Optional)	
								1 DIMM	2 DIMM
ADATA	AX3U2800W4G12-DGV	4GB	SS	-	-	12-12-14-36	1.65V	●	●

DDR3 2666 Qualified Vendors List (OVL)

Vendors	Part No.	Size	SS/DS	Chip Brand	Chip NO.	Timing	Voltage	DIMM socket support (Optional)	
								1 DIMM	2 DIMM
TEAM	TXD38G2666HC11CBK	8GB	DS	-	-	11-13-13-35	1.65V	●	●

DDR3 2933 Qualified Vendors List (OVL)

Vendors	Part No.	Size	SS/DS	Chip Brand	Chip NO.	Timing	Voltage	DIMM socket support (Optional)	
								1 DIMM	2 DIMM
G.SKILL	F3-2933C12Q-16GTDXG	4GB	SS	-	-	12-14-14-35	1.65V	●	●

4 DIMM Slots

- **1 DIMM**: Supports one module inserted in any slot as Single-channel memory configuration
- **2 DIMM**: Supports 2 modules inserted into both the blue or black slots as two pairs of Dual-channel memory configuration

-When installing total memory of 4GB capacity or more, Windows 32-bit operation system may only recognize less than 3GB. Hence, a total installed memory of less than 3GB is recommended.
-It is recommended to install the memory modules from the slots for better overclocking capability.
-The default DIMM frequency depends on its Serial Presence Detect (SPD), which is the standard way of accessing information from a memory module. Under the default state, some memory modules for overclocking may operate at a lower frequency than the vendor-marked value.