

30" TFT LCD Display / TV

LWX-30AMS-1



- Resolution : 1280 x 768 Pixels (WXGA).
- Brightness : 500 cd/m².
- Contrast : 500:1.
- Viewing Angle : H : 170° / V : 170°.
- 0.5025 mm x 0.5025 mm Pixel Pitch.
- Response time (Gray to Gray) : 16 ms.
- VESA VGA, SVGA, XGA Compatible.
- Built in 5W x 2 Stereo Speaker.
- SRS (WOW) Surrounding Sound.
- DVI Input.
- 3D Motion De-interlacing and 3:2 Pull Down.
- 3D Comb Filter.
- Photo Frame : JPEG Format (Opt.).
- Hard Coating AR Glass (Opt.).
- RS-232 Port.
- Power Supply : 100 ~ 240V_{AC} Input (PFC).
- Power Consumption : 160W max. ; Standby : 3W.
- Dimension : 816 (W) x 486 (H) x 89 (D) mm.
(W / O Stand).
- 816 (W) x 532 (H) x 176 (D) mm.
(Including Stand).
- Packing Dimension : 915 (W) x 650 (H) x 256 (D) mm.
- Net Weight / Gross Weight : 16.5 KG / 19.5 KG.
- Container Loading : 20ft - 180 sets / 40ft - 390 sets.

TV / Video Converter Function (Opt.):

- 1 x Composite Video In.
- 1 x S-Video In.
- 2 x Component (Y, Cb / Pb, Cr / Pr) In.
- HDTV Ready : 480i / 480p / 1080i / 720p.
- 1 x Cable / Antenna (75Ω) TV In (Opt.).
- 1 x Composite Video Out.
- Closed Caption, V chip (USA).
- MTS / SAP (NTSC).
- Teletext / Nicam (PAL).
- IR Remote Control.



TV / Video
Converter (Opt.)



Wall Mount
(Opt.)



Desk Top Stand



Remote
Control