

Elo Touch Solution 1915L (E266835)

48.26 cm (19.0 ") TFT LCD, 1280 x 1024, 5:4, 270 nits, 5ms, CR 1000:1, VGA, Serial/USB, IntelliTouch, 50W



Price details:

Price excl. VAT: 552.19 €

Eco fees: 0.04 €

VAT 21 %: 115.97 €

Product details:

Product code: E266835

EAN: 7411493015656

Manufacturer: Elo Touch Solution

668.20 €

* VAT included

PDF generated on: 16 January, 2016

The 1915L touchmonitor is designed, developed and built to provide the most cost-effective touch solutions for system integrators and VARs. It packs Elo quality and reliability into an integrated, affordable touchmonitor.

Main specifications:

Display

Display diagonal:	19 "
Response time:	5 ms
Display brightness:	270 cd/m ²
Contrast ratio (typical):	1000:1
Display type:	LCD
Display resolution:	1024 x 768 pixels
Number of colours:	16.7 M
Horizontal scan range:	31.5 - 80 kHz
Vertical scan range:	56.3 - 75 Hz
Viewing angle, horizontal:	160 °
Viewing angle, vertical:	155 °
Aspect ratio:	5:4
Display viewable area (HxV):	376.3 x 301.1 mm
Full HD:	N
HD-Ready:	N

Performance

Mean time between failures (MTBF):	50000 h
------------------------------------	---------

Ports & interfaces

USB 2.0 ports quantity:	1
VGA (D-Sub) ports quantity:	1
RS-232 ports:	1

Design

Colour of product:	Grey
Certification:	UL/cUL, TÜV-GS, CE, FCC/IC/VCCI, C-Tick Class B

Ergonomics

VESA mounting interfaces:	100 x 100 mm
Wall mountable:	Y

Power

Power supply type:	AC
Power consumption (typical):	50 W

Operational conditions

Operating temperature (T-T):	0 - 40 °C
Storage temperature (T-T):	-20 - 60 °C
Operating relative humidity (H-H):	20 - 80 %
Storage relative humidity (H-H):	10 - 90 %

Weight & dimensions

Weight:	7900 g
Dimensions (W x D x H) with stand:	429 x 207 x 379 mm

Packaging data

Camera included:	N
Package weight:	11700 g

Other features

On Screen Display (OSD):	Y
Native resolution:	1280 x 1024
Package dimensions (WxDxH):	540 x 495 x 285 mm
Power requirements:	85 - 265 VAC, 47 – 63 Hz

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.