

Elo Touch Solution 1928L (E522556)

1928L, 48.26 cm (19.0 ") 1280 x 1024, 5:4, VGA, DVI-D, AccuTouch, Dual Serial/USB, Beige



Price details:

Price excl. VAT: 734.04 €

Eco fees: 0.04 €

VAT 21 %: 154.16 €

Product details:

Product code: E522556

EAN: 7411493311420

Manufacturer: Elo Touch Solution

888.24 €

* VAT included

PDF generated on: 5 August, 2016

The fully featured 1928L touchmonitor offers best in class optical performance mated to the leading touch technologies- IntelliTouch surface acoustical wave and AccuTouch five-wire resistive-along with a combination touch controller, DVI, VGA and built-in speakers. The product can be ordered in beige or gray color, touch and non-touch enabled versions.

The 1928L carries a wide array of certifications and includes an innovative IPX1 enclosure design which ensures that the entire touchmonitor sheds water and is safe from liquid drops and spills. As a result the 1928L is an excellent fit for any application benefiting from DVI-D input, speakers and best in class image performance.

Main specifications:

Display

Display diagonal:	19 "
Response time:	20 ms
Display brightness:	246 cd/m ²
Display resolution:	1280 x 1024 pixels
Display type:	LCD
Contrast ratio (typical):	1300:1
Horizontal scan range:	31.5 - 80 kHz
Vertical scan range:	56.3 - 75 Hz
Viewing angle, horizontal:	178 °
Viewing angle, vertical:	178 °
Aspect ratio:	5:4
Display viewable area (HxV):	376 x 301 mm
Touchscreen technology:	Resistive
Display number of colours:	16.78 million colours

Performance

Touch screen type:	Tabletop
Mean time between failures (MTBF):	50000 h
Built-in speaker(s):	Y
Number of loudspeakers:	2
RMS rated power:	4 W
Plug and Play:	Y

Ports & interfaces

USB 2.0 ports quantity:	1
DVI-D ports quantity:	1
VGA (D-Sub) ports quantity:	1
RS-232 ports:	1

Design

Colour of product:	Beige
Ergonomics	
VESA mounting interfaces:	100 x 100 mm
Wall mountable:	Y
Power	
Power supply type:	DC
Power consumption (typical):	48 W
AC adapter output voltage:	12 V
Operational conditions	
Operating temperature (T-T):	-20 - 60 °C
Storage temperature (T-T):	0 - 40 °C
Operating relative humidity (H-H):	20 - 80 %
Storage relative humidity (H-H):	10 - 90 %
Weight & dimensions	
Weight:	6100 g
Dimensions (W x D x H) with stand:	429 x 212 x 390 mm
Weight with stand:	8000 g
Packaging data	
Package weight:	11800 g
Other features	
On Screen Display (OSD):	Y
Package dimensions (WxDxH):	540 x 315 x 510 mm

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.