



## 4200L 42" Interactive Digital Signage Touch Display

### **The 42-inch 4200L is part of a new family of touch displays which bring interactivity to digital signage.**

The Elo TouchSystems 4200L features a choice of industry-leading touch technologies that optimizes the touch experience for a particular usage. For a seamless, zero-bezel design, the innovative Acoustic Pulse Recognition (APR) touch technology delivers an elegant appearance and a responsive touch experience. Elo zero-bezel APR technology recognizes touch on virtually the entire display surface, offering a full-screen interface for navigation regardless of how the display is touched—finger, prosthetic, stylus, card or pen. For a sensitive, accurate touch response, IntelliTouch surface wave product technology utilizes pure-glass construction to deliver excellent imagery with high light transmissions, not affected by changes in ambient light, and supports finger, gloved hand and soft stylus activation. Housed in a highly durable steel chassis for a long-life of reliable performance, the 4200L with either technology is an efficient display canvas for almost any commercial, public access application.

Optional high performance computer modules are well-suited for running interactive media and are available with a choice of two processing models: ECM1 with the Intel Celeron Dual-Core 2.2GHz and ECM2 with the Intel Core 2 Duo 3.0GHz. The computer modules are field-

installable, easily sliding into a dedicated bay behind the touch display and locking into place with two thumbscrews. These modules make the 4200L a reliable platform that is interoperable with content management servers and support optimal partitioning of locally cached and network stored content.

### **Benefits**

- Edge-to-edge glass design facilitates easy care and cleaning, plus dust and liquid resistance with APR
- IntelliTouch surface wave delivers a sensitive, accurate, touch experience for finger, soft-stylus activation
- Power and display control functions can be locked out to prevent tampering
- Built-in speakers provide audio expansion capabilities
- Pure-glass construction to deliver excellent imagery, high light transmissions; not affected by variations in ambient or extreme light.
- Features durable, scratch-resistant glass for continuous surface performance



# 4200L 42" Interactive Digital Signage Touch Display

Model	4200L
Useful screen area	Horizontal: 36.6" (930 mm); Vertical: 20.6" (523 mm)
Monitor dimensions (without stand)	Width: 40.2" (1020 mm); Depth: 5.2" (132 mm); Height: 24.1" (613 mm)
Touch technology	Zero-bezel Acoustic Pulse Recognition (APR); IntelliTouch surface wave
Speakers	A pair of 10 W stereo speakers facing down (in landscape mode)
Audio input connector	3.5 mm TRS jack
Audio input signal range	1 Vrms max stereo signal (standard PC line out)
Headphone output connector	3.5 mm TRS jack
Headphone output signal (for 1KHz signal)	Delivers 90 mW of power into a 32 ohm stereo load
LCD technology	Active matrix TFT LCD
Diagonal size	42"
Aspect ratio	16:9
On-screen display (OSD)	Controls: menu, up, down, select; settings: brightness, contrast, clock, phase, auto-adjust, H-position, V-position; maintain aspect ratio, sharpness, color temperature, OSD timeout, OSD language, mounting, OSD H-position, OSD V-position, volume, mute, recall defaults, video source, audio source; Languages: English, French, Italian, German, Spanish, Simplified Chinese, Traditional Chinese, Japanese; Lockouts: OSD, power; accessible through switches on the rear, or through the standard Elo OSD control box.
Stand options	Optional stand available, order Part Number E448725
Mounting options	VESA MIS-F, 600 x 400, Y, 6, 90
Native (optimal) resolution	1920 x 1080
Other supported resolutions	640 x 480 at 60 Hz; 720 x 480 at 60 Hz; 720 x 576 50 Hz; 800 x 600 at 56, 60 Hz; 1024 x 768 at 60 Hz; 1280 x 720 at 50, 60 Hz; 1280 x 960 at 60 Hz; 1280 x 1024 at 60 Hz; 1360 x 768 at 60 Hz; 1366 x 768 at 60 Hz; 1440 x 900 at 60 Hz; 1680 x 1050 at 60 Hz; 1920 x 1080 at 50, 60 Hz
Colors	16.7 million
Brightness (typical)	LCD panel: 700 nits; with APR: 630 nits; IntelliTouch Plus: 630 nits
Response time (Tr + Tf) total (typical)	6.5 msec
Viewing angle (typical)	Horizontal: ±89° or 178° total; Vertical: ±89° or 178° total
Contrast ratio (typical)	3500:1
Input video format	Analog VGA, HDMI 1.3
Input video signal connector	Female DE-15 for Analog VGA; HDMI Type A receptacle for HDMI
Input frequency	Horizontal: 32-80 kHz; Vertical: 47-61 Hz
Power supply	Internal AC
Input voltage	100-240 VAC, 50/60 Hz
Power connector	IEC 60320 C14
Power consumption (typical)	Monitor only: ON, max. audio, 100 V/60 Hz: 230 W; SLEEP, 100 V/60 Hz: 12.5 W; OFF, 100 V/60 Hz: 11.5 W
Temperature	Operating: 0°C to 40°C (32°F to 104°F); Storage: -20°C to 50°C (-4°F to 122°F)
Humidity (non-condensing)	Operating: 20-80%; Storage: 10-90%
Weight	Actual: w/o Computer Module: 74.7 lb (33.9 kg); with Computer Module: 80.5 lb (36.5 kg)
Shipping	99.7 lb (45.2 kg) (Computer Module shipped separately)
Shipping box dimensions	Width: 47.0" (1194 mm); Depth: 12.0" (305 mm); Height: 31.0" (788 mm)
Warranty	3 years
Backlight lamp life (typical)	50,000 hours to half-brightness
MTBF	50,000 hours demonstrated
Agency approvals	Argentina S-mark; Australia C-Tick; Canada cUL; China CCC; Mexico NOM; Russia & CIS GOST; United States UL; Elo declarations; Europe CE; Canada IC; Japan VCC; United States FCC

To find out more about our extensive range of Elo touch solutions, go to [www.elotouch.com](http://www.elotouch.com), or call the office nearest you.

<b>North America</b>	800-ELO-TOUCH	<b>Europe</b>	<b>Asia-Pacific</b>	<b>Latin America</b>
Elo TouchSystems	Tel 1-650-361-4800	Tel +32 (0)16 35 21 00	Tel +81 (45) 478-2161	Tel 786-923-0251
301 Constitution Drive	Fax 1-650-361-4722	Fax +32 (0)16 35 21 01	Fax +81 (45) 478-2180	Fax 305-931-0124
Menlo Park, CA 94025-1110	customerservice@elotouch.com	elosales@elotouch.com	www.tps.co.jp	www.elotouch.com.ar



Tyco Electronics reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Elo (logo), Elo TouchSystems, IntelliTouch, TE (logo) and Tyco Electronics are trademarks of the Tyco Electronics group of companies and its licensors. Windows is a trademark of Microsoft Corporation.

Copyright 2011 Tyco Electronics Corporation 01/11

