

Tandberg StorageLibrary™ T40+, T80+ and T120+

Professional, Scalable Tape Backup

The Tandberg StorageLibrary™ T40+ and T80+ and T120+ tape libraries are professional backup and data protection solutions, providing maximum performance and scalable capacities up to 182.4TB*.

The Tandberg StorageLibrary T40+ Series incorporates the new Pass-Thru feature, allowing you to add additional drives and storage capacity as and when you need it. The Pass-Thru feature will allow up to three T40+ units to be stacked together in a 19" rack configuration.

The T40+ base unit is available with either 24 or 40 slots and the Capacity on Demand (COD) feature allows you to electronically upgrade the number of slots from 24 to 40. The number of slots can be increased from 40 to 77 by adding one additional T40+ in Pass-Thru mode. By adding a third T40+, the number of slots will increase to 114. Each 4U unit can be installed with up to 4 half height LTO drives or up to 2 full height LTO drives and supports LVD SCSI, Native Fibre Channel or SAS connectivity.

The T40+ Series is designed to improve efficiency and minimize IT downtime. The Performance on Demand (POD) feature allows you add drives or upgrade to the next LTO generation, increasing your library's performance and capacity. The Web browser-based remote management interface allows you to monitor, control, configure and diagnose problems from anywhere in the world. The T40+ Series supports system monitoring via SNMP. It also supports SMTP, and will immediately send an e-mail on any error.

The T40+ is supplied with two power supplies to provide redundancy for mission critical operations and to avoid power interruption to the library. Both power supplies share the load under normal operating conditions. However, if one of the power supplies fails, the other will take the full load.

The T40+, T80+ and 120+ tape libraries provide outstanding value for IT managers that need to perform large, unattended backups, and who require flexibility, reliability and a future proof solution.



Key Benefits

- Capacity on Demand**
Start with 24 slots, expand to 114 slots, increasing capacity from 19.2TB to 182.4TB*
- Performance on Demand**
Add drives or upgrade to the next generation LTO technology to increase performance and meet demanding backup windows
- Ease of Management**
Browser-based remote management interface allows users to remotely monitor, control, configure and diagnose via the Internet
- Minimize Downtime**
The Redundant Power Supply (RPS) detects power failures and assures system availability
- WORM and Encryption**
WORM (write once read many) and Encryption (LTO-4 only) for enhanced data protection and regulatory compliance

* Assumes a 2:1 compression ratio



The Tandberg StorageLibrary T40* combines high capacity and performance in a scalable 4U form factor.

Specifications

	StorageLibrary T40*	StorageLibrary T80*	StorageLibrary T120*
Slots	24 or 40 slots	77 slots	114 slots
Drive Technology	LTO-3 / LTO-4	LTO-3 / LTO-4	LTO-3/LTO-4
Number of Drives (Half height)	1-4	1-8	1-12
Number of Drives (Full height)	1-2	1-4	1-6
Number of Cartridges	24 or 40	77	114
Capacity (native/compr.)	LTO-3 9.6TB / 19.2TB (24 slots) 16TB / 32TB (40 slots)	30.8TB / 61.6TB	45.6/91.2
	LTO-4 19.2TB / 38.4TB (24 slots) 32TB / 64TB (40 slots)	61.6TB / 123.2TB	91.2/182.4
Max Performance (native/compr.)	LTO-3 FH 0.58TB/hr / 1.2TB/hr (24 or 40 slots)	1.2TB/hr / 2.3TB/hr	1.7TB/hr / 3.5 TB/hr
	LTO-4 FH 0.86TB/hr / 1.7TB/hr (24 or 40 slots)	1.7TB/hr / 3.5TB/hr	2.6TB/hr / 5.2TB/hr
	LTO-4 HH 1.7TB/hr / 3.5TB/hr (24 or 40 slots)	3.5TB/hr / 6.9TB/hr	5.2TB/hr / 10.4TB/hr
Interface	Ultra SCSI LVD / Native FC / SAS	Ultra SCSI LVD / Native FC / SAS	Ultra SCSI LVD / Native FC / SAS
Remote Management (Web)	Standard	Standard	Standard
Barcode Scanner	Standard	Standard	Standard
Number of Removable Magazines	4	8	12
Temperature (Operating)	10C to 40C (50F to 104F)	10C to 40C (50F to 104F)	10C to 40C (50F to 104F)
Temperature (Non-operating)	-30C to 60C (-22F to 140F)	-30C to 60C (-22F to 140F)	-30C to 60C (-22F to 140F)
Relative Humidity (Operating) Non-Condensing	20 to 80%	20 to 80%	20 to 80%
Relative Humidity (Non-operating) Non-Condensing	10 to 90%	10 to 90%	10 to 90%
Rackmount-option	Standard	Standard	Standard
Redundant Power Supply	Standard	Standard	Standard
Power Consumption	100-240VAC, 50-60Hz, 70 W average	100-240VAC, 50-60Hz, 70 W average	100-240VAC, 50-60Hz, 70 W average
MTBF	250 000 hours	250 000 hours	250 000 hours
Software Compatibility	The StorageLibrary T40* is compatible with all major backup applications and operating systems		
Agency Certification	CE, FCC, TUV/GS, ICES VCCI, BSMI, CISPR 22, C-tick, UL, C-UL, CB, GOST and EN 55022 Class A		
* Assumes a 2:1 compression ratio			
Form Factor	4U	8U	12U
Height	17.75cm/7"	35.5cm /14"	53.25cm/21"
Width	44.66cm /17.6"	44.66cm /17.6"	44.66cm/17.6"
Depth	73.6cm /29"	73.66cm /29"	73.66cm/29"
Weight	37.7kg /82.9lbs	75.4kg /165.9lbs	113.1kg/248.8lbs

About Tandberg Data

Tandberg Data is a leading global supplier of backup and archiving technologies. Tandberg Data offers a complete range of tape libraries, tape autoloaders and tape drives (based on the LTO™, SLR™, VXA® tape technology platforms), storage software, data media and disk-based storage such as the RDX® QuikStor™. These solutions are marketed exclusively through a channel of qualified resellers and distributors. These solutions are underpinned by OEM agreements with major server manufacturers including IBM, Hitachi, Fujitsu, Fujitsu-Siemens, Apple and Dell and supported by all major operating systems and storage software applications to operate in heterogeneous network environments. All solutions are designed to meet the growing storage requirements of small and medium-sized organisations with scalability, reliability and backward compatibility features that ensure cost effective operation and long-term investment protection.

Tandberg Data ASA Økernveien 94 N-0579 Oslo Norway Tel: +47 (0) 2218 9090 Fax: +47 (0) 2218 9550	Tandberg Data GmbH Feldstrasse 81 44141 Dortmund Germany Tel: +49 (0) 231 5436 - 0 Fax: +49 (0) 231 5436 - 111	Tandberg Data Limited Bloxham Mill Business Centre Barford Road, Bloxham Banbury, England, OX15 4FF Tel: +44 (0) 845 070 6916 Fax: +44 (0) 1295 722 109	Tandberg Data S.A.S. Multi Management Service 55 rue de l'Université 75007 Paris, France Téléphone: 00 800 826 323 74 Télécopie: +33 (0)1 34 65 02 89	Tandberg Data Corporation 2108 55th Street Boulder, CO 80301 USA Tel: 303.442.4333 Fax: 303.417.7170	Tandberg Data (Asia) Pte Ltd 20 Bendemeer Road #04-05 Cyberhub Singapore 339914 Tel: +65 (0) 6396 0786 Fax: +65 (0) 6396 0787
---	---	--	--	---	--

In addition to the offices above TANDBERG DATA ASA has branch offices in the United Kingdom, France, Italy, India, China (PRC), Thailand and Brazil. TANDBERG DATA ASA is a publicly held company based in Oslo, Norway and is traded on the Oslo Stock Exchange (ticker=TAD). Specifications subject to change without notice. RDX QuikStor, BAKStor, and SLR are trademarks of Tandberg Data ASA. RDX is a registered trademark of ProStor Systems. LTO is a trademark of HP, IBM and Quantum. All other trademarks are the property of their respective owners. ©2009 TANDBERG DATA. All rights reserved.