

LV-CDP6034

Superior 3.0Megapixel IP Dome Camera

See more with 3.0MP IP dome camera that features 4mm Fixed Lens , with IR cut filter auto switch, IP66 protection, backlight compensation, and a true day and night twenty four seven monitoring function. Feel safe with innovation that secures.



ONVIF/UL Listed

LaView IP cameras is Onvif compliant to ensure compatibility with your system. We are also UL Listed certified.



DIGITAL WDR OFF

DIGITAL WDR ON

True WDR

See clearly indoor and outdoor with WDR that's capable of illuminating clear images in very bright and very dark areas even under backlighting.



3D DNR ON

3D DNR OFF

3D DNR

3D Dynamic Noise Reduction helps remove tiny specks in low light providing clearer and sharper images.

3.0MP IP Dome Camera

	LV-CDP6034	
Camera		
Image sensor	1/3" sensor	
Min. illumination	0.05 lux@F1.2, AGC on 0.14 lux@F2.0, AGC on 0 lux with IR	
Shutter time	1/25s ~ 1/100,000s	
Lens	4mm@F2.0, angle of view: 45.3°/ 2.8mm@F2.0, angle of view: 45.3°	
Lens mount	M12	
Angle adjustment	Pan: 0° ~ 355°, tilt: 0° ~ 65°	
Digital noise reduction	3D DNR	
Wide dynamic range	Digital WDR	
Day & night	ICR	
Compression standard		
Video compression	H.264 / MJPEG	
H.264 codec profile	Main profile	
Bit rate	32 Kbps ~ 16 Mbps	
Dual stream	Yes	
Image		
Max. image resolution	2048 × 1536	
Frame rate	60 Hz: 15fps (2048 × 1536), 30fps (1920 × 1080), 30fps (1280 × 720)	
Image settings	Saturation, brightness, contrast adjustable through client software, or web browser	
BLC	Yes, zone configurable	
Network		
Network storage	NAS (iSCSI optional)	
Alarm trigger	Motion detection, tampering alarm, network disconnect, IP address conflict, storage exception	
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos (SIP, SRTP, IPVo6 optional)	
System compatibility	ONVIF, PSIA, CGI	
General functionalities	Flickerless, heartbeat, mirror, user authentication, video mask, watermark	
Interface		
Communication interface	1 RJ45 10M / 100M ethernet port	
General		
Operating conditions	-25°C ~ 60°C (-13°F ~ 140°F) humidity 95% or less (non-condensing)	
Power supply	12 VDC ± 10%, PoE (802.3af)	
Power consumption	Max. 5.5W	
Impact protection	IEC60068-275EH, 50J; EN50102, up to IK10	
Ingress protection	IP66	
IR range	Approx 65 to 98 ft (About 20 to 30 meters)	
Dimensions	Φ 111 × 82 mm (4.4" × 3.2")	
Weight	500g (1.1lb)	