

Lenovo ThinkPad USB 3.0 Ethernet Adapter (4X90E51405)

ThinkPad USB 3.0 Ethernet Adapter



Price details:

Price excl. VAT: 18.20 €

Eco fees: 0.00 €

VAT 21 %: 3.82 €

Product details:

Product code: 4X90E51405

EAN: 0888228041933

Manufacturer: Lenovo

PDF generated on: 24 February, 2017



22.02 €

* VAT included

The ThinkPad USB 3.0 Ethernet (4X90E51405) adapter enables Ethernet on systems which do not have Ethernet RJ-45 connector through USB port on the system. The ThinkPad USB 3.0 Ethernet adapter not only provides high speed Gigabit Ethernet solution via USB 3.0 port, but also enables boot over the LAN on selected ThinkPad systems.

Connect it with your Ultrabook or Tablet to your corporate VPN at the office or go online in a hotel suite. The adapter's small form factor allows a convenient fit into any computer case or bag to travel, so you can easily take it with you anywhere.

- Full size RJ45 connector; LEDs on connector to indicate connection status
- Two LEDs on RJ45 port for power and data transfer indication. Green for power and Yellow for activity.
- Booting from LAN and loading image from remote server both on legacy BIOS and UEFI BIOS system
- QoS (Quality of Service) tagged packets and duplicate address detection
- Doesn't support POE (Power over Ethernet)
- Giga bit speed when running on USB3.0 environment
- 100M/10M adapt when running on USB2.0 environment
- Full Duplex flow control (IEEE 802.3x)
- Compliant with IEEE 802.3 and IEEE 802.3u
- IEEE 802.3az Giga bit Ethernet requirement

Main specifications:

Ports & interfaces

Connectivity technology:	Wired
Internal:	N
Host interface:	RJ-45
Interface:	USB
Ethernet LAN (RJ-45) ports:	1
USB ports quantity:	1

Bandwidth

Data transfer rate (max):	1000 Mbit/s
---------------------------	-------------

Networking

Ethernet LAN:	Y
Cabling technology:	10/100/1000BaseT(X)
Ethernet LAN data rates:	10,100,1000 Mbit/s
Networking standards:	IEEE 802.3,IEEE 802.3az,IEEE 802.3u,IEEE 802.3x

Design

Colour of product:	Black
--------------------	-------

Performance

Plug and Play:	Y
Weight & dimensions	
Width:	100 mm
Depth:	280 mm
Height:	16 mm
Weight:	45 g
Certificates	
Certification:	VCCI, CB, Ukraine CoC, ACA/C-Tick, CE MARK, ICES, KC (Korea), EAC, FCC, BSMI
Operational conditions	
Operating temperature (T-T):	0 - 70 °C

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.