ProConnect® Series

LINKSYS'

Connect Multiple PCs with Just One Console



ProConnect® 8-Station KVM Switch (SVIEW08 v2) AT/Serial KVM Switch Cabling Kit (SVPAT10) PS/2 KVM Switch Cabling Kit (SVPPS10)

Benefits

- Switch Instantly Among Multiple PCs with the Touch of a Button
- Benefit from Incredible Savings in Equipment, Space, and Power Costs
- Conserves Desktop and Storage Space
- Serves as a Convenient Docking Station for Notebook PCs
- Free Technical Support—24 Hours a Day,
 7 Days a Week for North America Only
- 1-Year Limited Warranty

ProConnect® 8-Station KVM Switch

Conserve Desktop Space While Using Multiple PCs

Take control of your PCs with the ProConnect KVM Switches. Ready to run out of the box, the ProConnect KVM Switch lets you connect multiple PCs to a single keyboard, monitor, and mouse. Switch between PCs with the press of a key, or use the switch's cycling feature to rotate between each PC's progress automatically at programmed intervals. Got a notebook PC? Plug it into the KVM Switch and control it from your desktop's full-sized keyboard, monitor, and mouse - just like a docking station!

Built to last, the ProConnect 8-Port KVM Switch virtually eliminates cable swapping, while you save hundreds of dollars in storage space and hardware costs. Your connection can be simple and inexpensive with the Linksys ProConnect KVM Switch. It's the perfect choice for any Server room, Internet Service Provider, or testing lab where you need to manage multiple PCs efficiently and easily.

Features

- Supports HotKeys and Pushbutton Switching
- Serves as a Convenient Docking Station for Notebook PCs
- Supports Hot-Swapping of Cables
- · Cycling Feature Switches Among PCs Automatically
- Fully Expandable Cascade KVM Switches Together to Support up to 512 PCs
- Runs with Virtually All Software and Operating Systems
- Compatible with All Standard PS/2, AT/Serial, and Windows Keyboards
- Sturdy Metal Chassis and Quality Connectors
- Programmable On-Screen Display
- Free Technical Support-24 Hours a Day, 7 Days a Week for North America Only
- 1-Year Limited Warranty

Specifications

Model Numbers: SVIEW08 v2

Cabling Kits*: SVPPS10, SVPAT10

Scan Intervals: 3, 5, 10, 15, 20, 30, 40, and 60 seconds

Monitors

Supported: VGA, SVGA, and MultiSync with DDC, DDC2, and

DDC2B

Maximum

Resolution: 1920 x 1440 SVGA

Environmental

Dimensions: 14.5" x 9.75" x 1.75" (368mm x 248mm x 44mm)

Unit Weight: 120 oz. (3.4 Kg)

Power: 9V DC 1.62w maximum

Certifications: FCC Class B, CE Mark Commercial

Operating Temp: 5°C to 40°C (41°F to 104°F)

Storage Temp: -10°C to 60°C (14°F to 140°F)

Operating Humidity: 10% to 85%, Non-Condensing

Storage Humidity: 5% to 90%, Non-Condensing

Cables for connecting PCs to the KVM switch are sold separately under the above listed model numbers. If you are unsure which cabling kits to purchase, please contact Linksys for assistance.

Package Contents

ProConnect® 8-Station KVM Switch

- One ProConnect® 8-Station KVM Switch
- One AC Power Adapter
- One User Guide and Registration Card

System Requirements

8-Station Console Ports:

- One VGA, SVGA, or Multisync monitor capable of the highest resolution that you will be using on any computer installed
- One PS/2 style mouse
- One PS/2 style keyboard

- One VGA, SVGA or Multisync video card
- One 6-pin mini-DIN (PS/2 style) or DB-9 (standard serial) mouse port
- One 6-pin mini-DIN (PS/2 style) keyboard port with a +5V DC on pin 4 and Ground on pin 3 or a 5-pin DIN (AT style) keyboard port with +5V DC on pin 5 and Ground on pin 4.

Linksys 17401 Armstrong Ave. Irvine, CA 92614 USA

Sales Information (800) 546-5797 **Technical Support** (800) 326-7114 (949) 261-1288 Fax (949) 261-8868 World Wide Web* http://www.linksys.com **Email** sales@linksys.com support@linksys.com

China (10) 6432 1920 Tech Support Sales (10) 6432 1923 (10) 6437 6891 Japan

(03) 5259-5139 Telephone Fax (03) 5259-5117 **Philippines**

Telephone Fax

(632) 635 6772 Singapore

(632) 638 5580

552-8998

552-1024

Telephone Fax Thailand

717-0770 Telephone 717-0738

United Kingdom

0870 7393939 Tech Support 01245 352403 Sales Fax 0870 7393938

*Visit our website for the most current contact information

