

Phone: +32-2-4531312 - Fax: +32-2-4531763 E-mail: info@lasystems.be

StarTech.com HSB430SATBK drive bay panel (HSB430SATBK)

StarTech.com 4 Drive 3.5in Trayless Hot Swap SATA Mobile Rack Backplane



This 4 Bay SATA Mobile Rack lets you swap between 3.5in Serial ATA (SATA, SATA II, SATA III-6Gbps) hard drives in seconds.

A time saving storage solution, the mobile rack offers four trayless SATA hard drive bays, allowing you to hot swap Serial ATA hard drives but avoid having to mount the drives to trays for deployment or unfasten them for replacement.

To maximize performance and utilize the full speed potential of your SATA III hard drives, this HDD Backplane supports SATA III for transfer speeds up to 6 Gbps when paired with a compatible controller.

Supporting up to four hard drives, the mobile SATA hot swap rack only takes up three 5.25in drive bays inside a host computer - maximizing space-efficiency within the computer. The mobile rack/backplane is fully compatible with RAID installations to ensure maximum performance and versatility for enhanced storage applications.

Using Terabyte hard drives? Don't expose your Hard Drive and valuable data to unnecessary heat! The HSB430SATBK has two built-in 40mm fans that re-distribute the heat build-up generated as a result of typical drive operation. This feature is especially important for larger volume storage drives, and faster "spinning" drives (i.e 7200 RPM), as it can help optimize drive operability and in turn preserve stored data integrity.

- The StarTech.com Advantage
- Quickly and easily install or remove hard drives without having to open the chassis with the innovative trayless design
- Rubber shock absorbers, a solid aluminum construction and 10,000+ insertion rating ensures longevity from both the
- drives and bay
- Maximize performance, with file transfer speeds up to 6Gbps when paired with SATA III HDD and controller

Main specifications:

Technical details	
Type: Be	zel
Size: 5.2	25 "
Number of hard drives supported: 4	
Hard drive size: 3.5	5 "
Hard drive interface: Se	rial ATA, Serial ATA II, Serial ATA III
Number of fans: 2	
Fan diameter: 40	mm
Data transfer rate: 6 0	Gbit/s
Operating temperature (T-T): 0 -	50 °C
LED indicators: Ac	tivity,Power
Colour of product: Bla	ack
Material: Alu	uminium,Plastic

Certification: RoHS compliance:	CE, FCC Y
Weight & dimensions Width: Depth: Height: Weight:	146 mm 194 mm 127 mm 1400 g
Packaging data Package dimensions (WxDxH): Package weight:	182 x 270 x 218 mm 2100 g
Packaging content Cables included: Screws included: Manual:	SATA Y Y

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herin, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.