

StarTech.com UNIDOCKU33 (UNIDOCKU33)

StarTech.com Universal hard drive docking station - SATA and IDE dock - 2.5in & 3.5in HDD and SSD docking station with UASP & SATA III



Price details:

Price excl. VAT: 64.58 €

Eco fees: 0.00 €

VAT 21 %: 13.56 €

Product details:

Product code: UNIDOCKU33

EAN: 0065030859813

Manufacturer: StarTech.com

78.14 €

* VAT included

PDF generated on: 4 August, 2016

StarTech.com
Hard-to-find made easy

Connect both an IDE and a SATA 2.5/3.5in hard drive or solid state drive to your computer system using an available USB 3.0 port, with support for UASP for optimal performance. The UNIDOCKU33 USB 3.0 Universal HDD / SSD Dock enables you to instantly access your 2.5 or 3.5in IDE and SATA hard drives through two top loading drive slots, saving you the hassle of mounting the drives into a computer or external enclosure or tray. Enhanced with UASP (USB Attached SCSI Protocol), this hard drive docking station lets you get the most out of the fastest drive technologies such as SATA III (6 Gbps), solid state drives (SSD) and hybrid, drives with performance up to 70% faster than conventional USB 3.0 when paired with a UASP-enabled host controller. See our UASP testing results below for further details. The slot-loading design holds the SATA and IDE drives upright inside the docks, neatly keeping them off the desk, for convenience and a clutter-free setup. For SATA drives, the HDD can be inserted and connected directly through the designated dock slot, while the IDE drive slot is conveniently positioned near the rear panel 40-pin data and LP4 power connections, making it easy to connect to the dock using the included IDE data and power cables. A single USB 3.0 connection to your host computer, enables access to both the IDE & SATA hard drives simultaneously - a convenient solution for migrating data from an IDE drive to a SATA drive or vice versa. The dock can also be used to greatly increase the storage and backup capabilities of your computer system with support for high capacity drives (tested with up to 6TB 3.5" and 2TB 2.5" drives). The UNIDOCKU33 is backed by a StarTech.com 2-year warranty and free lifetime technical support. Improved Performance with UASP is supported in Windows 8, Mac OSX (10.8 or above), and Linux. In testing, UASP performs with a 70% faster read speed and 40% faster write speed over traditional USB 3.0 at peak performance. At the same peak in testing UASP also shows an 80% reduction in required processor resources. Testing results were obtained using an Intel Ivy Bridge system, a UASP-enabled StarTech.com Enclosure, and a SATA III solid state drive. The StarTech.com Advantage- Versatile configuration options, with support for IDE and SATA 2.5in and 3.5in drives- Save time, with file transfers up to 70% faster than traditional USB 3.0 when used with a UASP-supported host- Hassle-free operation and reduced workspace clutter, with upright slot-loading design

Main specifications:

Hard drive

| | |
|-------------------------------------|---|
| Storage media type: | HDD,SSD |
| Storage drive interface: | IDE,Serial ATA,Serial ATA II,Serial ATA III |
| Storage drive sizes supported: | 2.5,3.5 " |
| Number of storage drives supported: | 2 |
| Maximum storage capacity: | 6 TB |

Ports & interfaces

| | |
|-----------------|----------------------------|
| Host interface: | USB 3.0 (3.1 Gen 1) Type-B |
| DC-in jack: | Y |

Technical details

| | |
|-----------------------------|----------|
| Standard interfaces: | USB 3.0 |
| Maximum data transfer rate: | 5 Gbit/s |
| Colour of product: | Black |
| Material: | Plastic |

| | |
|------------------------------------|---------------------------|
| Hot-swap: | Y |
| Plug and Play: | Y |
| RAID support: | N |
| Mean time between failures (MTBF): | 30000 h |
| UASP support: | Y |
| Chipset: | JMicron - JMS561U, JMD330 |
| Cooling | |
| Fan: | N |
| Power | |
| AC input voltage: | 110-240 V |
| Input current: | 1.3 A |
| Output voltage: | 12 V |
| Output current: | 3 A |
| Plug type: | Type M |
| Weight & dimensions | |
| Width: | 130 mm |
| Depth: | 140 mm |
| Height: | 70 mm |
| Weight: | 512 g |
| Packaging data | |
| Package dimensions (WxDxH): | 120 x 185 x 210 mm |
| Package weight: | 1100 g |
| Packaging content | |
| AC adapter included: | Y |
| Cables included: | USB |
| Manual: | Y |
| Indication | |
| LED indicators: | Activity,Power |
| Operational conditions | |
| Operating temperature (T-T): | 5 - 80 °C |
| Storage temperature (T-T): | -40 - 70 °C |
| Operating relative humidity (H-H): | 8 - 90 % |
| Certificates | |
| Certification: | CE, FCC |
| RoHS compliance: | Y |

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.