

# StarTech.com USB3S2ESATA (USB3S2ESATA)

StarTech.com 3ft USB 3.0 to eSATA Cable Adapter - USB 3.0 to eSATA External Hard Drive Adapter cable 3 feet (1 Meter)



## Price details:

Price excl. VAT: 29.72 €

Eco fees: 0.01 €

VAT 21 %: 6.24 €

## Product details:

Product code: USB3S2ESATA

EAN: 0065030843171

Manufacturer: StarTech.com

**35.97 €**

\* VAT included

PDF generated on: 4 August, 2016

StarTech.com  
Hard-to-find made easy

Enable fast access to an eSATA device from a USB 3.0 port. The USB3S2ESATA USB 3.0 to eSATA Adapter Cable lets you connect an external SATA (eSATA) device or enclosure to a host computer through USB 3.0, in a single convenient package. The adapter cable combines USB 3.0 and eSATA cables into an integrated cable, with no external power adapter or driver installation required, for simple and hassle-free installation - No assembly or searching for the right cable required. With support for SuperSpeed USB 3.0 connectivity at transfer rates up to 5 Gbps (10 times faster than USB 2.0), and backward compatibility with USB 2.0, the USB 3.0 to eSATA adapter cable provides a fast and easy-to-use Plug-and-Play experience for home, office or laptop users alike. Backed by a StarTech.com 2-year warranty and free lifetime technical support. The StarTech.com Advantage- Integrated cabling, with no driver installation delivers a complete and easy-to-use solution- Support for USB 3.0 with transfer rates up to 5 Gbps, while also backward compatible with USB 2.0 for older systems- Long, integrated cables allow for easily running from the back of computers or other hard-to-reach places to more accessible locations

## Main specifications:

### Ports & interfaces

Connector 1:	USB 3.0 A
Connector 2:	eSATA
Gender:	Male/Male

### Design

Colour of product:	Black
Cable length:	1.36 m
Certification:	CE, FCC, RoHS

### Performance

Maximum data transfer rate:	3 Gbit/s
Compatible operating systems:	Windows 2000/ XP(32/64bit)/ Server 2003(32/64bit)/ Vista(32/64bit)/ 7(32/64bit)/ Server 2008 R2, Mac OS 10.2.x ~ 10.6.x

### Operational conditions

Operating temperature (T-T):	0 - 50 °C
Storage temperature (T-T):	-20 - 80 °C
Relative humidity:	5 - 85 %

### Packaging data

Package width:	140 mm
Package depth:	175 mm
Package height:	30 mm
Package weight:	100 g
Package length:	175.00 mm

### Weight & dimensions

Net weight: 77 g

Inner carton

Quantity inner carton: 50 pc(s)

\*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.