

3 ft SuperSpeed USB 3.0 to eSATA Cable Adapter

StarTech ID: USB3S2ESATA



The USB3S2ESATA USB 3.0 to eSATA Adapter Cable lets you connect an external SATA (eSATA) device or enclosure to a host computer through USB 3.0, in a single convenient package. The adapter cable combines USB 3.0 and eSATA cables into an integrated cable, with no external power adapter or driver installation required, for simple and hassle-free installation - No assembly or searching for the right cable required.

With support for SuperSpeed USB 3.0 connectivity at transfer rates up to 5 Gbps (10 times faster than USB 2.0), and backward compatibility with USB 2.0, the USB 3.0 to eSATA adapter cable provides a fast and easy-to-use Plug-and-Play experience for home, office or laptop users alike.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Applications

- Laptop users who do not want to bother with having to assemble or carry multiple cables
- Home or office users who would not need to move the eSATA enclosure frequently (fixed distance/location)
- Connect an eSATA enclosure via the more commonly available USB interface



Features

- SuperSpeed USB 3.0 compliant host interface, with supported data transfer rates of up to 5 Gbps
- eSATA interface compliant with SATA revision 2 and other SATA revisions, with supported data transfer rates up to 3 Gbps
- Integrated 1m (3.3ft) USB 3.0 cable and 30cm (1ft) eSATA cable
- No driver or software installation required
- Backward compatible with USB 2.0 systems, with support for USB 2.0 transfer rates of up to 480 Mbps
- Built-in Link/Activity LED indicator
- Plug-and-Play and Hot-Swap compatible

Technical Specifications

Warranty 2 Years

Chipset ID LucidPort - USB300

Max Drive Capacity Tested up to 2.0 TB

Port Multiplier No

Type and Rate USB 3.0 - 5 Gbit/s
Type and Rate SATA II (3 Gbps)

Drive Connectors 1 - eSATA (7 pin; Data) Plug

Host Connectors 1 - USB Type-A (9 pin) USB 3.0 Male

OS Compatibility OS independent; No software or drivers required

Note eSATA port does not support Port Multiplier.

System and Cable Requirements Available USB port

LED Indicators 1 - Link/Activity Humidity 5% \sim 85% RH

Operating Temperature 0°C to 50°C (32°F to 122°F)
Storage Temperature -20°C to 60°C (-4°F to 140°F)

Color Black Enclosure Type Plastic

Product Length 4.5 ft [1.4 m]
Product Weight 2.9 oz [81 g]
Shipping (Package) Weight 4.6 oz [131 g]

Included in Package 1 - USB 3.0 to eSATA cable

Included in Package 1 - Instruction Manual





Certifications, Reports and Compatibility







