

# StarTech.com USB3SSATAIDE (USB3SSATAIDE)

StarTech.com USB 3.0 to SATA or IDE Hard Drive Adapter Converter - 2.5 / 3.5 IDE and SATA to USB 3 Adapter - HDD / SSD to USB Converter



## Price details:

Price excl. VAT: 38.28 €

Eco fees: 0.04 €

VAT 21 %: 8.05 €

## Product details:

Product code: USB3SSATAIDE

EAN: 0065030851091

Manufacturer: StarTech.com

**46.37 €**

\* VAT included

PDF generated on: 4 August, 2016

StarTech.com  
Hard-to-find made easy

The USB3SSATAIDE USB 3.0 to IDE/SATA Adapter Cable connects any standard 2.5in or 3.5in SATA or IDE hard drive to a computer through an available USB 3.0 Port (Backward compatible with USB 2.0). The adapter lets you connect a bare drive with no enclosure, saving time and hassle.

The USB 3.0 SATA/IDE Adapter lets you externally connect a bare drive with no drive enclosure or HDD dock required, and features LED indicators that allow you to easily monitor status and activity updates.

The adapter cable works with Windows®, Linux, and Mac® computers and does not require any software or driver installation - a true plug-and-play solution for adding cost-effective external storage, or overcoming incompatibility between all hard drives and USB enabled motherboards that may not be SATA or IDE-equipped.

Backed by our 2-year warranty, the USB3SSATAIDE USB 3.0 to IDE/SATA Adapter Cable comes complete with universal adapter and power cords, providing the additional power required to connect 3.5-inch and larger capacity 2.5-inch hard drives.

### The StarTech.com Advantage

- Versatile adapter, supports both 2.5in/3.5in SATA, and IDE hard drives
- USB 3.0, for fast access to external storage at up to 5Gbps
- Backward compatible with USB 2.0 and 1.1

## Main specifications:

### Ports & interfaces

Connector 1:	USB 3.0 A
Connector 2:	IDE/SATA/LP4
Gender:	Male/Female

### Design

Colour of product:	Black
Material:	Plastic
LED indicators:	Activity,Link
RoHS compliance:	Y
Certification:	CE, FCC

### Performance

Maximum data transfer rate:	4.8 Gbit/s
Output current:	2000 mA
Chipset:	Innostor - IS611
Hot-swap:	Y
Plug and Play:	Y

### Operational conditions

Operating temperature (T-T):	0 - 50 °C
Storage temperature (T-T):	-20 - 60 °C
Relative humidity:	5 - 85 %

#### Weight & dimensions

Width:	70 mm
Depth:	43 mm
Height:	18 mm
Weight:	62 g

#### Packaging data

Package width:	148 mm
Package depth:	215 mm
Package height:	50 mm
Package weight:	653 g
Package type:	Box

#### Packaging content

Cables included:	AC,SATA
AC adapter included:	Y
Manual:	Y