- 4 outlets
- 7.38" length
- Lighted master switch

All metal housing



DESCRIPTION

The Waber-by-Tripp Lite 4SPDX Power Strip offers a convenient method of power distribution in workbench, wallmount or floor mount applications. Includes 4 NEMA 5-15R output receptacles with 1.520 inch center-to-center spacing, 6 foot AC line cord and keyhole mounting for installation in a wide variety of applications. Corded, multi-outlet strip reduces cabling clutter and enables the connection of multiple electrical devices to a single AC wall socket. Unfiltered electrical pass-through makes 4SPDX ideal for distributing alternate waveform UPS or generator power. Features rugged metal housing, lighted power switch with integrated 15 amp resettable circuit breaker and attractive beige color scheme. Lifetime warranty.

PLUG / OUTLETS - Input: NEMA 5-15P / Output: 4 NEMA 5-15R

ELECTRICAL - 120VAC, 50/60Hz, 15A (Requires standard NEMA 5-15R wall receptacle)

FORMAT - Corded power distribution strip

KEY BUYING POINTS

- Multi-outlet power strip offers convenient power distribution in workbench, wallmount or floor mount applications
- Includes 4 NEMA 5-15R output receptacles with 1.520 inch center-to-center spacing
- Lighted combination power switch with integrated circuit breaker
- Keyhole mounting support permanent installation on a wide variety of surfaces
- UL1363 (USA), cUL (Canada)
- 15 amp power handling capacity
- 6 foot AC line cord
- Lifetime warranty

TYPICAL APPLICATIONS

Offers multiple outlet power distribution in workbench, wallmount or floor mount applications. Unfiltered electrical pass-through makes
 4SPDX ideal for distributing alternate waveform UPS or generator power to protected equipment.

PACKAGE INCLUDES

- 4SPDX Power Strip
- · Warranty information

COMPLETE SPECIFICATIONS

SYSTEM OVERVIEW	
System overview:	4 outlet power strip, 6 ft. cord
Voltage compatibility:	120VAC
Frequency compatibility:	50/60 Hz
OUTPUT	
Output volt amp capacity (amps):	15A
Outlet quantity / type:	4 Nema 5-15R
Outlet orientation:	Single row of 4
Outlet spacing:	1.520 in.
INPUT	
Input connection type:	Nema 5-15P input plug
Input cord length (ft.):	6
Input cord length (m):	1.8288
Recommended electrical service:	15A 120V
LEDS ALARMS & SWITCHES	
Switches:	Lighted combination switch / circuit breaker
PHYSICAL	
Unit Dimensions (HWD/in):	7.5 x 2.5 x 1.5
Unit Dimensions (HWD/cm):	19.1 x 6.4 x 3.8
Material of construction:	Metal
Integrated keyhole mounting tabs:	Keyhole mounting tabs enable mounting to a variety of surfaces
Housing color:	Beige
Receptacle color:	Beige
AC line cord color:	Beige
CERTIFICATIONS	
UL1363 (Power Tap):	UL1363
cUL / CSA (Canada):	cUL
WARRANTY	
Product warranty:	Lifetime

The policy of Tripp Lite is one of continuous improvement.

Specifications are subject to change without notice.

Therefore, your product may vary slightly from what is currently listed.



Tripp Lite World Headquarters 1111 W. 35th Street Chicago, IL 60609 USA

> Customer Support (773) 869-1234

© 2004 Tripp Lite. All Rights Reserved.