



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: SUPER6OMNID

Protect It! Surge Suppressor



Highlights

- 6 universal outlets
- 1.8 m power cord with German/French plug
- 750 joule rating
- Lighted on/off switch with integrated circuit breaker
- Lifetime warranty

Description

Tripp Lite's Protect It! SUPER6OMNI D offers economical AC surge suppression for full protection of 220-250V workstations, desktop PCs, telecom systems and other sensitive electronics. Built-in AC surge suppression shields connected equipment from damage and performance problems due to transient surges. The SUPER6OMNI D offers 6 universal outlets and a 1.8 meter AC line cord with German/French plug. AC suppression rated at 750 joules shields equipment from surges and line noise. Lighted on/off switch with integrated circuit breaker provides power control over connected equipment. Right-angle outlets keep connected cords from blocking adjacent outlets. Attractive light gray high-impact housing. Lifetime warranty.

INPUT: 1.8 m AC line cord with German/French plug

OUTPUT: 6 universal receptacles

ELECTRICAL: 220-250V AC, 50/60Hz, 10A

FORMAT: Corded multi-outlet strip

SUPPRESSION: - AC: 750 joules

Applications

- Ideal for any desktop, network or home computing application requiring AC surge suppression

Package Includes

- SUPER6OMNI D AC surge suppressor
- Instruction manual and warranty information

Features

- Protect It! SUPER6OMNI D offers economical AC surge suppression
- 750 joules AC surge suppression shields equipment from surges and line noise
- 6 universal outlets protect computers and peripherals
- 1.8 m AC line cord with German/French plug
- Built-in power switch and 10 amp circuit breaker offers power control and overload protection over all outlets
- Fail-safe thermal fusing protects against fire and other damage in the event of an extreme, extended overvoltage or surge condition

- Attractive light gray high-impact housing with keyhole mounting tabs allow versatile placement options
- Right-angle outlets keep connected cords from blocking adjacent outlets
- Lifetime warranty

Specifications

OVERVIEW	
Intended Application	Home/Office
SYSTEM OVERVIEW	
Voltage compatibility (VAC)	220-250
OUTPUT	
Frequency compatibility	50 / 60 Hz
Output volt amp capacity (amps)	10
Overload protection	10A resettable illuminated combo switch/circuit breaker
Outlet quantity / type	6 universal outlets
Outlet orientation	right-angled
INPUT	
Recommended Electrical Service	230V (220-250V)
Input connection type	German
Input cord length (ft.)	6
Input cord length (m)	1.8
LEDS ALARMS & SWITCHES	
Switches	Two position power switch
SURGE / NOISE SUPPRESSION	
AC suppression joule rating	750
AC suppression response time	< 1 ns
Protection modes	Includes full normal mode (H-N) and common mode (N-G/H-G) line surge suppression
DATALINE SURGE SUPPRESSION	
Telephone/DSL Protection	No
Cable (Coax) Protection	No
Network (Ethernet) Protection	No
PHYSICAL	
Shipping weight (lbs)	1.32
Shipping weight (kg)	0.60
Unit Dimensions (HWD/in)	15.50 x 2.50 x 1.25
Unit Dimensions (HWD/cm)	39.4 x 6.4 x 3.2
Shipping Dimensions (HWD/in)	18.50 x 4.50 x 2.00

Shipping Dimensions (HWD/cm)	47.0 x 11.4 x 5.1
Unit weight (lbs)	1.0
Unit weight (kg)	0.45
Material of construction	Plastic
Integrated keyhole mounting tabs	Yes - slotted
AC line cord color	light gray
Style	Strip
WARRANTY	
Product Warranty Period (U.S., Canada & Puerto Rico)	lifetime

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=2733.

Copyright © 2010 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.