



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: UL800CB-15

### Waber-by-Tripp Lite Power Strip with 10 Side-by-Side Outlets and 15-ft. Cord

#### Highlights

- 10 outlets
- 15 ft. cord
- 17.5" length
- Lighted master switch
- All metal housing



#### Description

The Waber-by-Tripp Lite UL800CB-15 Power Strip offers reliable, convenient, cost effective method of power distribution for appliances, power tools, lighting and other electrical equipment. Includes 10 NEMA 5-15R output receptacles arranged with traditional wall socket spacing to accept large equipment plugs with minimal outlet blockage. Includes 15 foot AC line cord and flat sheet metal flanges for installation in a wide variety of applications. Corded, multi-outlet strip reduces cabling clutter and enables the connection of multiple electrical devices to a single AC wall socket. Unfiltered electrical pass-through makes UL800CB-15 ideal for distributing alternate waveform UPS or generator power. Features rugged all-metal housing, lighted power switch, 15 amp resettable circuit breaker and attractive blue/gray color scheme. PLUG/OUTLETS - Input: NEMA 5-15P/Output: 10 NEMA 5-15R ELECTRICAL - 120VAC, 50/60Hz, 15A (Requires standard NEMA 5-15R wall receptacle) FORMAT - Corded power distribution strip

#### Applications

- Offers reliable, convenient, cost effective method of power distribution for appliances, power tools, lighting and other electrical equipment. Unfiltered electrical pass-through makes UL800CB-15 ideal for distributing alternate waveform UPS or generator power to protected equipment.

#### Package Includes

- UL800CB-15 Power Strip
- Warranty information
- Instruction manual

#### Features

- Multi-outlet power strip offers reliable, convenient, cost effective method of power distribution for appliances, power tools, lighting and other electrical equipment.
- Includes 10 NEMA 5-15R output receptacles arranged with traditional wall socket spacing to accept large equipment plugs with minimal outlet blockage
- Lighted on/off switch controls power to all outlets
- Keyhole mounting tabs support permanent installation on a wide variety of surfaces
- UL Recognized Component, Tested to UL1363 (Power Tap), cUL (Canada)
- 15 amp power handling capacity with circuit breaker
- 15 foot AC line cord

#### Specifications

|               |
|---------------|
| <b>OUTPUT</b> |
|---------------|

|   |  |
|---|--|
| Frequency compatibility                   | 50 / 60 Hz   |
| Circuit Breaker (amps)                    | 15   |
| Outlet quantity / type                    | 10 Nema 5-15R  |
| Outlet orientation                        | Two rows of 5 outlets  |
| <b>INPUT</b>                              |  |
| Nominal Input Voltage(s) Supported        | 120V AC  |
| Recommended Electrical Service            | 15A 120V   |
| Input connection type                     | Nema 5-15P   |
| Input cord length (ft.)                   | 15   |
| Input cord length (m)                     | 4.572  |
| Input cord gauge, type                    | 14 gauge, SJT  |
| Voltage compatibility (VAC)               | 120  |
| <b>LEDS ALARMS &amp; SWITCHES</b>         |  |
| Switches                                  | Lighted 2 position switch controls power to all outlets                                    |
| <b>PHYSICAL</b>                           |  |
| Unit Dimensions (HWD/in)                  | 17.5 x 4 x 1.75  |
| Unit Dimensions (HWD/cm)                  | 44.5 x 10.2 x 4.4  |
| Material of construction                  | Metal  |
| Integrated keyhole mounting tabs          | Keyhole mounting tabs enable mounting to a variety of surfaces                             |
| Receptacle Color                          | Black  |
| AC line cord color                        | Black  |
| Outlets center to center measurement      | Distance between horizontal outlets = 71.45mm; Distance between vertical outlets = 38.90mm |
| Keyhole slot center to center measurement | Distance between end tabs = 462.30mm   |
| <b>CERTIFICATIONS</b>                     |  |
| UL1363 (Power Tap)                        | UL Recognized Component, Tested to UL1363 (Power Tap)                                      |
| cUL / CSA (Canada)                        | cUL  |
| <b>WARRANTY</b>                           |  |
| Product Warranty Period (Worldwide)       | Lifetime limited warranty  |

## Related Items

### Optional Products

| Related Model               | Description   | Qty. |
|-----------------------------|---|------|
| <a href="#">PDU5IDEBRKT</a> | Enables Vertical Installation of Select 1U PDUs, Power Strips and Surge Suppressors in SmartRack Configurations | 1    |

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?variables.txtModelID=1961](http://www.tripplite.com/en/products/model.cfm?variables.txtModelID=1961).

---

Copyright © 2012 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.