

## NOT For Patient Areas - 4-outlet Power Strip with Hospital-Grade Plug & Receptacles

MODEL NUMBER: **PS-415-HG**



### Description

Tripp Lite's PS-415-HG Power Strip offers 15A AC power distribution in a rugged all-metal outlet strip for 120V applications. Features 4 output receptacles, 15-ft. AC power cord and a built-in resettable circuit breaker that controls power to all outlets and protects against overloads. Switchless design prevents accidental shutoff. Optional-use keyhole mounting tabs and flanges.

PLUG/OUTLETS: NEMA 5-15P-HG hospital-grade plug and 4 NEMA5-15R-HG hospital-grade receptacles

ELECTRICAL: 120V AC, 50/60Hz, 15A

FORMAT: All-metal corded multi-outlet strip

### Features

- Rugged all-metal housing withstands years of use without breakage
- 4 x NEMA 5-15R-HG hospital-grade output receptacles
- 15-ft. AC cord with integrated, molded NEMA5-15P-HG hospital-grade plug
- Optional-use keyhole mounting tabs and flanges
- Switchless design prevents accidental shutoff
- 15A electrical capacity with built-in resettable circuit breaker
- 120V, 50/60Hz
- Certified by UL (USA) and cUL (Canada)

## Specifications

OVERVIEW	
Intended Application	Hospital/Medical
Model Type	NOT For Patient Areas

### Highlights

- Versatile power distribution strip
- 4 hospital-grade receptacles and hospital-grade plug
- 15-ft. cord
- 15A resettable circuit breaker

### Applications

- AC power distribution with hospital-grade receptacles and plug where durability and reliability are required.
- Not for use where NEC requires hospital-grade receptacles.

### Package Includes

- PS-415-HG Power Strip
- Owner's manual and warranty information



<b>OUTPUT</b>	
Frequency compatibility	50 / 60 Hz
Circuit Breaker (amps)	15
Overload protection	15A circuit breaker
Outlet quantity / type	4 NEMA 5-15R-HG
Outlet orientation	Single row of 4
<b>INPUT</b>	
Nominal Input Voltage(s) Supported	120V AC
Recommended Electrical Service	15A 120V
Input connection type	NEMA 5-15P-HG
Input cord length (ft.)	15
Input cord length (m)	4.572
Voltage compatibility (VAC)	120
<b>LEDS ALARMS &amp; SWITCHES</b>	
Audible Alarm	No power switch
<b>PHYSICAL</b>	
Unit Dimensions (HWD/in)	1.5 x 8.65 x 2.5
Unit Dimensions (HWD/cm)	3.8 x 21.9 x 6.4
Material of construction	Metal
Integrated keyhole mounting tabs	Keyhole mounting tabs and flanges enable mounting to a variety of surfaces
Receptacle Color	White
AC line cord color	White
Style	Strip
Outlets center to center measurement	Inner outlets = 32.5mm
Keyhole slot center to center measurement	Distance between keyhole tabs = 127mm; Distance between end tabs = 207.45mm
<b>CERTIFICATIONS</b>	
UL1363 (Power Tap)	UL1363 (Series Number: AGIB12015SL)
cUL / CSA (Canada)	cUL (Series Number: AGIB12015SL)
<b>WARRANTY</b>	



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

Product Warranty Period (Worldwide)	Lifetime limited warranty
-------------------------------------	---------------------------

© 2014 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.