

# NOT For Patient Areas - 6-outlet Power Strip with Hospital-Grade Plug & Receptacles & 15-ft. Cord

MODEL NUMBER: PS-615-HG



### **Highlights**

- Versatile power distribution strip
- 6 hospital-grade receptacles and hospital-grade plug
- 15-ft. cord
- 15A resettable circuit breaker

#### **Applications**

- AC power distribution with hospital-grade receptacles and plug where durability and reliability are required.
- Not for use where NEC requires hospital-grade receptacles.

### **Package Includes**

- PS-615-HG Power Strip
- User manual with warranty information

#### Description

Tripp Lite's PS-615-HG Power Strip offers 15A capacity AC power distribution in a rugged all-metal outlet strip for 120V applications. Features 6 hospital grade-receptacles, 15-ft. AC power cord and built-in resettable circuit breaker. Switchless design prevents accidental shutoff. Optional-use keyhole mounting tabs and flanges.

PLUG/OUTLETS: NEMA 5-15P-HG hospital-grade plug and 6 NEMA 5-15R-HG hospital-grade receptacles

ELECTRICAL: 120V AC, 50/60Hz, 15A

FORMAT: All-metal corded multi-outlet strip

#### **Features**

- Rugged all-metal housing withstands years of use without breakage
- 6 x NEMA 5-15R-HG hospital-grade output receptacles
- 15-ft. AC cord with integrated, molded NEMA 5-15P-HG hospital-grade plug
- Optional-use keyhole mounting tabs and flanges.
- Switchless design prevents accidental shutoff
- 15A electrical capacity with built-in resettable circuit breaker
- 120V, 50/60Hz electrical compatibility
- Certified by UL (USA) and cUL (Canada)

## **Specifications**

OVERVIEW	
Intended Application	Hospital/Medical
Model Type	NOT For Patient Areas



OUTPUT		
Frequency compatibility	50 / 60 Hz	
Circuit Breaker (amps)	15	
Overload protection	15A circuit breaker	
Outlet quantity / type	6 NEMA 5-15R-HG	
Outlet orientation	Single row of 6	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	15A 120V	
Input connection type	NEMA 5-15P-HG	
Input cord length (ft.)	15	
Input cord length (m)	4.572	
Voltage compatibility (VAC)	120	
LEDS ALARMS & SWITCHES		
Switches	No power switch	
PHYSICAL		
Unit Dimensions (HWD/in)	1.5 x 13.75 x 2.5	
Unit Dimensions (HWD/cm)	3.8 x 34.9 x 6.4	
Material of construction	Metal	
Integrated keyhole mounting tabs	Keyhole mounting tabs and flanges enable mounting to a variety of surfaces	
Receptacle Color	White	
AC line cord color	White	
Style	Strip	
Outlets center to center measurement	38.7mm	
Keyhole slot center to center measurement	Distance between keyhole slots = 261.92mm; Distance between end tabs = 330.17mm	
CERTIFICATIONS		
UL1363 (Power Tap)	UL1363 (Series Number: AGIB12015SL)	
cUL / CSA (Canada)	cUL (Series Number: AGIB12015SL)	
WARRANTY		



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Product Warranty Period (Worldwide) Lifetime limited warranty

© 2014 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.