USR5470, USR015470 & USR805470 Wireless Starter Kit

Includes Model 5462 802.11g Wireless Router & Model 5422 802.11g Wireless USB Adapter

> The U.S. Robotics Wireless Starter Kit is ideal for users setting up their first wireless network. The kit includes a 4-Port Wireless Router and slim profile USB Adapter, providing 54 Mbps wireless performance and supporting both 802.11g and 802.11b standards.

Integrated firewall and wireless security protects your network and included Parental Control allows blocking of offensive or inappropriate web sites.



U.S.Robotics®

Features and Benefits What you need to start a Wireless network

Easy to Install and Use Quick and easy installation with Universal Plug and Play, will

have you sharing your Internet connection in minutes

Great Wireless Compatibility Compatible with all Wi-Fi (54 Mbps 802.11g and 11 Mbps

802.11b) wireless devices

Flexibility and Portability Slim profile USB Adapter is easily transportable and USB

> format is compatible with both laptop and desktop PCs, delivering high performance with a USB 2.0 interface

Solid Security Built-in firewall protects your PCs against hackers - support

for Web Site blocking, MAC Address Authentication,

64/128-bit WEP encryption and WPA

Integrated 4-Port 10/100 Ethernet switch to support up to 4 Universal Connectivity

wired devices (up to 253 with additional hubs/switches)
















USR5470, USR015470 & USR805470 Wireless Starter Kit

802.11g Wireless Router

Specifications and Standards

General

- Complies with IEEE 802.11g 54 Mbps and 802.11b 11 Mbps wireless standards
- Operating Channels: 11 (US, Canada), 13 (Europe -ETSI)
- RF Power Output: 16 dBm 802.11b & 15 dBm 802.11g
- Supports Universal Plug and Play (Windows Me and XP)
- Auto MDI/MDIX support on LAN ports
- IEEE 802.3 10BASE-T Ethernet
- IEEE 802.3u 100BASE-TX Class II Fast Ethernet repeater
- IEEE 802.3x Flow Control
- Integrated firewall protection for security
- Static and dynamic IP addressing
- DHCP server (LAN) and client (WAN)
- Embedded PPP over Ethernet (PPPoE)
- Embedded PPTP Client
- VPN pass-through support for PPTP, IPSec, and L2TP
- DMZ support
- Supports up to 253 clients (with additional hubs or switches)

Security

- Encryption WEP 64/128 bit, WPA
- Enhanced security with secure key generation WPA-PSK (including TKIP)
- Mac Address Authentication, Disable Broadcast SSID

Physical

- Visual diagnostic LEDs: Power, WAN, LAN, WLAN
- One RJ-45, 10/100 Mbps Ethernet WAN port
- Four RJ-45, 10/100 Mbps Ethernet LAN ports

Dimensions/Weight

• 6.13 x 5 x 1.12 inches (15.6 x 12.7 x 2.84 cm)

Regulatory

- · FCC approved
- · IC approved
- UL/CUL listed
- CE Approved

IC Approved FC CULUS CE0560 © © &

802.11g Wireless USB Adapter

Specifications and Standards

General

- Complies with IEEE 802.11g 54 Mbps and 802.11b 11 Mbps wireless standards
- Operating Channels: 11 (US, Canada), 13 (Europe ETSI)
- USB 2.0 (backward compatible with USB 1.1)
- Supports Universal Plug and Play (Windows Me and XP)
- RF Power Output: 17 dBm (maximum)

Security

• Encryption - WEP 64/128 bit, WPA, 802.1x authentication

Physical

- Low profile stick format
- Visual diagnostic LED

Dimensions

• 3.25 x .8 x .375 inches (8.26 x 2 x .95 cm)

Regulatory

- · FCC approved
- · IC approved
- UL/CUL listed
- CE Ap proved

Wireless Network Starter Kit

Package Contents

- U.S. Robotics Wireless Router & Wireless USB Adapter
- One Ethernet cable
- · Quick Installation Guide
- CD with full User Manual
- Power Supply

Dimensions/Weight

- 15 (W) x 13 (H) x 3.64 (D) inches (38.1 x 33 x 9.25 cm)
- Weight: 2.6 lb (1.18 Kg)

Language Support

- Blister pack: English, German, French, Italian, Spanish, Dutch
- Install guide: English, German, French, Italian, Spanish, Dutch
- User guide (CD Only): English, German, French, Italian, Spanish, Dutch, Czech, Polish, Hungarian, Portuguese, Turkish, Russian

Minimum Systems Requirements

- Router Connect any device that supports 10/100 or 1000 Mbps Ethernet and RJ-45 connector
- USB Adapter Any PC or Laptop with available USB port and Windows 98SE/Me/2000/XP

Warranty

• 2-year limited manufacturer warranty from date of purchase