

ViewSonic® VX924 LCD Display

19" LCD XTREME 4MS CLEARMOTIV™ DISPLAY



Extremely fast, extremely clear.

ViewSonic's 19" VX924 LCD delivers **XTREME PERFORMANCE WITH ASTOUNDING, INDUSTRY-LEADING 4MS VIDEO RESPONSE TIME** for smooth, broadcast-quality, full-motion video. ViewSonic's innovative Dynamic Structure™ and Amplified Impulse™ technologies combine to replace blurs and ghosts with pure, vibrant, absolutely clear images. **GAMING, VIDEOS AND GRAPHIC INTENSIVE APPLICATIONS HAVE NEVER LOOKED BETTER.** OptiSync® technology further enhances this display's appeal by enabling connections to multiple digital and analog video sources. The VX924 also features 1280x1024 native resolution, high brightness and contrast ratios, and wide viewing angles. All these performance features are packed into the elegant, floating head, slim bezel design that looks great on any contemporary desktop.



VIEWSONIC PRODUCTS, PROGRAMS AND SERVICE HAVE NOW WON MORE THAN 2,000 AWARDS WORLDWIDE.

Beauty and performance for demanding professionals

❖ ClearMotiv 4ms video response time

XTREME 4ms video response enables digital HD broadcast-quality full motion video.

❖ **OPTISYNC** digital/analog inputs expand your connectivity

Multi-mode input technology supports both digital (DVI) and analog (VGA) signals for ultimate compatibility and configuration flexibility.

❖ Ultra-high brightness and contrast

270-nit brightness (typ) and 550:1 contrast ratio (typ) for rich, detailed images.

❖ Stylish slim-bezel design

The full 19" viewable screen in a thin bezel lets you see more without taking up valuable desktop real estate. The high neck and floating head design accentuate the visual experience.

❖ XtremeView® ultra-wide viewing angles extend your view

Up to 160° viewing angles horizontally and vertically provide enhanced image legibility from all directions.

❖ Full 19" viewable

❖ 1280x1024 resolution

❖ OnView® controls for superior screen adjustability

Screen adjustments are precisely made via an easy-to-use on-screen menu.

❖ VESA® 100mm wall mount compliant

❖ PC and Mac® compatible

❖ TCO'99 and ENERGY qualified



Create a Total Desktop Solution
Add ViewMate® Collection accessories to your display for a complete desktop solution. Choose stylish mice and wireless keyboards, or turn that display into a TV with a TV/video processor.


GO XTREME

ViewSonic®

the choice of professionals

ViewSonic® VX924 LCD Display

19" LCD XTREME 4MS CLEARMOTIV™ DISPLAY



1. Sleek buttons control all major functions
2. Extended neck, floating head design
3. Space-saving slim-line panel design is only 2.6" thick
4. Slim bezel, attractive styling



Available colors:
Black & silver

19" LCD DISPLAY WITH 4MS CLEARMOTIV™ BROADCAST QUALITY

LCD	Type	19" Color TFT Active Matrix SXGA LCD
	Display Area	14.8" horizontal x 11.9" vertical; 19.0" diagonal
	Optimum Resolution	1280x1024
	Contrast Ratio	550:1 (typ)
	Viewing Angles	160° horizontal, 160° vertical @ contrast ratio > 5
	Response Time	4ms (gray-to-gray); 5ms(typ)
	Light Source	Long life, 40,000 hrs. (typ)
INPUT SIGNAL	Video	RGB analog (75 ohms, 0.7 Vp-p); DVI-D (TMDS, 100 ohms)
	Sync	H/V separated (TTL), composite, sync-on-green
COMPATIBILITY	PC	VGA up to 1280x1024 non-interlaced
	Mac®*	Power Mac™ G3/G4/G5 1280x1024
CONNECTOR	Analog	15-pin mini D-sub and DVI-D
	Power	3-pin AC plug, (CEE22)
POWER	Voltage	AC 100–240V, 50–60Hz (auto switch)
	Consumption	35W (typ)
CONTROLS	Basic	Power, 1, down, up, 2
	OnView®	Auto image adjust, brightness, contrast, input select (analog, digital), ViewMatch® color adjust (sRGB, 9300K, 6500K-default, 5400K, user color - RGB), information (resolution, H. frequency, V. frequency, pixel clock, model number, serial number), manual image adjust (H. size, H. position, V. position, fine tune, sharpness), setup menu, language (English, French, German, Italian, Spanish, Finnish, Japanese, Traditional Chinese, Simplified Chinese), resolution notice, OSD position, OSD timeout, OSD background, memory recall
OPERATING CONDITIONS	Temperature	32–104°F (0–40°C)
	Humidity	10–90% (no condensing)
DIMENSIONS (W x H x D)	Physical	17.0" x 18.4" x 7.9" (with stand)
		431mm x 468mm x 201mm (with stand)
		17.0" x 14.6" x 2.6" (without stand)
WEIGHT	Net	14.8 lb. (6.7 kg) (with stand)
	Gross	18.7 lb. (8.5 kg) (with stand)
REGULATIONS		UL, cUL, FCC-B, CB, CE, ENERGY, NOM, NEMKO/GS (covers TUV/GS), NEMKO ERGO (covers TUV/ERGO, ISO13406-2 & MPR II), TCO'99, GOST-R + 20 original copies hygienic, SASO, PCBC, VCCI, BSMI, CCC, PSB, C-TICK, Argentina-S, PSE (power adapter), Green Mark
POWER MANAGEMENT		Meets TCO'99 and ENERGY standards
PACKAGE CONTENTS		LCD display, power cable, 15-pin VGA video cable, DVI cable, Quick Start Guide, ViewSonic Wizard CD
WARRANTY		Three-year limited warranty on LCD, parts and labor

specifications



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

ViewSonic® 
the choice of professionals

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Phone (800) 888-8583 or (909) 444-8888 • In Canada (866) 262-1967 • Fax (909) 839-7922 • SalesInfo@ViewSonic.com • ViewSonic.com

*Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country. See your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2005 ViewSonic Corporation. All rights reserved. [12342-01B-04/05] VX924-1

For more product information, visit us on the web at ViewSonic.com