

Expanding Your Viewing Experience Full HD Frameless Display for Ultimate Entertainment



Designed with frameless bezel and touch keys, the ViewSonic VX2370Smh-LED/VX2770Smh-LED sets a new milestone for display design delivering cutting-edge, trendy ambience into any living space or office. Through the remarkable image quality of Full HD 1080P, 30,000,000:1 dynamic contrast ratio, and up to 4ms response time, combined with SuperClear™ IPS, the VX2370Smh-LED/VX2770Smh-LED brings vivid and sharp images to life with no limited viewing angles. An HDMI port provides high resolution image/video connection with devices for gaming, graphics, and HD entertainment. A pair of speakers powered by SRS Premium Sound® delivers true-to-nature high-end stereo, complementing the refined display perfectly for a wide variety of applications.

Frameless and slim with touch keys



The frameless bezel on VX2370Smh-LED/ VX2770Smh-LED removes the boundary between reality and virtuality, featuring an elegant and glossy finish to complement any home or office. Sleek and seamless touch function key provides a simple and intuitive touch experience, making screen adjustment easy and fast. The VX2370Smh-LED/ VX2770Smh-LED is a stylish addition to a wide range of environments.

SuperClear™ IPS wide-viewing angles

Industry-leading SuperClear™ IPS Wide Viewing Angles technology delivers 178° viewing angle from the horizontal and vertical with an accurate, vibrant, and dynamic image. Brightness levels are consistent across all viewing angles with no distortion or decay.



Normal

SuperClear™

4ms fast response time at optimum

VX2370Smh-LED/ VX2770Smh-LED is equipped with IPS panel, delivering not only wide-viewing angle but also fast response time. In optimal condition, VX2370Smh-LED/ VX2770Smh-LED can reach up to 4ms response time, bringing the smooth and no-blur image quality when watching action movies or playing games featuring fast motion.

VX2370Smh-LED/VX2770Smh-LED

Expanding Your Viewing Experience Full HD Frameless Display for Ultimate Entertainment

On-Live SRS Premium Sound® surrounding stereo

Dual 1.5-Watt speakers, powered by SRS Premium Sound® surround stereo delivers audiophile quality sound for anyone seeking supreme audio performance and gaming experience. SRS Premium Sound® produces deep rich bass and crisp highs with no requirement to connect external speakers, maximizing desk space to let the all-immersive audio journey begin.



30,000,000:1 dynamic contrast ratio

Dynamic Contrast Ratio achieves a superior 30,000,000:1 level, delivering maximum definition to grayscale, darker blacks, and brighter whites, while rendering everything in between with the finest detail, for rich and natural imagery.



Normal



Dynamic Contrast Ratio

HDMI Inputs

HDMI Interface on the VX2370Smh-LED/ VX2770Smh-LED allows flawless streaming with a variety of media devices, including computers, set-top boxes, Blu-ray disc players, HD digital cameras, gaming consoles, and many others with HDMI. The convenience of HDMI enables image/video streaming between life, work, and entertainment for the ultimate true high definition experience.



Specifications

Item		Content	
		VX2370Smh-LED	VX2770Smh-LED
LCD Panel	Display Area	23" Wide	27" Wide
	Optimum Resolution	1920 x 1080	
	Brightness	250 cd / m ²	
	Contrast Ratio	1,000:1	
	Dynamic Contrast Ratio	30,000,000:1	
	Viewing Angles	178° / 178°	
	Response Time	GTGbw: 4ms	
	Pixel Arrange	0.265 mm x 0.265 mm	0.3114 mm x 0.3114 mm
	Panel Surface	Anti-glare Type, 3H Hardness	
	Backlight	White-light LED	
Backlight Life	30,000 Hrs (Min.)		
Input	Analog	RGB Analog (75Ω, 0.7 / 1.0 Vp-p)	
	Video	DVI / HDMI (TMDS, 100Ω)	
	Sync	Separate Sync / Composite Sync / SOG	
	Frequency	Fh = 24 ~ 83 kHz; Fv = 50 ~ 76 Hz	
Compatibility	PC	VGA up to 1920x1080 non-interlaced	
	MAC	Power MAC (up to 1920x1080)	
Connector	Video	Analog: D-sub	
		Digital:DVI- D, HDMI 1.3	

Item		Content		
		VX2370Smh-LED	VX2770Smh-LED	
	Audio Out	3.5mm Jack (Blue)		
	Audio In	3.5mm Jack (Green)		
	Power	External Power Adapter		
Audio	Speaker	1.5W *2		
Ergonomics	Tilt	20° ~ -5°		
Power	Voltage	AC 100 - 240V(Universal); 50 / 60 Hz		
	Consumption	Standard:	27W	Standard: 27W
		Optimize:	23W	Optimize: 23W
Conserve:		20W	Conserve: 20W	
Operating Conditions	Temperature	32° F to 104° F (0° C to 40° C)		
	Humidity	20% to 90% (No condensation)		
Dimensions	W/ Stand	532.38 x 409 x 179.5mm	622.29 x 459.3 x 192.5mm	
Weight	W/ Stand	3.9 Kg	4.98 Kg	
Regulations	CE,CB, BSMI, SASO, C-tick, UL/cUL, FCC-B (including ICES003), TUV-S, UL CoC,MexicoEnergy, GOSTR / Hygienic, UkrSEPRO, TCO 5.2, Erp, CCC, ChinaEnergy, Energy Star, EPEAT Silver, WEEE, RoHS, SVHC list			

What's in the box?

Power Cable (with AC Adapter) *1, D-Sub Video Cable *1, DVI *1, Audio Cable*1, Quick Start Guide *1, ViewSonic Wizard CD-ROM *1

*Specifications are subject to change without notice.