



The power to do more

Reliable colour printer with enhanced print performance and robust security features



## Dell™ Colour Printer - C2660dn

Meet demanding printing needs reliably with the C2660dn printer. This robust printer with a high duty cycle<sup>1</sup> delivers brilliant colour prints at fast speeds, and comes with security features to safeguard your data. Built-in Gigabit Ethernet connectivity enables fast network transfers for greater efficiency, while the optional External Wireless Adapter gives you freedom to print from virtually anywhere within the wireless network<sup>2</sup>.

Designed with the environment in mind, this energy efficient printer features low melt toner technology to help reduce power consumption and save on total cost of ownership. The printer also includes a duplexer for automatic two-sided printing.

Get excellent performance and outstanding value while consuming fewer resources with the Dell Colour Printer – C2660dn.



1. Duty cycle is defined as the maximum number of imaged outputs a device could deliver in a month. This metric provides a comparison of robustness in relation to other Dell printers and multifunction printers.  
2. The printer and the device must be connected on the same network.



Print at fast speeds of up to 27ppm<sup>1</sup> (A4)

## Stellar performance and ease of use

- Get high quality colour and mono prints at fast print speeds of up to 27 ppm (A4)<sup>1</sup>.
- Handle large print loads reliably with a monthly duty cycle<sup>2</sup> of up to 50,000 pages.
- Easily navigate printer functions with the 4-line LCD user interface and 10-digit numeric pad.
- Print directly from a variety of mobile devices with:
  - Dell Mobile Print app (for Android™ mobile devices)<sup>3</sup>
  - AirPrint (for iOS mobile devices)<sup>4</sup>
  - Google Cloud Print™
- Get fast connection to your network with Gigabit Ethernet connectivity.
- Connect to a wireless network with the optional External Wireless Adapter (sold separately).



Protect your data with embedded security features

## Robust security and simplified manageability

- Safeguard sensitive prints from remaining uncollected with Secure Print, which requires users to enter a 4-digit PIN on the printer before releasing the prints.
- Secure network data transmission with Secure Socket Layer (SSL) and Internet Protocol Security (IPSec).
- Simplify driver deployment and setting changes with Dell Open Printer Driver (OPD).
- Monitor, manage and create reports for the Dell printers on your network with the Dell OpenManage™ Printer Manager v2 (OMPM).



Save on printing costs with optional high yield toner cartridges

## Exceptional value and long-term savings

- Benefit from a low cost per page with optional high yield toner cartridges.
- Save on maintenance costs with standard 1-year Limited Warranty<sup>5</sup> and 1-year Next Business Day On-site Service after Remote Diagnosis<sup>5</sup>. Dell printers base and extended warranty also cover the fuser maintenance kit within the warranty period.



Reduce paper consumption with default two-sided printing

## Environmentally-conscious design

- Designed with the environment in mind, the C2660dn is ENERGY STAR® qualified<sup>6</sup> and RoHS compliant<sup>7</sup>.
- Save on energy costs and reduce carbon dioxide emissions with Dell low melt toners, which use less power and shorten first print out time.
- Reduce paper consumption with the default two-sided print setting. The C2660dn also supports printing on recycled, renewable content, and chlorine-free paper.
- Activate the Toner Save mode to reduce toner usage on each printed page.
- Reduce power consumption by activating the Power Save button to put the printer into sleep mode.



1. Measured in accordance with ISO IEC 27434/35 methodology. Actual print speeds will vary with use.  
 2. Duty cycle is defined as the maximum number of imaged outputs a device could deliver in a month. This metric provides a comparison of robustness in relation to other Dell printers and multifunction printers.  
 3. The printer and the mobile device must be connected to the same network.  
 4. AirPrint-enabled printers work with iPad, iPhone (3GS or later), and iPod touch (3rd generation or later) running iOS 4.2 or later.  
 5. For copy of Limited Hardware Warranty, write Dell Products, Dell House, The Boulevard, Cain Road, Bracknell, Berkshire, RG12 1LF, UK or see [www.dell.com/warranty](http://www.dell.com/warranty). For warranty information for other countries, see website: [www.dell.com/servicecontracts](http://www.dell.com/servicecontracts) and then select the country. Service may be provided by third party. Technician will be dispatched if necessary following phone-based troubleshooting. Subject to parts availability, geographical restrictions and terms of service contract. Service timing dependent upon time of day call placed to Dell. Defective unit must be returned. Replacements may be refurbished.  
 6. For details on energy efficiency of ENERGY STAR® qualified products, refer to: [www.energystar.gov](http://www.energystar.gov)  
 7. Meets the requirements of the EU RoHS Directive 2011/65/EU on the Restriction of the use of certain Hazardous Substances (RoHS).

Consumables		Warranty and service options	
<b>Ship-with toner cartridge capacity<sup>1</sup></b>	1,200 pages (black) 1,200 pages (colour - CMY)	<b>Standard service<sup>2</sup></b>	1 Year Limited Hardware Warranty and 1 Year Next Business Day On-site Service after Remote Diagnosis
<b>Standard capacity toner cartridge<sup>1</sup></b>	1,200 pages (black) 1,200 pages (colour - CMY)		
<b>High capacity toner cartridge<sup>1</sup></b>	3,000 pages (black) 4,000 pages (colour - CMY)		
<b>Extra high capacity cartridge<sup>1</sup></b>	6,000 pages (black)		
<b>Imaging Drum</b>	55,000 page yield (black) 55,000 page yield (colour)		
<b>Fuser unit</b>	100,000 pages		
<b>Toner waste container capacity</b>	Up to 30,000 pages		
		<b>Service upgrade options<sup>2</sup></b>	<ul style="list-style-type: none"> <li>• 2 - 5 Years Next Business Day Service after Remote Diagnosis</li> <li>• 1 - 5 Years Dell ProSupport™ available during the term of warranty</li> </ul>

## Accessories



### Optional 550-sheet lockable input drawer

Increase the input capacity of the C2660dn printer to 950 sheets with the optional 550-sheet input drawer.



### External Wireless Adapter

Connect the C2660dn printer to WiFi network with the optional wireless adapter.

## Product Specifications

<b>Physical specifications</b>	<b>Dimensions (W x D x H)</b>	Printer: 439 mm x 485 mm x 379 mm Shipping: 570 mm x 686 mm x 526 mm
	<b>Weight</b>	Printer: 25.6 kg; Shipping: 30.5 kg
	<b>Operating environment</b>	Temperature: 5°C to 32°C; Relative humidity: 15% to 85% RH, non-condensing; Altitude: ≤ 3,100 m
	<b>Storage</b>	Temperature: 0°C to 35°C; Relative humidity: 5% to 90% RH, non-condensing; Altitude: ≤ 3,100 m
	<b>Acoustics (Pressure/Power)</b>	Printing: 53dB <sup>3</sup> / 6.92B <sup>3</sup> ; Standby: 25.5dB <sup>3</sup> / 4.3B <sup>3</sup>
	<b>Power specifications</b>	<b>Voltage</b>
<b>Power consumption</b>		Printing mode: 705 W Ready mode: 61 W Power saver mode: 9.5 W (Sleep), 2 W (Deep sleep)
<b>Typical Energy Consumption (TEC)<sup>4</sup></b>		2.4 kWh
<b>Environmental compliance</b>		ErP Lot 4 and 6, RoHS-compliant <sup>5</sup> , ENERGY STAR <sup>®</sup> qualified <sup>6</sup> , Blue Angel (Germany) UZ171, WEEE, GS Mark (Germany)
<b>Connectivity</b>		<b>Standard interfaces</b>
<b>Operating Systems</b>	<b>Windows</b>	Microsoft <sup>®</sup> Windows <sup>®</sup> 8 (32/64 bit), Windows 8 RT, Windows 7 (32/64 bit), Windows Vista (32/64 bit), Windows Server 2008 R1 & R2, Windows 8.1 (available in Nov, 2013), Windows XP (32/64 bit), Windows 2003, Windows Cluster Server Environment, Windows 2012 Server
	<b>Macintosh</b>	Macintosh OS 10.5 to 10.8
	<b>Others</b>	SUSE <sup>®</sup> Linux Enterprise Desktop 10, 11; Red Hat Linux Enterprise Desktop 5, 6; Nowell <sup>®</sup> Netware Support; SAP R/3 Release 4.6B onwards; Citrix <sup>®</sup> Presentation Server <sup>™</sup> 4.5, Citrix XenApp 5.0 to 6.5
<b>Supported languages</b>	English, French, German, Italian, Spanish, Dutch, Danish, Norwegian and Swedish	
<b>Product certifications</b>	<b>Safety certifications</b>	IEC/EN60950-1:2005 2nd edition (International); EN60950-1:2006 2nd edition; IEC60825-1 (Laser); SEMKO; CE Mark (EU); cTUVus; FDA/DHHS (21CFR, Chapter 1, Subchapter J)
	<b>Other certifications</b>	CE mark (EU countries) EMC/Safety Standard; EN55022:2006 + A1:2007 Class B; EN61000-3-2:2006; EN 61000-3-3:1995+A1:2001+A2:2005; EN55024:1998+A1:2001+A2:2003; FCC CFR Title 47, Part 15 Class B (USA); ICES-003, Issue 4 (Canada); WHQL, Citrix, SAP, Novell, USB, WiFi, Google Cloud Print, Apple Airprint
<b>Contents in box</b>	Dell Colour Printer – C2660dn, Ship-With Black Cartridge and Colour (Cyan, Magenta, Yellow) Cartridges (1,200-page yield <sup>1</sup> ), Power cord, Quick Setup Guide, Software and Instructions CD, Important Information	

1. Toner yield based on testing in accordance with ISO/IEC 19798. Yields vary with usage and environmental conditions.

2. For copy of Limited Hardware Warranty, write Dell Products, Dell House, The Boulevard, Cain Road, Bracknell, Berkshire, RG12 1LF, UK or see [www.dell.com/warranty](http://www.dell.com/warranty). For warranty information for other countries, see website: [www.dell.com/servicescontracts](http://www.dell.com/servicescontracts) and then select the country. Service may be provided by third party. Technician will be dispatched if necessary following phone-based troubleshooting. Subject to parts availability, geographical restrictions and terms of service contract. Service timing dependent upon time of day call placed to Dell. Defective unit must be returned. Replacements may be refurbished.

3. Tested in accordance with ISO 7779 and reported in accordance with ISO 9296. Acoustics - Declared noise emission values of computer and business equipment

4. For the Typical Energy Consumption value calculation details please visit: [www.energystar.gov/ia/products/fap/IE\\_TEC\\_Test\\_Procedure.pdf](http://www.energystar.gov/ia/products/fap/IE_TEC_Test_Procedure.pdf)

5. Meets the requirements of the EU RoHS Directive 2011/65/EU on the Restriction of the use of certain Hazardous Substances (RoHS).

6. For details on energy efficiency of ENERGY STAR<sup>®</sup> qualified products, refer to: [www.energystar.gov](http://www.energystar.gov)

# Product Specifications

<b>Printer specifications</b>	<b>Print speed (Mono/Colour)</b>		
	Simplex (600 x 600 dpi)	Up to 27 ppm <sup>1</sup> (A4)	
	Duplex (600 x 600 dpi)	Up to 18 ppm <sup>1</sup> (A4)	
	<b>First page out time from Ready state</b>	Less than or equals to 14 seconds (simplex)	
	<b>Print resolution</b>	600 x 600 dpi (up to 2400 dpi image quality)	
	<b>Operation panel</b>	LCD: 4 Lines Bitmap based Mono LCD, font scalable; 10-key Numeric pad; Viewing Area: 1.97" (49.97 mm) (W) x 0.8" (19.17 mm)(L); Backlight: White backlight; Status LED: 1 LED (combination "Data Green/Error Amber") Power Saver Button (Light on/off)	
	<b>Print language</b>		
	Printer Driver Language	PCL6, PostScript™ 3, XPS	
	Printer data stream (FW)	PCL5C, PCL 6 (PCLXL 2.1), PostScript 3	
	<b>Fonts</b>	HP PCL® 6 Emulation: 80 scalable fonts PostScript® Level 3 : 80 scalable fonts	
	<b>Processor speed</b>	525 MHz	
	<b>Memory</b>	512 MB <sup>2</sup>	
	<b>Maximum duty cycle</b>	Up to 50,000 pages per month <sup>3</sup>	
	<b>Recommended monthly print volume</b>	450 - 4,000 pages per month	
<b>Mobile printing support</b>	Dell Mobile Print <sup>4</sup> (Android™ OS), AirPrint <sup>5</sup> (iOS). Google Cloud Print		
<b>Printer management</b>	Dell Printer Configuration Web Tool, Dell ColourTrack 2.2, Dell Toner Management System, Dell Open Print Driver (OPD), Dell OpenManage™ Printer Manager v2 (OMPM)		
<b>Security features</b>	<b>Print Job Management</b>	Secure Print with 4 Digit Pin, Virtual Mail Box, Print Job disable/enabling scheduling	
	<b>Network Authentication</b>	SNMP V3	
	<b>Data Encryption</b>	Ipssec (Ikev1)/Pre-shared key	
	<b>Access Control Management</b>	Embedded Web Server access control of Enable/Disable of network port & Protocol , printer settings & report access, Operator Panel access	
	<b>I/O Access control</b>	Protocol base (Network)	
	<b>Colour Control</b>	Dell ColourTrack 2.2	
	<b>Lock type and location</b>	Kensington lock for printer, primary input tray, optional input drawer and accessories (wireless dongle)	
	<b>Standard media types, sizes and paper weights</b>	<b>Standard tray</b>	
Media types and weights supported		Plain paper (60-90 gsm), Thicker paper (91-105 gsm), Heavier paper (106-216 gsm), Preprint (60-163 gsm), Letterhead (60-163 gsm), Prepunched (60-105 gsm), Cardstock (106-216 gsm), Coated paper (95-216 gsm), Recycled paper	
Media sizes		A4 Short Edge Feed (SEF), B5 SEF, A5 SEF, US Letter SEF, Executive SEF, Folio (8.5" x 13") SEF, US Legal SEF Custom size: 148 mm – 215.9 mm (W), 210 mm – 355.6 mm (L)	
<b>Multipurpose tray</b>			
Media types and weight supported		Plain paper (60-163 gsm), Preprinted (60-163 gsm), Letterhead (60-163 gsm), Prepunched (60-105 gsm), Cardstock (106-216 gsm), Heavier paper (164-216 gsm), Coated paper (95-216 gsm), Recycled paper, Labels, Envelope, Hagaki cards	
Media sizes		A4 SEF, B5 SEF, A5 SEF, US Letter SEF, Executive SEF Folio (8.5" x 13") SEF, US Legal SEF, Envelope Com-10 (SEF), Envelope Monarch (SEF), Envelope DL (LEF/SEF), C5 (SEF), Post Card Custom size: 76.2 mm – 216 mm (W), 127 mm – 355.6 mm (L)	
<b>Optional Tray</b>			
Media types and weights supported		Plain paper (60-90 gsm), Thicker paper (91-105 gsm), Heavier paper (106-216 gsm), Preprint (60-163 gsm), Letterhead (60-163 gsm), Prepunched (60-105 gsm), Cardstock (106-216 gsm), Coated paper (95-216 gsm), Recycled paper, Labels	
Media sizes		A4 SEF, B5 SEF, A5 SEF, US Letter SEF, Executive SEF, Folio (8.5" x 13") SEF, US Legal SEF Custom size: 148 mm – 215.9 mm (W), 210 mm – 355.6 mm (L)	
<b>Duplexer</b>			
Media types and weights supported		Plain paper (60-90 gsm), Thicker paper (91-105 gsm), Heavier paper (106-163 gsm), Recycled paper, Coated paper (95-163 gsm)	
Media sizes		US Letter SEF, Executive SEF, A5 SEF, A4 SEF, B5 SEF, US Legal 13 SEF, US Legal 14 SEF Custom size: 148.5 mm – 215.9 mm (W), 210 mm – 355.6mm (L)	
<b>Printable area</b>		207.9 mm x 347.6 mm	
<b>Paper handling</b>		<b>Standard input sources</b>	250-sheet standard tray, 150-sheet multipurpose tray
	<b>Additional input capacity</b>	550-sheet option drawer	
	<b>Maximum input capacity</b>	950 sheets (via addition of one 550-sheet optional drawer)	
	<b>Duplexer</b>	Automatic two-sided printing (default)	
	<b>Standard output capacity</b>	250 sheets	
	<b>Maximum output capacity</b>	250 sheets	

1. Measured in accordance with ISO IEC 27434/35 methodology. Actual print speeds will vary with use.

2. 1.MB means 1 million bytes, 1 GB means 1,000 megabytes or 1,000,000,000 bytes; total accessible capacity varies depending on operating environment.

3. Duty cycle is defined as the maximum number of imaged outputs a device could deliver in a month. This metric provides a comparison of robustness in relation to other Dell printers and multifunction printers.

4. The printer and the mobile device must be connected on the same network.

5. AirPrint-enabled printers work with iPad, iPhone (3GS or later), and iPod touch (3rd generation or later) running iOS 4.2 or later.

©2013 Dell Corporation Limited. Dell, the Dell logo and Dell Toner Management System are registered trademarks or trademarks of Dell Inc. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Dell disclaims proprietary interest in the marks and names of others. Microsoft, Windows and Windows NT are registered trademarks or trademarks of Microsoft Corporation. Android and Google Cloud Print are registered trademarks of Google Inc. iPad, iPhone, iPod, and iPod touch are trademarks of Apple Inc., registered in the U.S. and other countries. AirPrint and the AirPrint logo are trademarks of Apple Inc. Dell Products, Dell House, The Boulevard, Cain Road, Bracknell, Berkshire, RG12 1LF, UK. Product availability varies by country. Please contact your Dell representative for more information.

Specifications are subject to change without notice. Dell cannot be responsible for errors and omissions in typography or photography.