



DGE-530T

DGE-530T copper Gigabit PCI card for desktop PC

10/100/1000Mbps Copper Gigabit PCI Card for PC

The DGE-530T is a 10/100/1000Mbps copper Gigabit PCI card for desktop PC. Installable in a PC equipped with PCI expansion slots, this card turns a desktop computer into a high-bandwidth Gigabit workstation or a server running at 2000Mbps full-duplex speed.

High-performance Gigabit Speed

Capable of running at full-duplex Gigabit speed, this card gives your PC 2000Mbps data transmission on your existing Cat. 5 twisted-pair network cable. As an inexpensive alternative solution to fiber-optic, the card allows you to instantly upgrade to Gigabit without requiring you to install new, expensive fiber cables. The card supports 10/100/1000Mbps network speed auto-sensing and full/half duplex auto-negotiation.

VLAN to Improve Performance and Security

The card provides on-board screening of VLANs Tagged Ethernet frames, allowing your PC to be configured with a VLAN-supported switch. Your PC can be part of a VLAN network, where domains are segmented up to enhance performance and security.

Flow Control to Minimize Packet Loss

The card's embedded flow control and independent FIFO for each port provide a means to protect against possible data loss during transmission on the network. When connected to a Gigabit switch Supporting flow control, the card receives signals from the switch regarding buffer overrun during peak usage periods. The card then delays transmission until the switch is ready again to accept new data.

Small Form Factor, Lower Power Requirement

Using a single chip solution, this card is very small in size and consumes very little power of your computer system.

Key Features

- Copper Gigabit connection for PC
- 10/100/1000Mbps auto-sensing speeds
- 2000Mbps Gigabit full duplex support
- 32-bit Bus Master operation
- Supports PCI clock speed at 33MHz
- 802.3x Flow Control for fast, reliable data transmission
- Supports ACPI 2.0 WOL power management
- Supports SNMP v.1
- Supports 802.1Q VLAN Tagging *
- PCI 2.2 plug-and-play
- Universal bus 3.3V & 5V support
- Runs Win98 SE, 2000, ME, NT, XP, NetWare, Linux, Unix
- Very small size, very low power consumption

* Available in next version.

DGE-530T

Technical Specifications

10/100/1000Mbps PCI Card

General

Standards

- IEEE 802.3 10BASE-T Ethernet
- IEEE 802.3u 100BASE-TX Fast Ethernet
- IEEE 802.3ab 1000BASE-T Gigabit Ethernet
- ANSI/IEEE 802.3 NWay auto-negotiation
- PCI local bus 2.2 specifications
- Universal Bus Support 3.3V, 5V
- IEEE 802.3x Flow Control
- IEEE 802.1Q VLAN tagging *

Topology

Star

Protocol

CSMA/CD

Data Transfer Rates

- Ethernet:
 - 10Mbps (half duplex)
 - 20Mbps (full duplex)
- Fast Ethernet:
 - 100Mbps (half duplex)
 - 200Mbps (full duplex)
- Gigabit Ethernet:
 - 2000Mbps (full duplex)

Network Cables

- 10BASE-T:
 - UTP Cat. 3, 4, 5 (100 m max.)
 - EIA/TIA-586 100-ohm STP (100 m max.)
- 100BASE-TX, 1000BASE-T:
 - UTP Cat. 5 (100 m max.)
 - EIA/TIA-568 100-ohm STP (100 m max.)

Diagnostic LED Report

- Link/Active
- Full duplex
- 1000Mbps
- 100Mbps

Flow Control

- IEEE 802.3x flow control per for full duplex
- Back pressure in half duplex

System Setup

IRQ

Allocated by system

I/O Address

Allocated by system

Full/half Duplex

- Full duplex only (1000Mbps)
- Full/half duplex (10/100Mbps)

Environmental & Physical

Operating Temperature

0° - 40° C

Storage Temperature

-25° - 55° C

Humidity

5% - 90% non-condensing

Emission

- FCC Class B
- CE Class B
- C-Tick
- BSMI Class B

Network O.S. Support

- Microsoft Windows NT, 2000, 98SE/ME, XP
- Novell Netware 4.2, 5.x, 6.x, ODI 1.11
- Linux 2.0, 2.2 *
- SCO UnixWare 7.0 *
- SCO OpenServer 5.05 *
- Red hat Linux 7.3 (kernel 2.4.18 - 3) and later



ACN 052 202 838

Ordering Information

Copper Gigabit PCI Card

DGE-530T 10/100/1000Mbps PCI card

D-Link®

Specifications subject to change without prior notice.
D-Link is a registered trademark of D-Link Corporation/D-Link System Inc. All other trademarks belong to their proprietors.

U.S.A	TEL: 1-949-788-0805	FAX: 1-949-753-7033
Canada	TEL: 1-905-8295033	FAX: 1-905-8295095
Europe	TEL: 44-20-8731-5555	FAX: 44-20-8731-5511
Germany	TEL: 49-6196-77990	FAX: 49-6196-7799300
France	TEL: 33-1-30238688	FAX: 33-1-30238689
Benelux	TEL: 31-10-2045740	FAX: 31-10-2045880
Italy	TEL: 39-2-2900-0676	FAX: 39-2-2900-1723
Iberia	TEL: 34-93-4090770	FAX: 34-93-4910795
Sweden	TEL: 46-(0)8564-61900	FAX: 46-(0)8564-61901
Norway	TEL: 47-22-309075	FAX: 47-22-309085
Denmark	TEL: 45-43-969040	FAX: 45-43-424347
Finland	TEL: 358-9-2707-5080	FAX: 358-9-2707-5081
Singapore	TEL: 65-6774-6233	FAX: 65-6774-6322
Australia	TEL: 61-2-8899-1800	FAX: 61-2-8899-1868
Japan	TEL: 81-3-5434-9678	FAX: 81-3-5434-9868
China	TEL: 86-10-8518-2533	FAX: 86-10-8518-2250
India	TEL: 91-22-652-6696	FAX: 91-22-652-8914
Middle East	TEL: 9714-8834234	FAX: 9714-8834394
Turkey	TEL: 90-212-335-2553	FAX: 90-212-335-2500
Chile	TEL: 56-2-232-3185	FAX: 56-2-232-0923
Brasil	TEL: 55-11-3094-2910	FAX: 55-11-3094-2921
South Africa	TEL: 27(0)1266-52165	FAX: 27(0)1266-52186
Russia	TEL: 7-095-737-3389	FAX: 7-095-737-3390
Taiwan	TEL: 886-2-2910-2626	FAX: 886-2-2910-1515
D-Link Corp.	TEL: 886-2-2916-1600	FAX: 886-2-2914-6299



RECYCLABLE
Rev. 01 (Mar. 2003)
Printed in Taiwan

* Available in next version.